

PYLE®

AUDIO.COM



2013

Complete Product Catalog



PLMC592



PLCM9200



PYLE®

Pyle Audio will give your eyes and ears something to love. For over 30 years, we've been dedicated to providing affordable, technologically advanced and versatile electronics. We'll help you find the solution to improve your audio and video experiences in the car and on the road! Get a taste of the future when the wheels are rolling and ride into the future with Pyle Audio.

2013

www.pyleaudio.com

Complete Product Catalog

Table of Contents:

Pyle Car

Mobile Video/Navigation	4
Headrest Monitors	8
Roof Mount / Wall Mount Monitors	13
Wireless Headphones	18
Power Inverters / HDTV Tuner / Wall Mounts	19
Step-Down Converters	21
Backup Cameras	22
CD/MP3 Player Headunits	27
Cigarette Lighter Accessories	30
Amplifiers	32
Equalizers	36
Speakers	37
Tweeters	45
Subwoofers	46
Subwoofer Enclosures / Bass Boxes	50
Subwoofer Tubes	55
Capacitors	56
Ground Loop Isolators / iPod Audio Interfaces	57
Speaker Wiring / Converters / Distribution Amps	59
Vehicle Security Systems	62
Motorcycle Speaker Kits	63
HID Driving Lights	67

Pyle Marine

CD/DVD Receivers	68
Headunits / Speaker Combo Kits	72
Water Resistant Housings / Stereo - RCA Adaptors	75
Waterproof Amplifiers	76
Capacitors / Amplifier Kits	78
Marine Speakers	79
Marine Subwoofers	87

2013 Complete Product Catalog

PIDNVC51 6.5" Double DIN In-Dash Touchscreen TFT/LCD Monitor w/ Bluetooth/GPS/DVD/CD/MP3/MP4/USB/SD/

- 6.5 " 16:9 Wide Screen TFT LCD Display
- Touchscreen Operation
- With Built-in Bluetooth Technology you can stream audio directly from your hand-held Bluetooth enabled device with crystal clear wireless performance (iPhone, Droid, Blackberry, iPads, Tablets, Etc.)
- Picture Control: Brightness/Contrast/Hue/Chrome
- USB /SD-MMC Card Reader MP4-JPEG/MP3 WMA Playback
- Repeat/Program/Random/Intro Play
- Treble/Bass/Balance/Fader/Volume Control

- AM/FM Stereo Receiver
- Electronic Anti-Shock
- AUX Rear and A/V Input
- Auto Memory Store/Preset Scan
- Support DVD/VCD/CD/CD-R/CD-RW/MP3
- Parking Video Output
- 30 Preset Stations Memory
- 320 Watts Total Output (4 x 80 Watts)
- 4 Channel RCA Preamp Output plus Subwoofer Output
- Card-sized Full Function Remote Control

NEW!
for 2013



PIDNV781 7" Double DIN In- Dash Touch Screen TFT/LCD Monitor w/ DVD/CD/MP3/MP4/USB/SD/AMFM/RDS/Bluetooth

- 7" 16:9 Wide Screen TFT LCD Display
- Touch Screen (Graphic Screen Allows Easy Control of Operations by Touch)
- With Built-in Bluetooth Technology you can stream audio directly from your hand-held bluetooth enabled device with crystal clear wireless performance (iPhone, Droid, Blackberry, iPads, Tablets, Etc.)
- Picture Control: Brightness/Contrast/Hue/Chrome
- USB/SD-MMC Card Reader MP4-JPEG/MP3 WMA Playback

- Repeat/Program/Random/Intro Play
- Treble/Bass/Balance/Fader/Volume Control
- AM/FM Stereo Receiver
- Electronic Anti-Shock
- AUX Rear Input
- Auto Memory Store/Preset Scan
- Support DVD/VCD/CD/CD-R/CD-RW/MP3
- Parking Video Output
- 30 Preset Stations Memory
- 320 Watts Total Output (4 x 80 Watts)



PIDN70U 7" Double Din TFT Touch Screen AM/FM DVD/VCD/CD/MP3/MP4/CD-R/USB/SD-MMC Card Slots

- DVD/VCD/MPEG4/MP3/CD/CD-RW Compatible
- Motorized Slide Down Front Panel
- Treble/Bass/Balance/Fader/Encoder Volume
- PLL Synthesizer Tuner
- Auto Store/Preset Scan
- AM/FM-MPX 2 Band Radio
- 30 Station Memory (18FM/12AM)
- Built-IN 7" (16:9) TFT Color Monitor
- Touch Screen Control Operation

- Res. 1440 x 324 Pixels Brightness: 200 cd/m2
- On Screen Display/Title/Time/Chapter/Subtitle
- Double-DIN Chassis
- PAL/NTSC Color System
- Anti-Shock Mechanism ESP Function
- LO/DX & ST/MO Selector
- Repeat/Intro Random
- Clock Function Mute Control
- RCA Line Out Preset EQ



PIDN72BT 7" Double Din TFT TOUCH SCREEN DVD/VCD/CD/MP3/MP4/CD-R/USB/SD-MMC Card Slots w/ Bluetooth

- DVD/VCD/MPEG4/MP3/CD/CD-RW Compatible
- Motorized Slide Down Front Panel
- With Built-in Bluetooth Technology you can stream audio directly from your hand-held bluetooth enabled device with crystal clear wireless performance (iPhone, Droid, Blackberry, iPads, Tablets, Etc.)
- Treble/Bass/Balance/Fader/Encoder Volume
- PLL Synthesizer Tuner
- Bluetooth A2DP Support
- Auto Store/Preset Scan

- AM/FM-MPX 2 Band Radio
- 30 Station Memory (18FM/12AM)
- Built-IN 7" (16:9) TFT Color Monitor
- Touch Screen Control Operation
- Res. 1440 x 324 Pixels Brightness: 200 cd/m2
- On Screen Display/Title/Time/Chapter/Subtitle
- Double-DIN Chassis
- PAL/NTSC Color System
- Anti-Shock Mechanism ESP Function
- LO/DX & ST/MO Selector



PIDN731 7" Double DIN TFT Touch Screen DVD/VCD/CD/MP3/MP4/CD-R/USB/SD-MMC Card Slot/AM/FM/iPod Connector

- DVD/VCD/MPEG4/MP3/CD/CD-RW Compatible
- Motorized Slide Down Front Panel
- Treble/Bass/Balance/Fader/Encoder Volume
- PLL Synthesizer Tuner
- Auto Store/Preset Scan
- AM/FM-MPX 2 Band Radio
- 30 Station Memory (18FM /12AM)
- Built-In 7"(16:9) TFT Color Monitor
- Touch Screen Control Operation
- Resolution: 1440 x 234 Pixels: Brightness: 200 cd/m2

- On screen Display: Title, Time, Chapter, Subtitle
- Double-DIN Chassis
- PAL/NTSC Color System
- Anti-Shock Mechanism-ESP Function
- LO/DX & ST/MO Selector
- Repeat/Intro/Random
- Clock Function, Mute Control
- RCA Line Out, Preset EQ
- Subwoofer Output
- Selectable View Angle



PIDN4BT

7" Double DIN TFT Touch Screen DVD/VCD/CD/MP3/MP4/CD-R/USB/SD-MMC Card Slot

- DVD/VCD/MPEG4/MP3/CD/CD-RW Compatible
- Motorized Slide Down Front Panel
- With Built-in Bluetooth Technology you can stream audio directly from your hand-held bluetooth enabled device with crystal clear wireless performance (iPhone, Droid, Blackberry, iPads, Tablets, Etc.)
- Treble/Bass/Balance/Fader/Encoder Volume
- PLL Synthesizer Tuner
- Bluetooth A2DP Support
- Auto Store/Preset Scan
- AM/FM-MPX 2 Band Radio
- 30 Station Memory (18FM /12AM)
- Built-In 7" (16:9) TFT Color Monitor
- Touch Screen Control Operation
- Resolution: 1440 x 234 Pixels: Brightness: 200 cd/m2
- On screen Display: Title, Time, Chapter, Subtitle
- Double-DIN Chassis
- PAL/NTSC Color System
- Anti-Shock Mechanism-ESP Function
- LO/DX & ST/MO Selector
- Repeat/Intro/Random
- Clock Function, Mute Control



PIDN790

7" Double Din TFT Touch Screen AM/FM/AUX For iPod & MP3 Input/MP4USB/SD-MMC Card Slot

- 7" TFT/LCD Touch Panel
- Treble/Bass/Balance/Fader/Encoder Volume
- Auto Store/Preset Scan • AM/FM-MPX 2 Band Radio • 30 Station Memory (18FM/12AM)
- Touch Screen Control Operation
- Res. 800x480 Pixels Brightness: 400 cd/m2
- On Screen Display/Title/Time/Chapter/Subtitle
- Double-DIN Chassis
- PAL/NTSC Color System
- LO/DX & ST/MO Selector & PLL Synthesizer Tuner
- Repeat/Intro Random
- Clock Function Mute Control
- RCA Line Out Preset EQ & Subwoofer Output
- Selectable View Angle
- A/V Input & A/V Output
- SD/MMC Card Slot-USB Connector
- Wireless Remote Control
- Rear Camera Output-Parking Video Input
- 320 Watts (4x80W)
- Dimensions: 7.26" x 4.08" x 6.36"



PIDN695

6.95" Double-DIN Touchscreen Video DVD/MP4/MP3/CD Player With Hands-Free Bluetooth, GPS

- Touchscreen Control Screen
- Picture control: Brightness/contrast/hue/chrome
- USB/SD-MMC card reader
- MP4-JPEG/MP3 WMA playback
- Repeat/program/random/intro play
- Treble/bass/balance/fader/volume control
- AM/FM stereo receiver
- Electronic anti-shock
- Auto memory store/preset scan
- Support DVD/VCD/CD/CD-R/CD-RW/MP3
- Parking video output & Aux rear input
- 30 preset stations memory
- 320 watts total output (4x80 watts)
- Bluetooth function auto muting feature, hands free talking capabilities
- 4 channel RCA preamp output/subwoofer output
- Card-sized full function remote control

NEW!
for 2013



PIDN720

7" Single DIN In-Dash Motorized Touch Screen TFT/LCD Digital Monitor

- In Dash 7" 16:9 High Definition Wide TFT LCD
- Digital Video Player/VCD/MPEG4/MP3/CD/CD-R CD-RW Compatible
- AM/FM-MPX 2 Band Radio
- PLL Synthesizer Tuner
- Auto Store/Preset Scan
- 30 Station Memory
- Touch Screen Control Operation
- Full Motorized Screen Telescopes out and Up Including Front to Back Angling
- Detachable Front Panel
- LCD Digital Display
- On Screen Display Title, Time, Chapter, Subtitle
- Treble, Bass, Balance, Fader, Encoder, Volume
- PAL/NTSC Color System
- Resolution: 1440 x 234 Pixels
- Brightness: 400 NITS
- Last Position Memory
- ESP (Electronic Shock Protection)
- Anti-shock Mechanism
- LO/DX & ST/MO Selector
- Repeat/Intro/Random
- Direct Connection of Alternate Audio/ Video Source Through AUX Line Input Jack (MP3/Digital Video)

NEW!
for 2013



PIDN76X

7" Single DIN In-Dash Motorized Touch Screen TFT/LCD Monitor w/ DVD/CD/MP3/MP4/USB/SD/AM-FM Player

- AM/FM-MPX 2 Band Radio
- PLL Synthesizer Tuner
- Auto Store/Preset Scan
- 30 Station Memory
- Touch Screen Control Operation
- Full Motorized Screen Telescopes Out And Up
- LCD Digital Display
- On Screen Display Title, Time, Chapter, Subtitle
- Treble/Bass/Balance/Fader/Encoder Volume
- Pal/NTSC Color System
- Resolution: 1440x234 Pixels
- Brightness: 400 Nits
- Last Position Memory
- ESP (Electronic Shock Protection)
- Anti-Shock Mechanism
- Lo/DX & St/Mo Selector
- Direct Connection Of Alternate Audio/Video Source Through Aux line
- Input Jack (Mp3/Dvd/Cd)
- Repeat/Intro/Random
- Clock Function
- Mute Control

NEW!
for 2013



2013 Complete Product Catalog

PLT578DUB 7" Single DIN In-Dash Detachable Motorized Touch Screen TFT/LCD

- DVD/VCD/MPGE4/MP3/CD-RW Compatible
- Am/Fm-MPX 2 Band Radio
- Built-in Bluetooth Technology PLL Synthesizer Tuner
- Auto Store/Preset Scan
- 30 Station Memory
- Touch Screen Control Operation
- Full Motorized Screen Telescopes Out And Up
- LCD Digital Display
- On Screen Display Title, Time, Chapter, Subtitle
- Treble/Bass/Balance/Fader/Encoder Volume
- Pal/NTSC Color System
- Relolution: 1440x234 Pixels
- Brightness: 400 Nits
- Last Position Memory
- ESP (Electronic Shock Protection)
- Anti-Shock Mechanism
- Lo/Dx & St/Mo Selector



PLD7MU 7" Single DIN TFT Touch Screen DVD/MP3/MP4/CD-R/USB/SD/AM/FM/RDS Receiver

- DVD/MPEG4/MP3/MP4/DIVX/CD/CD-R/CD-RW Compatible
- Motorized Drop-Down Fixed Front Panel
- Full Front Panel Detachable
- Treble/Bass/Balance/Fader/Encoder/ Volume Control
- PLL Synthesizer Tuner
- Auto Store/Preset Scan
- AM/FM-MPX 2 Band Radio
- Switchable USA/Europe Radio Frequency
- 30 Station Memory (18FM/12AM)
- Built-In 7" (16:9) TFT Color Monitor
- Touch Screen Control Operation
- Resolution: 2400x480 Pixels/ Brightness: 500nits
- On Screen Display Title/Time/Chapter/Subtitle/Angle
- Dolby Digital Coaxial Outputs
- ESP Function Anti-Vibration/Shock Protection
- LO/DX & ST/MO Selector
- Repeat/Intro/Random
- Clock Function/ Mute Control
- Front Panel AUX Input (Ipod/MP3)
- RCA Line Out/ Preset EQ
- Subwoofer Output



PL78DLB 7" Touchscreen Motorized Detachable Digital Receiver & Bluetooth System

- AM/FM-MPX 2 Band Radio
- PLL Synthesizer Tuner
- Auto Store/Preset Scan
- 30 Station Memory
- Touch Screen Control Operation
- Full Motorized Screen Telescopes Out And Up
- LCD Digital Display
- On Screen Display Title, Time, Chapter, Subtitle
- Treble/Bass/Balance/Fader/Encoder Volume
- PAL/NTSC Color System
- Last Position Memory
- ESP (Electronic Shock Protection)
- Anti-Shock Mechanism
- LO/DX & St/Mo Selector
- Direct Connection Of Alternate
- Audio/Video Source Through Aux Line
- Input Jack(Mp3/Dvd/Cd)
- Repeat/Intro/Random
- Clock Function
- Mute Control
- RCA Line Out
- Built-in Bluetooth
- Sub-Woofers
- A/V Input & A/V Output

NEW!
for 2013



PL75DL 7" Touchscreen Motorized Detachable Digital Receiver

- AM/FM-MPX 2 Band Radio
- PLL Synthesizer Tuner
- Auto Store/Preset Scan
- 30 Station Memory
- Touch Screen Control Operation
- Full Motorized Screen Telescopes Out And Up
- LCD Digital Display
- On Screen Display Title, Time, Chapter, Subtitle
- Treble/Bass/Balance/Fader/Encoder Volume
- PAL/NTSC Color System
- Last Position Memory
- ESP (Electronic Shock Protection)
- Anti-Shock Mechanism
- LO/DX & St/Mo Selector
- Direct Connection Of Alternate
- Audio/Video Source Through Aux Line
- Input Jack(Mp3/Dvd/Cd)
- Repeat/Intro/Random
- Clock Function
- Mute Control

NEW!
for 2013



PLD10BT 10.1" Motorized TFT/LCD Touch Screen Detachable Display DVD/VCD/CD/MP3/CD-R/USB/AM/FM/RDS Receiver

- DVD/VCD/MPEG4/MP3/DIVX/CD/CD-RW Compatible
- Motorized & Full Detachable 10.1 Front Touch Screen Panel
- With Built-in Bluetooth Technology you can stream audio directly from your hand-held bluetooth enabled device with crystal clear wireless performance(iPhone, Droid, Blackberry, iPads, Tablets, Etc.)
- Treble/Bass/Balance/Fader/Encoder
- Volume PLL Synthesizer Tuner
- Auto Store/Preset Scan
- AM/FM-MPX 2 Band Radio
- 30 Station Memory(18FM/12AM)
- 10.1 Inch(16:9) Tft Detachable Color Monitor
- Touch Screen Control Operation
- Resolution: 1024x600 Pixels
- Brightness: 400nits
- On Screen Display Title, Time, Chapter, Subtitle & Angle

NEW!
for 2013



PID7MU 7" TFT Touch Screen DVD/CD/MP3/CD-R/USB/AM/FM/RDS Receiver

- DVD/MPGE4/MP3/CD/CD-R/CD-RW Compatible
- Motorized Slide Down Detachable Front Panel
- Treble/Bass/Balance/Fader/Encoder Volume
- PLL Synthesizer Tuner
- Auto Store/Preset Scan
- AM/FM-MPX 2 Band Radio
- 30 Station Memory(18FM/12AM)
- Built In 7 Inch(16:9) TFT Color Monitor
- Touch Screen Control Operation
- Resolution: 1440x234 Pixels
- Brightness: 400nits
- On Screen Title, Time, Chapter,Subtitle,Angle
- Dolby Digital Coaxial Outputs PAL/NTSC System Color
- ESP Function Anti-Shock Mechanism
- LO/DX & ST/MO Selector
- Repeat/Intro/Random
- Clock Function
- Mute Control
- RCA Line Out
- Preset EQ
- Subwoofer Output
- Selectable View Angle
- A/V Input & A/V Output



PIT56DU 7" Touch Screen Motorized Detachable TFT/LCD Monitor With DVD/CD/MP3/AM/FM Receiver

- DVD/VCD/MPGE4/MP3/CD-RW Compatible
- AM/FM-MPX 2 Band Radio
- PLL Synthesizer Tuner
- Auto Store/Preset Scan
- 30 Station Memory
- Touch Screen Control Operation
- Full Motorized Screen Telescopes Out And Up
- LCD Digital Display
- On Screen Display Title, Time, Chapter, Subtitle
- Treble/Bass/Balance/Fader/Encoder Volume
- PAL/NTSC Color System
- Relolution:1440x234 Pixels
- Brightness: 400 Nits
- Last Position Memory
- ESP (Electronic Shock Protection)
- Anti-Shock Mechanism
- LO/DX & St/Mo Selector
- Direct Connection Of Alternate
- Audio/Video Source Through Aux Line
- Input Jack(Mp3/Dvd/Cd)



PID7BT 7" TFT Touch Screen DVD/VCD/CD/MP3/CD-R/USB/AM/FM/RDS Receiver

- DVD/MPGE4/MP3/CD/CD-R/CD-RW Compatible
- Motorized Slide Down Detachable Front Panel
- With Built-in Bluetooth Technology you can stream audio directly from your hand-held bluetooth enabled device with crystal clear wireless performance(iPhone, Droid, Blackberry, iPads, Tablets, Etc.)
- Treble/Bass/Balance/Fader/Encoder
- Volume PLL Synthesizer Tuner
- Auto Store/Preset Scan
- AM/FM-MPX 2 Band Radio
- 30 Station Memory(18FM/12AM)
- Built In 7 Inch(16:9) Tft Color Monitor
- Touch Screen Control Operation
- Resolution: 1440x234 Pixels
- Brightness: 400nits
- On Screen Display Title, Time, Chapter, Subtitle & Angle
- Dolby Digital Coaxial Outputs
- PAL/NTSC Color System
- Anti-Shock Mechanism
- ESP Function
- LO/DX & ST/MO Selector
- Repeat/Intro/Random



PID7F 7" Touch Screen Slide Out TFT/LCD Monitor with DVD/CD/MP3/AM/FM Receiver

- DVD/VCD/MPGE/MP3/CD-RW Compatible
- AM/FM-MPX 2 Band Radio
- PLL Synthesizer Tuner
- Auto Store/ Preset Scan
- Touch Screen Comntrol Operation
- PAL/NTSC Color System
- Resolution: 1440 x 234 Pixels
- Last Position Memory
- ESP (Electronic Shock Protection)
- Anti-Shock Mechanism / Preset EQ
- ST/MO Selector / Repeat/Intro/Random
- RCA Line Out
- A/V Inout & A/V Output
- Rear Camer Input & USB Connector
- SD/MMC Card Slot• 320 Watts Total Outputs (4 x 80 Watts)
- Dimensions: 7.01" W x 1.98" H x 6.54" Dz



PID40MU 4.3" Touch Screen TFT/LCD Monitor w/ Digital Video Player/CD/MP3/USB/SD/AM/FM/RDS Player

- Built In 4.3 Inch Wide TFT Color Monitor
- Digital Video Player/VCD/MPGE4/MP3/CD/CD-R/CD-RW Compatible
- AM/FM-MPX 2 Band Radio
- PLL Synthesizer Tuner
- Auto Store/Preset Scan
- 30 Station Memory
- Touch Screen Control Operation
- Flip Down Detachable Front Panel
- On Screen Display Title, Time, Chapter, Subtitle
- Treble/Bass/Balance/Fader/Encoder Volume
- PAL/NTSC Color System
- Last Position Memory
- ESP (Electornic Shock Protection)
- Anti-Shock Mechanism
- LO/DX & ST/MO Selector
- Repeat/Intro/Random
- Direct Connection Of Alternate
- AUDIO/VIDEO Source Through AUX Line
- Input Jack(MP3/Digital Video Player/CD)
- Clock Function
- Mute Control
- RCA Line Out
- PRset EQ



2013 Complete Product Catalog

PLD33MU 3" TFT/LCD Monitor DVD/VCD/MP3/MP4/CDR/SD/USB Player & AM/FM

- 3" Inch 16:9 Wide Screen TFT/LCD Display
- Flip-Down & Full Detachable Front Panel
- Res. 960x240 Pixels/ Brightness: 400nits
- Treble/Bass/Balance/Fader/Encoder Volume Control
- Picture Control: Brightness/Contrast/Chroma/Hue
- Electronic Screen Angle/Position Memory
- USB/SD-MMC Card Reader MP4-JPEG/MP3 WMA-Playback
- Repeat/Program/Random/Intro Play
- AM/FM-MPX Stereo Radio
- Clock Function
- ESP Function Anti-Vibration/Shock Protection

- Auto Memory Store/Preset/Scan
- Support DVD/VCD/CD/CD-R/CDRW/MP3
- Parking Video Output
- DSP Equalizer Control-Rock-Classic-Pop
- 30 Preset Stations Memory (18FM/12AM)
- 4 Channel RCA Preamp Output
- Subwoofer Output
- Full Function Wireless Remote Control
- NTSC PAL Compatible
- 320 Watts Total Output (4 X 80 Watts)
- Dimensions 7.09"W 1.97"H 6.02"D



PL3MP4 3" TFT/LCD Monitor MP3/MP4/SD/USB Player & AM/FM Receiver

- 3" Inch 16:9 Wide Screen TFT/LCD Display
- Full Detachable Front Panel
- Res. 400x240 Pixels/ Brightness: 400nits
- Treble/Bass/Balance/Fader/Encoder Volume Control
- USB/SD-MMC Card Reader MP4-JPEG/MP3 WMA
- AM/FM-MPX Stereo Radio
- ESP Function Anti-Vibration/Shock Protection
- Auto Memory Store/Preset/Scan
- Parking Video Output

- 2 Channel RCA Preamp Output
- Front Video/AUX Input (Ipod/MP3)
- Subwoofer Output
- Full Function Wireless Remote Control
- 240 Watts Total Output (4 X 60 Watts)
- Dimensions 7.09"W 1.97"H 6.14"D



PLD21 Universal Mount DVD/VCD/CDR/CDRW/MP3/USB/SD Reader

- PAL/NTSC Color System
- DVD/VCD/MPEG4/CD/CD-R/CDRW Compatible
- Anti-Shock Mechanism
- Floor/Under-Dash Mounting Brackets
- Repeat/Random Function
- Mute Control
- Dolby Digital Coaxial Out

- ESP Function
- Last Position Memory
- Auto Power On
- USB/SD Slot
- Wireless Remote Control
- DC 12 Volt Power Source



PHR105B=PHR108W 10.2" TFT/LCD Headrest Monitor w/Headrest Stand & Shroud

- 10.2" TFT/LCD Digital Monitor
- 16:9 Wide Screen Format
- High Resolution 1024 x 600
- NTSC/ PAL System Compatible
- 2 Video Input, 1 Audio Input
- RCA Connectors
- Built-in IR Transmitter for Wireless Headphones
- Built with Speaker

- Brightness/ Contrast/ Color/ Tint Adjustments
- Headrest Shroud & Universal Stand Mount
- Wireless Full Function Remote Control
- Power Requirement: Dc 12V +/- 10%
- Power Consumption: 5W Max
- Unit Dimensions: 9.7"H x 6.6"W x 0.8"D



PLHR9TSB=PLHR9TW 9" Headrest TFT LCD Monitor w/ VGA & Touch Screen

- Screen Size: 9 inch
- Type: Stand TFT LCD Monitor
- Dual Video Inputs; VGA Input with Touch Screen
- System: PAL & NTSC Auto Switching
- Power Supply: DC 12V
- OSD Menu; remote control

- AV Resolution: 800 x 480
- Contrast, Color, Brightness Adjustable
- View Angle Range: (left/right) 65° (top)40° (down)15°
- Dimensions: 10" x 6.7" x 1.2"
- Headrest in Black Color



PLHR7 7" Wide Screen TFT LCD Video Monitor w/Headrest Shroud and Universal Stand

- 7" Tft LCD Active Matrix Video Monitor
- 16:9 Wide Screen
- PAL/NTSC System
- High Resolution: 1440 X 234
- Wireless Remote Control
- Earphone Jack (3.5mm) Audio Output

- Two RCA Video Inputs
- AV input jack(3.5mm)
- Power Supply: Dc12v
- Headrest Shroud & Universal Stand Mount
- Dimension: 7.60"W X 5.24"H X 0.98"D



PLHR78W 7" Widescreen TFT Headrest Monitor in White

- 7" TFT Active Matrix Display
- 16:9 Wide Screen Format
- Resolution: 1440 x 234 Dots
- NTSC / PAL System Compatible
- Wireless Remote Control
- Dual Video Input
- Reverse Imaging Left/Right Up/Down
- Brightness/ Contrast/ Color/ Tint Adjustments
- Headrest Shroud and Universal Stand Mount
- On Screen Display
- Brightness, Contrast, Color
- DC 12 Volt Power
- Dimensions: 7.25" (W) x 5.65" (H) x 1.45" (D)



PLHR79 7" Widescreen TFT Headrest Monitor

- 7" TFT Active Matrix Display
- 16:9 Wide Screen Format
- Resolution: 1440 x 234 Dots
- NTSC / PAL System Compatible
- Wireless Remote Control
- Dual Video Input
- Reverse Imaging Left/Right Up/Down
- Brightness/ Contrast/ Color/ Tint Adjustments
- Headrest Shroud and Universal Stand Mount
- On Screen Display
- Brightness, Contrast, Color
- DC 12 Volt Power
- Dimensions: 7.25" (W) x 5.65" (H) x 1.45" (D)



PLHR95B 9.2" TFT/LCD Headrest Monitor w/Headrest Stand & Shroud w/RCA Connectors

- 9.2" TFT/LCD Digital Monitor
- 16:9 Wide Screen Format
- High Resolution 800 x 480
- NTSC/ PAL System Compatible
- 2 Video Input, 1 Audio Input
- RCA Connectors
- Built-in IR Transmitter for Wireless Headphones
- Built with Speaker
- Brightness/ Contrast/ Color/ Tint Adjustments
- Headrest Shroud & Universal Stand Mount
- Wireless Full Function Remote Control
- Power Requirement: Dc 12V +/- 10%
- Power Consumption: 5W Max
- Unit Dimensions: 8.7"H x 5.7"W x 0.8"D



PLHR76 7" Widescreen TFT/LCD Video Monitor w/Headrest Shroud

- 7" Widescreen TFT/LCD Active Matrix Monitor
- No Radiation
- Fashion Design
- PAL/ NTSC System
- High Resolution
- Low Power Consumption
- With Remote Control
- Earphone Jack Output
- 2 AV Inputs
- Headrest Shroud & Universal Stand Mount



PLHR75 7" TFT Wide Screen Headrest Monitor

- PAL/NTSC System
- Two Video Inputs
- Power Supply: DC 12V
- Resolution: 1440 x 234
- Full Function Remote Control
- 7" TFT Active Matrix Display
- Back Light: Cold Cathode Filament Tube
- Headrest Shroud & Universal Stand Mount
- Viewing Angles:(Left/Right)60°(Top)30°(Down)10°
- Dimension: 7.25"W x 4.75" x 0.90"



PLHRQD7B 7" Quad TFT/LCD Video Monitor w/Headrest Shroud RCA Connectors

- 7" TFT/LCD Active Matrix Video Monitor
- Built-in Quad Control Box Screen Function
- Supports Four Video Camera Inputs (V1/V2/V3/V4)
- Selectable Viewing Modes: Single Full View / Split Dual Video View / Quad Four Source View
- PAL/NTSC Video Format Compatible
- Reverse Image Function
- High Resolution: 480 x 234
- Operating Temperature: -20 to +65
- Wireless Full Function Remote Control
- Headrest Shroud for Flush Mounting
- Universal Stand Compatible
- RCA Connectors
- Direct DC 12 Volt Compatible
- AC Power Supply Included
- Power Requirement: Dc 12V +/- 10%
- Power Consumption: 5W Max
- Working temperature -20-60 degrees
- Storage temperature -30-70 degrees



2013 Complete Product Catalog

PLHR97W 9" TFT LCD Headrest Monitor w/ Stand (White)

- 9" TFT Active Matrix Display
- 16:9 Wide Screen Format
- Resolution: 1440 x 234 Dots
- NTSC/ PAL System Compatible
- Wireless Remote Control
- Dual Video Input
- Built-in IR Transmitter for Wireless Headphones
- Reverse Imaging Left/Right Up/Down
- Brightness/ Contrast/ Color/ Tint Adjustments
- Headrest Shroud & Universal Stand Mount
- On Screen Display
- Brightness/ Contrast/ Color
- DC 12 Volt Power.



PLHR98W 9.2" TFT/LCD Headrest Monitor w/Headrest Stand & Shroud w/RCA Connectors

- 9.2" TFT/LCD Digital Monitor
- 16:9 Wide Screen Format
- High Resolution 800 x 480
- NTSC/ PAL System Compatible
- 2 Video Input, 1 Audio Input
- RCA Connectors
- Built-in IR Transmitter for Wireless Headphones
- Built with Speaker
- Brightness/ Contrast/ Color/ Tint Adjustments
- Headrest Shroud & Universal Stand Mount
- Wireless Full Function Remote Control
- Power Requirement: Dc 12V +/- 10%
- Power Consumption: 5W Max
- Unit Dimensions: 8.7"H x 5.7"W x 0.8"D



PLHRQD9B 9" Quad TFT/LCD Video Monitor w/Headrest Shroud RCA Connectors

- 9" TFT/LCD Active Matrix Video Monitor
- Built-in Quad Control Box Screen Function
- Supports Four Video Camera Inputs (V1/V2/V3/V4)
- Selectable Viewing Modes: Single Full View / Split Dual Video View / Quad Four Source View
- PAL/NTSC Video Format Compatible
- Reverse Image Function
- High Resolution: 640 x 234
- Operating Temperature: -20 to +65
- Wireless Full Function Remote Control
- Headrest Shroud for Flush Mounting
- Universal Stand Compatible
- RCA Connectors
- Direct DC 12 Volt Compatible
- AC Power Supply Included
- Power Requirement: Dc 12V +/- 10%
- Power Consumption: 5W Max
- Working temperature -20-60 degrees
- Storage temperature -30-70 degrees



PLHRQD9W 9" Quad TFT/LCD Video Monitor w/Headrest Shroud RCA

- 9" TFT/LCD Active Matrix Video Monitor
- Built-in Quad Control Box Screen Function
- Supports Four Video Camera Inputs (V1/V2/V3/V4)
- Selectable Viewing Modes: Single Full View / Split Dual Video View / Quad Four Source View
- PAL/NTSC Video Format Compatible
- Reverse Image Function
- High Resolution: 640 x 234
- Operating Temperature: -20 to +65
- Wireless Full Function Remote Control
- Headrest Shroud for Flush Mounting
- Universal Stand Compatible
- RCA Connectors
- Direct DC 12 Volt Compatible
- AC Power Supply Included
- Power Requirement: Dc 12V +/- 10%
- Power Consumption: 5W Max



PLHRQD7B 7" Quad TFT/LCD Video Monitor w/Headrest Shroud RCA

- 7" TFT/LCD Active Matrix Video Monitor
- Built-in Quad Control Box Screen Function
- Supports Four Video Camera Inputs (V1/V2/V3/V4)
- Selectable Viewing Modes: Single Full View / Split Dual Video View / Quad Four Source View
- PAL/NTSC Video Format Compatible
- Reverse Image Function
- High Resolution: 480 x 234
- Operating Temperature: -20 to +65
- Wireless Full Function Remote Control
- Headrest Shroud for Flush Mounting
- Universal Stand Compatible
- RCA Connectors
- Direct DC 12 Volt Compatible
- AC Power Supply Included
- Power Requirement: Dc 12V +/- 10%
- Power Consumption: 5W Max
- Working temperature -20-60 degrees
- Storage temperature -30-70 degrees



PLHRQD7W 7" Quad TFT/LCD Video Monitor w/Headrest Shroud RCA

- 7" TFT/LCD Active Matrix Video Monitor
- Built-in Quad Control Box Screen Function
- Supports Four Video Camera Inputs (V1/V2/V3/V4)
- Selectable Viewing Modes: Single Full View / Split Dual Video View / Quad Four Source View
- PAL/NTSC Video Format Compatible
- Reverse Image Function
- High Resolution: 480 x 234
- Operating Temperature: -20 to +65
- Wireless Full Function Remote Control
- Headrest Shroud for Flush Mounting
- Universal Stand Compatible
- RCA Connectors
- Direct DC 12 Volt Compatible
- AC Power Supply Included
- Power Requirement: Dc 12V +/- 10%
- Power Consumption: 5W Max



PLMN7SU 7" Battery Powered TFT/LCD Monitor with MP3/MP4/USB/SD/MMC Card Player

- 7" TFT LCD Monitor
- Super Thin and Multifunction Remote Control
- Built-In Stereo Speakers
- On Screen Menu
- Three-In-One SD/MMC/MS Card Reader & Mini USB Input
- Built-In Foldable Picture Frame Stand
- AV Input Function
- Earphone Jack Audio Output
- Universal Stand Included
- 12V Car Cigarette Lighter Plug
- AC Adapter 110-220V
- PAL/NTSC Compatible
- High Resolution: 480 x 234
- Built-In Long Life Rechargeable Battery Can Work Up to 2 Hours
- Dimensions: 7.08" (W) x 5.9" (H) x 1.28" (D)



PLMN9SU 9" Battery Powered TFT/LCD Monitor with MP3/MP4/USB/SD/MMC Card Player

- 9" TFT LCD Monitor
- Super Thin and Multifunction Remote Control
- Built-In Stereo Speakers
- On Screen Menu
- Three-In-One SD/MMC/MS Card Reader & Mini USB Input
- Built-In Foldable Picture Frame Stand
- AV Input Function
- Earphone Jack Audio Output
- Universal Stand Included
- 12V Car Cigarette Lighter Plug
- AC Adapter 110-220V
- PAL/NTSC Compatible
- High Resolution: 480 x 234
- Built-In Long Life Rechargeable Battery Can Work Up to 2 Hours
- Dimensions: 7.08" (W) x 5.9" (H) x 1.28" (D)



PL1104HRBK Adjustable Headrest w/ Built-In 11.3" TFT LCD Monitor and IR Transmitter

- English OSD Menu
- Power Supply 12V
- 4:3 Display Format
- PAL/NTSC Compatible
- Resolution: 800 x 600
- Brightness: 180 cd/m2
- 11.3" TFT Monitor w/ Headrest
- Built-in Transmitter for Wireless IR
- Full Function Wireless Remote ControlsHeadphones
- Dimensions: 15.75" x 12.8 x 5"
- Color: Black

NEW!
for 2013



PL1104HRGR Adjustable Headrest w/ Built-In 11.3" TFT LCD Monitor and IR Transmitter

- 11.3" TFT Monitor w/ Pillow
- 4:3 Display Format
- Resolution: 800 x 600
- Brightness: 180 cd/m2
- PAL/NTSC Compatible
- Full Function Wireless Remote Controls
- English OSD Menu
- Power Supply 12V
- Built-in Transmitter for Wireless IR Headphones
- Dimensions: 15.75" x 12.8 x 5"

NEW!
for 2013



PL7PHB Adjustable Headrest Pair with Built-in 7" TFT-LCD Monitors (Black)

- Headrest Package Includes Two 7" TFT Monitor
- Screen Size: 7" TFT-LCD Monitor
- Built-in Speaker
- Aspect Ratio: 16:9 Wide Screen
- 1440 x 234 Resolution
- Contrast: Ratio: 300:1
- Brightness: 350cd/m3
- Headphone Jack
- Up Down Tilting Feature
- Viewing Angle: U/D: 160° L/R: 160°
- Response Time: 25ms
- Video Input Systems: AV1,AV2
- PAL/NTSC Compatible
- Full Function Wireless Remote Control
- English OSD Menu
- IR Transmitter for Wireless IR Headphones
- Adjustable Mouning Posts From 4 3/4" - 7 1/2"
- Dual Diameter Mounting Posts (1/2" 3/8")
- Dimensions: 10"W x 7.5"H x 4.5"D



PL90HR Adjustable Headrests w/ Built-In 9" TFT/LCD Monitor w/IR Transmitter & Cover

- 9" TFT Monitor with Pillow
- 3.5mm Mini Front Panel Video Input
- Full Function Wireless Remote Controls
- High Resolution: 1024 x RGB x 600
- Aspect Ratio: 16:9 Wide Screen
- Headrest with Zipper Cover
- Contrast Ratio: 300:1
- Brightness: 350cd/m2
- PAL/NTSC Compatible
- English OSD Menu
- Power Supply 12V
- Built-In IR Transmitter
- Dimensions: 11.5" (W) x 8.1" (H) x 4.7" (D)



PL90HRGR
(Gray)



PL90HRTN
(Tan)



PL90HRBK
(Black)

2013 Complete Product Catalog

PL91HR Adjustable Headrests w/ Built-In 9" TFT/LCD Monitor w/IR Transmitter & Cover

- 9" TFT monitor with pillow
- Full Function Wireless Remote Control
- Headrest with Zipper Hide-Away Cover
- Aspect Ratio: 16:9 Wide-Screen
- High Resolution: 1024 x 600
- Contrast Ratio: 300:1
- Brightness: 350cd/m2
- PAL/NTSC Compatible
- Front Panel Audio/Video Input
- Headphone jack
- English OSD menu
- Power Supply: Dc12v
- Built in IR Transmitter
- Adjustable Mounting Posts: 4.3" to 7.1"
- Dimensions: 11.5"W x 8.1"H x 4.7"D



PL91HRGR
(Gray)



PL91HRTN
(Tan)



PL91HRBK
(Black)

*11" TFT/LCD Monitor Models:

PL1101HRGR
(Gray)

PL1101HRTN
(Tan)

PL1101HRBK
(Black)

PLD72 Adjustable Headrests w/ Built-In 7" TFT/LCD Monitor w/Built-in DVD Player IR Transmitter & Cover

- 7" LCD/TFT Monitor With Built In DVD Player
- Headrest With Zipper Hide-Away Cover
- USB/SD-MMC Card Reader
- Built In Game With Joystick
- Aspect Ratio: 16:9 Widescreen
- High Resolution: 1440x234
- Contrast: 300:1
- Brightness: 350CD/M2
- AV Inputs/Outputs
- PAL/NTSC Compatible
- Auto Switching
- Full Function Wireless Remote Control
- English OSD Menu
- Power Supply: Dc12v
- Built In IR Transmitter For Wireless IR Headphones
- Plays DVD/VCD/MP3/JPG/MP4/CD-R/CD-RW
- Adjustable Mounting Posts: 4.3" To 7.1"
- Dimensions: 11.5"W X 8.3"H X 4.7"D



PLD72GR
(Gray)



PLD72TN
(Tan)



PLD72BK
(Black)

*Without DVD Players:

PLHR72GR
(Gray)

PLHR72TN
(Tan)

PLHR72BK
(Black)

PL72 Adjustable Headrests w/ Built-In 7" TFT/LCD Monitor w/IR Transmitter & Cover

- 7" TFT Monitor With Pillow
- Headrest with Zipper Hide-Away Cover
- Aspect Ratio: 16:9 Widescreen
- High Resolution: 1440x234
- Contrast Ratio: 300:1
- Brightness: 350cd/M2
- PAL/NTSC Compatible
- Auto Switching
- Full Function Wireless Remote Control
- English OSD Menu
- Power Input: Dc 12V
- Built In IR Transmitter For Wireless IR Headphones
- Adjustable Mounting Posts: 4.3" To 7.1"
- Dimensions: 11.5"W X 8.3"H X 4.7"D



PL72HRGR
(Gray)



PL72HRTN
(Tan)



PL72HRBK
(Black)

PLD76 Adjustable Headrests w/ Built-In 7" TFT/LCD Monitor w/ Built-In DVD Player & IR/FM Transmitter

- 7" TFT monitor w/DVD player
- Headrest with zipper cover
- DVD/VCD/MP3/JPG/MP4
- CD-R/CD-RW, USB/SD/MMC card reader
- Built in Game with joystick
- 440 x 234 resolution - Contrast ratio: 300:1
- Brightness: 350cd/m2
- AV/Inputs/output, Auto Switching
- Full function wireless remote
- IR transmitter for IR headphones
- Dimensions: 11.5"W x 8.3"x 4.7"D



PLD76GR
(Gray)



PLD76BK
(Black)



PLD76TN
(Tan)

IR WIRELESS HEADPHONES:

Infrared wireless stereo headphones for car audio systems
Double channel for two audio sources. Compatible with all vehicle AV applications. Auto mute and auto power off. Effective range up to 10 meters
Ultra light weight design for comfortable wearing with adjustable headband.

PLRD92 9" Flip Down Roof Mount Monitor & DVD player with Wireless FM Modulator/ IR Transmitter

- 9" 16:9 Wide Screen TFT-LCD Monitor
- High Resolution: 640 x 234 Pixels
- Brightness: 450 Cd/ Sq.M
- Contrast Ratio: 500:1
- Viewing Angle: 140 degree (Left/Right) 120 degree(Top/Down)
- Overhead Console with Twin Dome Lights w/ LED
- IR transmitter Ready for Wireless Headphone
- Built-In FM Modulator
- Full Function Wireless Remote

- On Screen Menu System
- Front Push Buttons Controls
- Audio/ Video Inputs
- USB SD Card Inputs
- Mult System: NTSC PAL Auto Switching
- DVD/VCD/CD/CD-R/CDRW/MP3 Compatible
- Power Requirement: 12 DC
- DIN Cable w/ RCA Jacks for A/V Connections
- Dimensions: 8.46" (W) x 2.17" (D) x 9.45" (H)



PLRD94 9.4" Flip Roof Mount Monitor & DVD Player with Wireless FM Modulator, IR Transmitter,

- Contrast Ratio 500:1
- PAL/NTSC Compatible
- Power Supply: DC 12V
- One Way Audio/Video Input
- One Way Audio/Video Output
- Built-In Dome LED Led Lights

- Built-In Dual IR/FM Transmitter
- Full Function Wireless Remote Control
- Display Mode: 16:9 Wide View Screen
- Slot-In Disc Loading (Anti-Shock Mechanism)
- English OSD Menu with Multi-Language Support
- Dimensions: 11.8" W x 9.96" D x 2.13" H



PLRD1031F 10.4" TFT LCD Flip-Down Roof Mount DVD Monitor & IR/FM Transmitter

- 10.4" Active Matrix TFT LCD Monitor
- Built In DVD Disc Player
- 4:3 High Resolution 800 x 600 Pixels
- Dual Dome Light Universal Roof Mount Console
- 90° Swivel Screen
- DVD/VCD/CD/CD-R/CD-RW/MP3 Comparable
- USB/SD/MMC/MP5/3-IN-1 Card Input
- Video System: NTSC/PAL Auto Switching
- On Screen Display

- Wireless Remote Control with two Joystick
- Audio/Video Input & Output
- Picture Brightness, Contrast, Color Adjusting
- Built In IR Transmitter for Use with IR Headphones
- Built-In FM Transmitter
- New Digital Technology
- Power Supply: DC 12V
- Dimension: 10.63" x 10.24" x 1.25"



PLRD145 13.3" Roof Mount TFT LCD Monitor Built In DVD/USB/SD Player w/ Wireless FM/IR Transmitter & 3 Color Skins

- 13.3" Wide Screen Hi Resolution TFT-LCD Monitor
- Overhead Console with Dual LED Dome Lights
- 3 sets of interchangeable 2pc snap-on color skins Choose from Grey, Black, or Tan
- Resolution: 1280 x 800
- Brightness: 450 Cd/Sq.M
- Contrast Ratio: 500:1
- On Screen Menu Control
- 140 degree viewing angle adjustment
- IR Transmitter Ready for Wireless Headphone
- Overhead Console with Dual LED Dome Lights
- Wireless FM Transmitter to broadcast to a existing

- FM stereo (Portable/Car/Etc.)
- Push button dual function front mounted controls
- 1 Set RCA Audio Video Inputs
- 1 Set RCA Audio Video Outputs
- Multi System: NTSC/PAL Auto Switch
- Side Mount Slot-Load DVD Player
- DVD CD/CD/CD-R/CDRW/MP3 Compatible
- Built in Speaker's and audible button indicators
- Anti-Skip Mechanism & Last position memory
- Full Function wireless remote control
- Power Source: DC 12 Volt
- Dimensions: 16.25"x W 13" D x 2.15" H Closed



2013 Complete Product Catalog

PLRD104 10.4" Flip Roof Mount Monitor & DVD Player with Wireless FM Modulator

- Contrast Ratio 500:1
- PAL/NTSC Compatible
- Power Supply: DC 12V
- One Way Audio/Video Input
- One Way Audio/Video Output
- Built-In Dome LED Led Lights

- Built-In Dual IR/FM Transmitter
- Full Function Wireless Remote Control
- Display Mode: 16:9 Wide View Screen
- Slot-In Disc Loading (Anti-Shock Mechanism)
- English OSD Menu with Multi-Language Support
- Dimensions: 11.8" W x 9.96" D x 2.13" H



PLRD125 12.1" TFT LCD Flip-Down Roof Mount Built-In DVD Player w/ FM Modulator

- 12.1" 16:9 Wide Screen TFT LCD Monitor
- Built-In DVD Disc Player
- High Resolution 800 x 600 Pixels
- Dual Dome Light Universal Roof Mount Console
- 320° Swivel Screen
- DVD/VCD/CD/CD-R/CD-RW/MP3 Compatible
- USB/SD/MMC/MP4/3-IN-1 Card Input
- Video System: NTSC/PAL Auto switching
- On Screen Display

- Wireless Remote Control
- With Two Joystick/Game Disc
- Audio/Video Input & Output
- Picture Brightness, Contrast, Color Adjustment
- Built-In IR Transmitter for Use with IR Headphones
- Built-In FM Transmitter
- Power Supply: DC 12V
- DIN Cable w/ RCA Jacks for A/V Connections
- Dimensions: 11.4" (W) x 12.8" (H) x 2.8" (D)



PLRD133F 12.1" Roof Mount TFT LCD Monitor w/ Built-In DVD Player

- 12.1" Wide Screen Hi Res TFT LCD Monitor
- Resolution: 1280 x 800
- Brightness: 450 Cd/Sq.M
- Contrast Ratio: 500:1
- Overhead Console w/ Twin Dome Lights w/ LED
- IR Transmitter Ready for Wireless Headphone
- Front Push Bottoms Controls
- Audio Video Inputs/Outputs

- Multi- System: NTSC & PAL Auto Switching
- Slot-Loading DVD Player
- DVD CD/CD-R/CD-RW/MP3 Compatible
- Built-In Speaker
- Anti-Skip Mechanism
- Last Position memory
- Full Function Wirelss Remote Control
- Dimension: 16.06"W x 13"H x 2.7"D



PLRD153IF 15.1" Flip Down Monitor w/ Built In DVD/SD/USB player, Wireless IR Transmitter

- 15.1" Wide Screen Hi Re TFT-LCD Monitor
- Flip Down Roof Mount
- Resolution: 1440 x 900
- Brightness: 450 Cd/Sq.M
- Contrast Ratio: 500:1
- Overhead Console w/Twin Dome Light w/LED
- 90 degrees Swivel Left/Right
- IR Transmitter Ready for Wireless Headphone
- Front Push Button Controls

- RCA Audio Video Inputs
- Multi System: NTSC PAL Auto Switching
- Slot-Load DVD Player
- DVD/CD/CD-R/CD-RW/MP3/MPEG4 Compatible
- USB SD Card Inputs
- Anti-Skip Mechanism
- Last Position Memory
- Full Function Wireless Remote Control
- Dimensions: 15.5"(W) x 15.2"(H) x 2.4"(D)



PLRD163IF 16.4" TFT LCD Flip-Down Roof Mount w/ Built In DVD/SD/USB Player

- 16.4" TFT/ LCD Active Matrix System
- On Screen Video Display Menu
- 16:9 Wide Screen Aspect Ratio
- High Resolution: 1280 x 1024
- PAL/ NTSC Compatible
- AV Input/Output
- Built-In IR Transmitter for Wireless IR Headphones
- English OSD Menu

- Full Function Wireless Remote Control
- Slot-load DVD Player
- DVD/CD/CD-R/CD-RW/MP3/MPEG4 Compatible
- USB SD Card Inputs
- Dual Dome Lights
- Universal Roof Mount Console
- Power Input: DC 12V
- Dimensions: 16.6" W x 13.5" H x 2.1" D



PLRD175IF 17" Flip Down Monitor w/ Built in DVD/ SD/ USB Player w/ Wireless FM

- 17" Wide Screen Hi-Resolution TFT-LCD Monitor
- Flip-Down Roof Mount
- Resolution: 1280 x 1024
- Brightness: 450 Cd/ Sq. M
- Contrast Radio: 500:1
- Overhead Console w/ Twin Dome Light w/ LED
- IR Transmitter Ready for Wireless Headphone
- Front Push Button Controls
- RCA Audio Video Inputs

- Multi-System: NTSC PAL Auto Switching
- Slot-load DVD Player
- DVD/CD/CD-R/CD-RW/MP3 Compatible
- USB SD Card Inputs
- Anti-Skip Mechanism
- Last Position Memory
- Full Function Wireless Remote Control
- Dimensions: 21.4"W x 16.7"H x 2.7"D



PLRD195F 19" Flip Down w/ Built In DVD/SD/USB Player w/ Wireless FM/ Modulator & IR Transmitter

- 19" Wide Screen Hi-Resolution TFT-LCD Monitor
- Flip-Down Roof Mount
- Resolution: 1440 x 900
- Brightness: 450Cd/Sq.M
- Contrast Ratio: 500:1
- Overhead Console w/ Twin Dome Lights w/ LED
- IR transmitter Ready for Wireless Headphone
- Front Push Button Controls
- RCA Audio Video Inputs

- Multi-System: NTSC PAL Auto Switching
- Slot-Load DVD Player
- DVD/CD/CD-R/CD-RW/MP3 Compatible
- USB SD Card Inputs
- Anti-Skip Mechanism
- Last Position Memory
- Full Function Wireless Remote Control
- Dimensions: 21.4"W x 16.7"H x 2.7"D



PLWR850 8.5" High Resolution TFT Flip Down Roof Mount Monitor & IR Transmitter

- 8.5" TFT LCD Flip Down Monitor
- Super Slim Design
- On Screen Display Menu
- Display Mode: 16:9
- Swivel Screen
- 2 AV Inputs

- Built-In IR Transmitter for Wireless IR Headphones
- Full Function Remote Control
- Dual Dome Light
- Universal Roof Mount Console
- Power supply dc 12 volt
- Dimensions: 9.6"H x 9.8"W x 1"D



PLWR1342R 13.4" TFT Roof Mount Monitor & IR Transmitter

- 13.4" TFT Active Matrix Monitor
- Overhead Console w/Flip Bracket
- Wide Angle, Off Axis Visibility
- Resolution: 800x600
- 4:3 Display Format
- Front Panel Controls
- 2 Audio Video Inputs

- Swivel Bracket Permits 45° L/R Rotation
- NTSC/PAL System
- OSD English Menu
- Built-In IR Transmitter for Wireless IR Headphones
- Wireless Remote Control
- Power Supply: DC12V
- Dimension: 13.5" x 11.5" x 1.2"



PLWR1443R 13.4" Flip-Down Roof Mount TFT LCD Monitor & IR Transmitter

- 13.4" TFT Active Matrix Monitor
- Overhead Console w/ Flip Bracket
- Wide Angle, Off Axis Visibility
- Resolution: 800 x 600
- 4:3 Display Format
- Front Panel Controls
- 2 Audio Video Inputs

- Swivel Bracket Permits 45° L/R Rotation
- NTSC/PAL System
- OSD English Menu
- Built-In IR Transmitter for Wireless IR Headphones
- Wireless Remote Control
- Power Supply: DC 12V
- Dimension: 13.5" x 11.5" x 1.2"



PLWR1440 14" High Resolution TFT Roof Mount Monitor & IR Transmitter

- 14" TFT Active Matrix System
- English OSD Menu
- NTSC/ PAL Color System
- 4:3 Display Format
- 45° Swivel Screen
- High Resolution 1024 x 768
- 2 AV Input

- Built-In IR Transmitter for Use with IR Headphones
- Full Function Wireless Remote Control
- Dual Dome Light Universal Roof Mount Console
- Wireless Remote Control
- DC 12 Volt Power Supply
- Dimensions: 13.5" x 11.7" x 1.25"



PLWR1442 14.7" High Resolution TFT Roof Mount Monitor & IR Transmitter

- 14.7" TFT Active Matrix System
- English OSD Menu
- NTSC/ PAL Color System
- 4:3 Display Format
- 45° Swivel Screen
- High Resolution 1024 x 768
- 2 AV Input

- Built-In IR Transmitter for Use with IR Headphones
- Full Function Wireless Remote Control
- Dual Dome Light Universal Roof Mount Console
- Wireless Remote Control
- DC 12 Volt Power Supply
- Dimensions: 13.5" x 11.7" x 1.25"



2013 Complete Product Catalog

PLVWR1542 15" High Resolution TFT Roof Mount Monitor & IR Transmitter

- 15" TFT LCD Flip Down Monitor
- Super Slim Design
- On Screen Display Menu
- Display Mode: 4:3
- High Resolution 1024 x 768
- 2 AV Inputs
- Built-In IR Transmitter for Wireless IR Headphones
- Full Function Remote Control
- Dual Dome Light
- Universal Roof Mount Console
- Dimensions: 15.2" x 13.5" x 1.4"



PLVWR1544 15.1" Flip Down Roof Mount TFT LCD Monitor & IR Transmitter

- 15.1" Roof Mount TFT LCD Monitor
- English OSD Menu
- Swivel Screen
- High resolution 1024 x 768
- 2 AV Inputs
- w/ Built-In IR Transmitter for Use w/ IR Headphones
- Full Function Wireless Remote Control
- Dual Dome Light Universal Roof Mount Console
- Dimensions: 16"W x 14"H x 1.9"D



PLVWR1752 18.5" Wide Screen TFT LCD Roof Mount Video Monitor w/IR Transmitter

- 18.5" TFT/LCD Active Matrix System
- Super Slim Design
- On Screen Video Display Menu
- 16:9 Wide Screen Aspect Ratio
- High Resolution: 1280x1024
- PAL/NTSC Compatible
- Two Video Inputs
- Built-in IR Transmitter for Wireless IR Headphones
- English OSD menu
- Full Function Wireless Remote Control
- Dual Dome light's
- Universal Roof Mount Console
- Power Input: Dc 12V
- Dimensions: 17"W x 13.8"H x 1.2"D



PLVWR1755 17.5" Flip Roof Mount Monitor W/ Wireless IR Transmitter

- 1 Audio Input - 2 Video Inputs
- Contrast: 400:1
- System: PAL/NTSC
- Power Supply: DC12V
- With build-in LED Light
- Power Consumption: <15 Watt
- Display Mode: 16:9 Wide View Angle
- Full Function Wireless Remote Control
- High Resolution: 1440 X (RGB) X 900 Pixel
- Image Bright, Contrast, Color, Tint Adjust
- 17.5" Flip Roof Mount Monitor with Wireless IR Transmitter
- Unit dimension: 19.4" x 15" x 16.8"



PLVWR1982 19" Widescreen TFT Roof Mount Monitor & IR Transmitter

- 19" TFT Active Matrix System
- English OSD Menu
- 16:9 Widescreen Format
- High Resolution 1280 x 800
- 2 Audio Video Inputs
- Built-In IR Transmitter for Wireless IR Headphones
- Full Function Wireless Remote Control
- Dual Dome Light Universal Roof Mount Console
- DC 12 Volt Power Supply
- Dimensions: 18.7"W x 15"H x 1.8"(D)



PLVWR2200 22" Flip Down Roof Mount TFT LCD Monitor & IR Transmitter

- 22" Roof Mount TFT LCD Monitor
- English OSD Menu
- Slim Design
- High Resolution 1820 x 1080
- 2 AV Inputs w/ Built In IR Transmitter
- For Use with IR Headphones
- Full Function Wireless Remote Control
- Dual Dome Light Universal Roof Mount Console
- Dimensions: 21.5" x 15.6" x 1.5"



PLVWR2400 25" Wide Screen TFT-LCD Roof Mount Video Monitor w/IR Transmitter

- 25" TFT/ LCD Active Matrix System
- On Screen Video Display Menu
- 16:9 Wide Screen Aspect Ratio
- High Resolution: 1920 x 1080
- PAL/NTSC Compatible
- Two AV Inputs
- Built-In IR Transmitter for Wireless IR Headphones
- English OSD Menu
- Full Function Wireless Remote Control
- Dual Dome Lights
- Universal Roof Mount Console
- Power Input: DC 12V
- Dimensions: 23.5" (W) x 16.8" (H) x 1.8" (D)



PLVW91W 9.2" In-Wall Mount TFT LCD Flat Panel Monitor For Home & Mobile Use

- BNC Connector
- 300:1 Contrast Ratio
- Brightness: 350cd/m²
- Power Supply: DC 12V
- 16:9 Screen Aspect Ratio
- 640 x 234 High Resolution
- PAL/NTSC Auto Color System
- Video Input: RCA, VGA & VESA
- TFT LCD Wall-Mountable Screen
- Viewing Angle: 40° Up - 70° Down - 70° Left & Right
- Wireless Remote Control and In-Wall Mounting Bracket
- Dimensions: (Screen): 9.84" W x 5.75" H x 1.10" D
- Weight: 1.03 kg

NEW!
for 2013



PLVW101W 10.4" In-Wall Mount TFT LCD Flat Panel Monitor For Home & Mobile Use

- BNC Connector
- 300:1 Contrast Ratio
- Brightness: 350cd/m²
- Power Supply: DC 12V
- 16:9 Screen Aspect Ratio
- 800 x 640 High Resolution
- PAL/NTSC Auto Color System
- Video Input: RCA, VGA & VESA
- TFT LCD Wall-Mountable Screen
- Viewing Angle: 40° Up - 70° Down - 70° Left & Right
- Wireless Remote Control and In-Wall Mounting Bracket
- Dimensions: (Screen): 11.41" W x 7.48" H x 0.98" D
- Weight: 2.27 lbs.


NEW!
for 2013



PLVW151W 15" In-Wall Mount TFT LCD Flat Panel Monitor For Home & Mobile Use

- BNC Connector
- 300:1 Contrast Ratio
- Brightness: 260cd/m²
- Power Supply: DC 12V
- 4:3 Screen Aspect Ratio
- 1024 x 768 High Resolution
- PAL/NTSC Auto Color System
- Video Input: RCA, VGA & VESA
- TFT LCD Wall-Mountable Screen
- Viewing Angle: 40° Up - 70° Down - 70° Left & Right
- Wireless Remote Control and In-Wall Mounting Bracket
- Dimensions: (Screen): 13.77" W x 10.23" H x 1.02" D
- Weight: 3.52 lbs.

NEW!
for 2013



PLVW171W 17" In-Wall Mount TFT LCD Flat Panel Monitor For Home & Mobile Use

- BNC Connector
- 300:1 Contrast Ratio
- Brightness: 350cd/m²
- Power Supply: DC 12V
- 16:9 Screen Aspect Ratio
- 1280 x 800 High Resolution
- PAL/NTSC Auto Color System
- Video Input: RCA, VGA & VESA
- TFT LCD Wall-Mountable Screen
- Viewing Angle: 40° Up - 70° Down - 70° Left & Right
- Wireless Remote Control and In-Wall Mounting Bracket
- Dimensions: (Screen): 16.07" W x 10.73" H x 1.10" D
- Weight: 1.03 kg

NEW!
for 2013



PLVW191W 19" In-Wall Mount TFT LCD Flat Panel Monitor For Home & Mobile Use

- BNC Connector
- 300:1 Contrast Ratio
- Brightness: 350cd/m²
- Power Supply: DC 12V
- PAL/NTSC Color System
- 16:9 Screen Aspect Ratio
- 1440 x 900 High Resolution
- PAL/NTSC Auto Color System
- Video Input: RCA, VGA & VESA
- TFT LCD Wall-Mountable Screen
- Viewing Angle: 40° Up - 70° Down - 70° Left & Right
- Wireless Remote Control and In-Wall Mounting Bracket
- Dimensions: (Screen): 18.3" W x 11.22" H x 1.10" D

NEW!
for 2013



2013 Complete Product Catalog

***For a complete list of detailed product information and specifics, remember to visit PyleAudio.com and search the item model number.**

PLVNH5 Wireless IR Mobile Video Stereo Headphones

- Single Wireless Infrared Stereo Headphone
- Light Weight Adjustable Size Comfortable Headset
- Power On/Off With Auto Shutdown Feature
- Volume Adjust Knob
- Carrier Frequency: Right Channel 2.8MHz, Left Channel 2.3 MHz
- 8 Meter Effective Range 45 degree Left Right
- Operates Up To 48 Hours On (2) AAA Batteries (Not Included)



PLVNH6 Dual Wireless IR Mobile Video Stereo Headphones w/Transmitter

- Studio Quality Headsets with Wide Angle Infrared Detection.
- Lightweight & Durable Construction
- Padded Ear Pieces For Long Term Listening
- High Quality Drivers for Excellent Frequency Response and Wired Performance.
- Headphones Feature Adjustable Fit Headsets That Can Accommodate A Child Or An Adult.
- Controls Conveniently Located On Headphone for Volume, Power and Mono/Stereo.
- Auto Muting Switch On Receiver
- Input: RCA Cable
- Power On/Off With Auto Shutdown Feature
- Carrier Frequency: Right Channel 2.8MHz, Left Channel 2.3 MHz
- 8 Meter Effective Range 45 degree Left Right
- Power Source: Transmitter DC 12VDC Hardwired,
- 2 AAA Batteries 1.5V For Each Headset (not included)
- Dimensions(Transmitter): 0.5" (H) X 3.75"(W) X 2.5" (D)



PLVNH1 In-car Infrared Dual-Channel Wireless Stereo Headphones Compatible

- Light Weight Design For Comfortable Wearing
- Small Ear Size Fits Children Well
- Auto Mute On Headphone
- Auto Power Off Function On Headphone
- Personal Volume Control
- Dual Channel
- A Channel: Right Channel: 2.8mhz; Left Channel: 2.3mhz
- B Channel: Right Channel: 3.8mhz; Left Channel: 3.2mhz
- Speaker: 30mm Mylar
- Cone Impedance: About 32ohm
- Effective Range(Maximum): About 10 Meters
- S/N Ratio: 70db(Minimum)
- Channel Separation: 40db(Minimum)
- Frequency Response: 30-20000Hz
- Power Supply: 2*AAA Battery
- Battery Life: About 48 Hours



PLVNH2 Dual A/B Channel Infrared Wireless Stereo Headphone

- Dual Channel Allows you to listen without interfering with other channels
- Studio Quality Headsets with Wide Angle Infrared Detection
- High Quality Drivers for Excelent frequency response
- Operational Distance: 100FT
- Selectable Program Source Inputs
- Adjustable Headphone Straps for Comfort
- Auto Mute Control
- Variable Volume Control
- MP3 Player Input Via 3.5mm Jack
- COmpatible with All In-Vehicle AV Application
- On/Off Switch saves battery life
- Channel (A) 2.8 MHZ (Right) 2.3 MHZ (left)
- Channel (B) 3.8 MHZ (Right) 3.2 MHZ (Left)
- Power Source: Transmitter DC 12VDC Hardwired
- 2 AAA Batteries 1.5V for each headset (not included)
- Current: <80mA
- Impedance: 10K OHM $\pm$ 15 %
- Auto on Lever: Less than 30MA (Input: 1 KHz)
- Auto off Time: 120 Sec - 240 Sec



PLVNH3 In-car Dual-Channel Wireless Stereo Headphones Compatible with In-Vehicle AV Applications

- Light Weight Design For Comfortable Wearing
- Auto Mute On Headphone
- Auto Power Off Function On Headphone
- Personal Volume Control• Dual Channel
- A Channel: Right Channel: 2.8mhz; Left Channel: 2.3mhz• B Channel: Right Channel: 3.8mhz; Left Channel: 3.2mhz
- Speaker: 30mm Mylar
- Cone Impedance: About 32ohm• Effective Range(Maximum): About 10 Meters
- S/N Ratio: 70db(Minimum)
- Channel Separation: 40db(Minimum)• Frequency Response: 30-20000Hz
- Power Supply: 2*AAA Battery
- Battery Life: About 48 Hours



PLVWCRK5 1/2" DIN Center Channel Amplified Speaker System

- High Power 50W Maximum Power Amplifier
- Five (5) 3/4" Forward Mount Full Range Audio
- Two (2) 1" Rear Mount Mid-Bass Response
- Mounting Brackets Hardware Included
- The Compact 1/2 Din Design Allows For Indash Mounting
- 5.1 Surround Sound Audio Speaker Amplifier Specs:
- Continuous Power Output: 25W
- Peak Power Output: 50W
- Frequency Response: 200 Hz To 28K Hz.
- Power Supply Voltage: 10.8V To 15.6V
- Current Consumption: 3A
- Dimensions: 1.75" (H) X 3.5" (W) X 5.75" (L)
- Weight: 1Lb
- Speaker Box Specs:
- Five (5) 3/4" Forward Mount Full Range Audio
- Two (2) 1" Rear Mount Mid-Bass Response
- Dimensions: 1.125" (H) X 6.75" (W) X 6.5" (L)
- Weight: 0.55Lb



PLVWGM3 Wireless 50 Game Mobile Video Gaming System

- Self Contained Mobile Video Gaming System
- Handheld Controller Wirelessly Transmits to Video Monitor
- IR Receiver allows for Concealed Installations
- Multi Direction Controller/Joystick
- Multi Function Button Controls
- 50 Hit Classic Games Built-into the Controller
- Controller/Receiver System
- 3.5mm Line Audio Video Output
- 3.5mm Male to Stereo Audio Video RCA Output
- 3.5mm Male to 3.5mm Male Cable Included
- 12V DC Power Compatible
- Requires 3 x AA Batteries Not Included
- Dimensions (Controller): 6" (H) X 5.5" (W) X 2.25" (D)
- Dimensions (Receiver): 3.5" (H) X 2.5" (W) X 1" (D)
- Download the Full Game List here



PLVATSC1 ATSC Digital Car HDTV Tuner/Receiver

- DTV Receiver ATSC Terrestrial To NTSC
- Channel Coverage: Terrestrial 2-69
- ATSC Terrestrial 8 VSB Demodulation
- Tunes & Decodes All 18 Approved ATSC DTV Broadcast Formats
- Auto & Manual Channel Program
- Mpeg-2 HD Video Decoding (MP@ML, MP@HL)
- Receive 1080i/ 720p/ 480i/ 480i Resolution
- Multiple Languages OSD (English/ Spanish/ French)
- Supports Multiple Languages Tracks
- Front/ Color/ Style/ Background Color Setting
- Signal Quality/ Signal Strength Indicator
- ELA 608 & EIA 708 Closed Caption And V-Chip Lock
- EPG Parental Guidance & Rating Control
- Sleep Mode For Power Saving/ Program Information Display
- Aspect Ratio 16:9 Or 4:3
- Time Zone Programmable
- One-Touch Channel Return
- Built-In Dolby Digital Audio Decoding
- Full Function Wireless Remote Control Included
- Digital Terrestrial Antenna Included
- Size: Approx 8.58" L X 4.09" W X 0.95" H
- Weight: 15.15OZ



PLGN19 19" Gooseneck Wall Mount for LCD Monitors and TV

- 19" Adjustable Gooseneck Mount
- For Use With Any Monitor or speaker and With 1/4" Slide Bracket
- To Hang On Wall Speakers
- Fully Adjustable Arm



PLGN24 24" Gooseneck Wall Mount for LCD Monitors and TV

- 24" Adjustable Gooseneck Mount
- For Use With Any Monitor and With 1/4" Slide Bracket
- Fully Adjustable Arm



PNV2000 Plug In Car 2000 Watts 12v DC to 115V AC Power Inverter with Modified Sine Wave

- No load current draw: 85%
- Low voltage / high voltage / overload / thermal protection circuitry
- Continued Power: 1000W
- Surge power: 2000W
- Dimension: 11.22" L x 6.93" W x 2.95" H



2013 Complete Product Catalog

PNV3000 Plug In Car 3000 Watts 12v DC to 115V AC Power Inverter with Modified Sine Wave

- No load current draw: 85%
- Low voltage / high voltage / overload / thermal protection circuitry
- Continued Power: 1500W
- Surge power: 3000 Watts
- Dimension: 13.58"(L) x 6.93"(W) x 2.95"(H)



PNV4000 Plug In Car 4000 Watts 12v DC to 115V AC Power Inverter with Modified Sine Wave

- No load current draw: 85%
- Low voltage / high voltage / overload / thermal protection circuitry
- Continued Power: 2000W
- Surge power: 4000W
- Dimension: 15.94"L x 6.93"W x 2.95"H



PNVR300 Plug In Car 300 Watts 12v DC to 115V AC Power Inverter with Modified Sine Wave

- No load current draw: 85%
- Low voltage / high voltage / overload / thermal protection circuitry
- Continued Power: 150W
- Surge power: 300W
- Dimension: 5.43"L x 4.33"L x 2.28"H



PNVR450 Plug In Car 440 Watts 12v DC to 115V AC Power Inverter with Modified Sine Wave

- No load current draw: 85%
- Low voltage / high voltage / overload / thermal protection circuitry
- Continued power: 220W
- Surge power: 440W
- Dimension: 6.22"L x 4.33"W x 2.28"H



PNVR800 Plug In Car 800 Watts 12v DC to 115V AC Power Inverter with Modified Sine Wave

- No load current draw: 85%
- Low voltage / high voltage / overload / thermal protection circuitry
- Continued power: 400W
- Surge power: 800W
- Dimension: 7.28"L x 4.33"L x 2.28"H



PNVU400 Plug In Car Compact 240 Watt Power Inverter DC/AC

- Cigarette Lighter Powered With 1 Power Output
- 120 Watts Maximum Continuous AC Output Power
- 240 Watts Maximum AC Output Surge Power
- General Dual 115 Volts 60 Cycles as Power From Any 12 Volt
- USB Airplane Power Plug
- Replaceable Spade Fuse
- Fan Cooled
- Use In Car, Truck, RV or Boat
- 90% Optimum Efficiency
- Use For Video Games
- 12.8-20 Amp Input Current
- Less Than 0.3A No Load Current Draw
- Electronic Over Load Protection w/Automatic Shutdown
- Low Battery Voltage Warning Followed By Automatic Shutdown
- High Input Voltage Protection
- Input Reverse Polarity Protection
- Dimensions: 3.10"W x 0.75"H x 5.5"D



***For a complete list of detailed product information and specifics, remember to visit PyleAudio.com and search the item model number.**

PNVU500

Plug In Car Ultra Compact 240 Watt Power Inverter DC/AC

- Cigarette Lighter Powered With 1 Power Output
- 120 Watts Maximum Continuous AC Output Power
- 240 Watts Maximum AC Output Surge Power
- General Dual 115 Volts 60 Cycles as Power From Any 12 Volt
- USB Airplane Power Plug
- Replaceable Spade Fuse
- Use In Car, Truck, RV or Boat
- 90% Optimum Efficiency
- Use For Video Games
- 12.8-20 Amp Input Current
- Less Than 0.3A No Load Current Draw
- Electronic Over Load Protection w/Automatic Shutdown
- Low Battery Voltage Warning Followed By Automatic Shutdown
- High Input Voltage Protection
- Input Reverse Polarity Protection
- Dimensions: 2.65"W x 0.75"H x 3.65"D



PSWNV120

24V DC to 12V DC Power Step Down 120 Watt Converter W/ PMW

- PMW Power Technology
- Power Output 60W Continuous
- Power Output 120W Peak
- For Use in 24 Volt Vehicles Trucks, RV, Buses, Etc. Allows installation of 12 Volt Items Such as Car Stereo's, CB Radio's, Fog Lights, Etc.
- No load current draw: <0.2 Amp
- 4 Ways Protection (Short Circuit, Over Load, High Voltage & Low Voltage)
- Input Voltage: DC 24 Volt
- Output Voltage: DC 12.5v-12.8 Volt
- Fuse Rating: 5A
- Converse Efficiency: 85%
- Dimensions: 1.96" x 4.72" x 1.88"



PSWNV240

24V DC to 12V DC Power Step Down 240 Watt Converter W/ PMW

- PMW Power Technology
- Power Output 120W Continuous
- Power Output 240W Peak
- For Use in 24 Volt Vehicles Trucks, RV, Buses, Etc. Allows installation of 12 Volt Items Such as Car Stereo's, CB Radio's, Fog Lights, Etc.
- No load current draw: <0.2 Amp
- 4 Ways Protection (Short Circuit, Over Load, High Voltage & Low Voltage)
- Input Voltage: DC 24 Volt
- Output Voltage: DC 12.5v-12.8 Volt
- Fuse Rating: 10A
- Converse Efficiency: 85%
- Dimensions: 3.34" x 4.72" x 1.88"



PSWNV480

24V DC to 12V DC Power Step Down 480 Watt Converter W/ PMW

- PMW Power Technology
- Power Output 240W Continuous
- Power Output 480W Peak
- For Use in 24 Volt Vehicles Trucks, RV, Buses, Etc. Allows installation of 12 Volt Items Such as Car Stereo's, CB Radio's, Fog Lights, Etc.
- No load current draw: <0.2 Amp
- 4 Ways Protection (Short Circuit, Over Load, High Voltage & Low Voltage)
- Input Voltage: DC 24 Volt
- Output Voltage: DC 12.5v-12.8 Volt
- Fuse Rating: 20A
- Converse Efficiency: 85%
- Dimensions: 4.72" x 4.72" x 1.88"



PSWNV720

24V DC to 12V DC Power Step Down 720 Watt Converter W/ PMW

- PMW Power Technology
- Power Output 360W Continuous
- Power Output 720W Peak
- For Use in 24 Volt Vehicles Trucks, RV, Buses, Etc. Allows installation of 12 Volt Items Such as Car Stereo's, CB Radio's, Fog Lights, Etc.
- No load current draw: <0.2 Amp
- 4 Ways Protection (Short Circuit, Over Load, High Voltage & Low Voltage)
- Input Voltage: DC 24 Volt
- Output Voltage: DC 12.5v-12.8 Volt
- Fuse Rating: 30A
- Converse Efficiency: 85%
- Dimensions: 5.51" x 4.72" x 1.88"



2013 Complete Product Catalog

PLCM10 License Plate Mount Rear View camera w/Night Vision

- Output Standard: PAL/NTSC
- High Resolution: 380TV Lines x 60 Fields
- Image Sensor: Ov 7910 Color CMOS
- Lens: 6mm 92°
- Low Light Illumination: 1.5 Lux/F1.2
- Video Output: RCA 1.0 Vpp Composite Video @ 75 Ohm
- Power Supply: DC 12 V > 75 Ohm
- Temperature: -10-50° Celcius
- Unit Dimensions: 1.3"(H) x 8"(W) x 1.26"(D)




PLCM18BC License Plate Mount Rear View Backup Color Camera w/ Distance Scale Line

- 420 TVL Horizontal Resolution
- Distance Scale Line
- True COLOR Reproduction
- Low Lux Performance of 0.2 LUX Night Vision
- Total Pixels: 656 x 492
- Resolution: 420 TV Lines
- Viewing Angle: 170 Degree
- Auto White Balance
- Waterproof (Ip67), Fog Resistant
- Low Lighting Capable
- Video Output: 1.0V PP-75 Ohm
- Power Supply: DC 12V 200mA
- 17 Foot male to male RCA Video Cable
- Dimension: 10"W x 1.3"H x 1.26"D



PLCM18SC License Plate Mount Rear View Backup Color Camera w/ Distance Scale Line

- 420 TVL Horizontal Resolution
- Distance Scale Line
- True COLOR Reproduction
- Low Lux Performance of 0.2 LUX Night Vision
- Total Pixels: 656 x 492
- Resolution: 420 TV Lines
- Viewing Angle: 170 Degree
- Auto White Balance
- Waterproof (Ip67), Fog Resistant
- Low Lighting Capable
- Video Output: 1.0V PP-75 Ohm
- Power Supply: DC 12V 200mA
- 17 Foot male to male RCA Video Cable
- Dimension: 10"W x 1.3"H x 1.26"D



PLCM221R Flush Mount Rear View Camera w/ 0 Lux Night Vision

- CMOS Water Proof 1.25" Flush Mount Housing
- 17 Foot Male to Male RCA Video Cable
- Drill Cutout Tool Included
- Image Sensor: OV7910 Color CMOS
- Total Pixels: 510 x 492
- Resolution: 380 TV Lines
- Night Vision Low Lighting Capable
- 10 IR LED Lights
- Min Illumination: 0.5 LUX
- Auto Image Adjustment
- Video Output: 1.0V pp-75 Ohm
- Power Supply: DC 12V 200 mA
- Dimensions: 1.25"(W) x 1.25"(H) x 1.77"(L)



PLCM231R Flush Mount Rearview Night Vision Camera w/ Distance Scale Line

- 420 TVL Horizontal Resolution
- Distance Scale Line
- True COLOR Reproduction
- Low Lux Performance of 0.2 LUX Night Vision
- Total Pixels: 656 x 492
- Resolution: 420 TV Lines
- Viewing Angle: 170 Degree
- Auto White Balance
- Waterproof (Ip67), Fog Resistant
- Low Lighting Capable
- Video Output: 1.0V PP-75 Ohm
- Power Supply: DC 12V 200mA
- 17 Foot male to male RCA Video Cable
- Hole Saw Mounting Bit
- Dimension: 1.25"W x 1.25"H x 1.80"D



PLCM241R Universal Mount Rear View Backup Camera

- Water Proof 1/3" Color CMD
- 17 Foot Male to Male RCA Video Cable
- Image Sensors: 1/3" Color CMD
- Total Pixels: 580 x 540
- Resolution: 420 TV Lines
- Min. Illumination: 1.0 LUX
- IP Rating: 68; Lens Angle: 170°
- Auto Image Adjustment
- Video Output: 1.0 Vpp-75 Ohm
- Power Supply: DC 12V
- Dimensions: 0.67" (W) x 0.67" (H) x 0.9" (L)



PLCM37RV Universal Mount Optional Front View & Rear View Backup Color CMD

- Water proof Front & Rear View Camera
- 17 Foot Male to Male RCA Video Cable
- Images Sensors: 1/3" Color CMD
- PAL/NTSC Compatible
- Total Pixels: 56- x 540
- Resolution: 420 TV Lines
- Min: Illumination: .05 LUX
- IP Rating 68; Lens Angle: 170°
- Auto Image Adjustment
- LED Light for Night Vision
- Video Output: 1.0 Vpp-75 Ohm
- Power Supply: DC 12V
- Dimensions: 0.78" (W) x 0.78" (H) x 0.78" (L)



PLCM38RV Universal Mount Optional Front View & Rear View Backup Color CMD

- Water Proof Front & Rear View Camera
- 17 Foot Male TO Male RCA Video Cable
- Image Sensors 1.3" Color DVD
- PAL/NTSC Compatible
- Total Pixels: S80 x S40
- Reclusion 420 TV Lines
- min. Illumination OS LUX
- Ip rating:68 Lens Angle: 170 degree
- Auto Image Adjustment
- LED Light For Night vision
- Distance Scale Line
- Video Output 1.0 Vpp-7S Ohm
- Power Supply: DC2v
- Dimensions: 3.18" (W) x 2.95"(H) x 2.17"(D)



PLCM39RV Waterproof Universal Mount Rear & Front View Camera With 420 Lines

- IP rating: Ip68
- Image Sensors: 1/4" color CMD
- TV system: PAL/NTSC
- Effective Pixels: 580X540
- Resolution(Tv lines): 420
- Lens Angle: 130 degree
- Water proof
- Power supply: DC 12V
- With Front view and Rear view optional function
- Distance Scale Line



PLCMB20 Universal Mount Infrared Adjustable Angle Rear View Camera with Anti-glare Shield & Distance Scale

- CMD Water Proof Rear View Camera
- 17 Foot Male to Male RCA Video Cable
- Image Sensors: 1/3" color CMD
- PAL/NTSC Compatible
- Video Output:1.0V pp-75 Ohm
- Effective Pixels: 580X540
- Resolution (TV lines): 420
- Lens Angle: 170 degree
- IP rating: Ip68
- Min Illumination:0.5 LUX
- Auto Image Adjustment
- With LED light for night vision
- Distance Scale Line
- Power supply: DC 12V
- Size:3.18 x2.95 x2.17



PLCM19 Low Lux Rear Camera Black Chrome Metal Lisence Plate Frame

- 420 TVL Horizontal Resolution
- Waterproof Rating : IP67
- Sensor Image: Color CMD Sensor
- Low Light Capable
- 17 Foot Male to Male RCA Video Cable
- TV System: PAL/NTSC
- Effective Pixels: 512 x 492
- Resolution (TV Lines) : 420
- Resolution (TV Lines) : 420
- Video Output: 1.0V pp-77Ohm
- Lens Angle: MAX 170°
- Power Supply: DC 12V
- Current Consupion (mA): 200mA
- Dimension: 312 x 162 mm
- Operating Temperature (Deg• C): -20 - +75 (RH95%MAX.)
- Storage Temperature (Deg• C): -40 - +85 (RH95%MAX)



PLCM21 License Plate Rear View Backup CCD Color Camera "Zinc Metal Chrome"

- 420 TVL Horizontal Resolution
- True COLOR Reproduction
- Low Lux Performance of 0.3 LUX at F2.0
- Toral Pixels: 512 x 492
- Resolution: 420 TV Lines
- Auto White Balance
- Waterproof (Ip67)
- Low Lighting Capable
- High Sensitive: 1/3" DSP Color CCD Built-In
- Video Output: 1.0V PP-75 Ohm
- Power Supply: DC 12V 200mA
- 17 Foot male to male RCA Video Cable
- Dimension: 12.7"W x 6.6"H



2013 Complete Product Catalog

PLCM31 3.5" Slim TFT LCD Window Suction Mount Monitor with Dual Mount Rearview Camera

Monitor:

- 3.5" window suction mount monitor
- Automatically switch when reversing
- Two video inputs
- Ntsc/Pal system auto switch
- Brightness: 200cd/m2
- Contrast: 200:1
- 12V DC cigarette plug included
- Dimension: 3.7"W x 3.3"H x 0.67"D

Camera:

- Dual mount micro sized video camera
- With full kit for both bracket mount and flush mount
- Drill bit included
- Low lux night vision camera with CMD sensor
- 170 degree L/R viewing angle
- Power supply: DC12V



PLCM32 3.5" TFT LCD Monitor w/ Universal Mount Rear View & Backup Color CMD

- 3.5" TFT LCD Stand Monitor
- 2 Video Inputs
- NTSC System
- Dimensions: 3.8" x 3.5" x 0.7"
- Brightness: 200 cd/m2
- Contrast: 200:1

Camera:

- Universal Mount
- Backup CMD Camera 1/3"
- Water Proof/ Night Vision
- Distance Scale Line Camera

- 17 foot Male to Male RCA Video Cable
- Image Sensors: 580 x 540
- Resolution: 420 TV Lines
- Min. Illumination: 1.0 LUX
- IP Rating: 68; Lens Angle: 170°
- Auto Image Adjustment
- Built-In Distance Scale Line
- Video Output: 1.0 Vpp-75 Ohm
- Power Supply: DC 12 V
- Dimensions: 0.67" (W) x 0.67" (H) x 0.9" (L)



PLCM34WIR 3.5" Monitor Wireless Back-Up Rearview & Night Vision Camera

Monitor:

- Wireless Back Up Rear View Camera
- 3.5" Slim TFT-LCD Stand Wireless Monitor
- Night Vision Car Camera Without Video Cable Fixing(Installation)
- Automatically Switched On When Reversing
- One RCA Video Input
- NTSC/PAL System Auto Switching
- Brightness: 200 cD/m
- Contrast: 200:1
- Built-in 2.4Ghz Wireless Video Receiver
- Dimensions: 4.13"W x 3.35"H x 0.87"D

Camera:

- Waterproof License Plate Mounting
- Image Sensor: OV7910 Color CMOS
- Total Pixels: 510 x 492
- Resolution: 380 TV Lines
- Night Vision Low Light Compatible
- Min. Illumination: 0.5Lux
- Video Output: 1.0 Vpp-75 Ohm
- Power Supply: DC 12V 200 mA
- Dimensions: 1.3"H x 8"W x 1.26"D



PLCM35R 3.5" TFT LCD Digital Monitor/Night Vision Rear-View Camera

- 3.5" TFT LCD Stand Monitor
- two Video Inputs
- NTSC System
- Dimesnions: 3.8" x 3.5" x 0.7"
- Brightness: 200 cd/m2
- Contrast: 200:1

Camera:

- CMOS waterproof 1.25" Flush MOunt Housing
- 17 foot male to male RCA Video Cable
- Required Drill Cutout Tool Included

- Image Sensor: OV7910 Color CMOS
- Total Pixels: 510 x 492
- Resolution: 380 TV Ilnes
- Night Vision Low Lighting Capable
- 10 IR LED Lights
- Min. Illumination: 0.5 LUX
- Auto Image Adjustment
- Video Output: 1.0Vpp-75?
- Power Supply: DC12V 200Ma
- Dimensions: 1.25" (W) x 1.25" (H) x 77" (L)



PLCM105 10.2" TFT LCD Rear View Mirror Monitor W/ Back Up Camera Night Vision & Waterproof

10.2" Rear View Mirror Monitor:

- Display Mode: Left 4.5", 5.6", 7", 8.5"
- Display Mode: Right, 8.5", 7", 5.6", 4.5"
- Touch Buttons
- Power Supply: DC12V
- Resolution: 800 X RGB X 240
- 2 Video Inputs
- Anti-Glade Mirror

- Mirror Dimensions: 10.7" x 4.3" x 1.0"
- Net weight: 0.9 KG
- Universal Mount Rear View Backup Color Camera
- Distance Scale Line Camera
- Resolution: 420 TV Lines
- Power Supply: DC 12V
- Camera Dimension: 0.67" (W) x 0.67" (H) x 0.9" (L)



PLCM36 3.5" Slim TFT LCD Digital Universal Mount Monitor w/ License Plate Mount

Screen Description:

- 3.5" slim TFT LCD Stand Monitor
- Automatically Switched On When Reversing
- Two Video Inputs
- PAL/NTSC Compatible
- Auto Switching
- Brightness: 200CD/M2
- Contrast ratio: 200:1
- Dimensions: 3.7"W x 3.3"H x 0.67"D

Camera Description:

- Output Standard: PAL/NTSC Compatible
- High Resolution: 380TV lines x 60 fields
- Image Sensor: OV7910 color CMOS
- Lens: 6MM 92 degree
- Low Light Illumination: 1.5LUX/ F1.2
- Video Output: RCA 1.0 VPP composite video @ 75OHM
- Power Supply: Dc12v
- Temperature: -10~ 50 Celsius
- Unit Dimensions: 1.3"H x 8"W x 1.26"D



PLCM4300WR Rearview Mirror Wireless Back-Up Camera System w/ 4.3" TFT Touch Screen & Universal Mount

- 4.3" TFT/ LCD Video Monitor Built-In into Full Size Rearview Mirror w/ Built-In Anti-Glare
- Touch Screen On Screen Display
- Universal Clip On Over Existing Rearview Mirror
- 16:9 Wide Screen Video Format
- Resolution: 480(H) x 271(V)
- Dual Video Inputs AV1 (DVD, TV, GPS, ETC) AV2 (camera) with Automatic Reverse Line Trigger
- Signal System: NTSC/PAL/Auto Switch
- Contrast Ratio: 300:1

- 2.4 Gig Hz Wireless Video Sender & Receiver Allows for Wireless Video Transfer from rear Mount Camera to Front Mount Video Monitor (Max Distance 25 Meter/ 82.02 Feet)
- Universal Mount Micro Sized Video Camera
- Low Lux Night Vision Camera with CMD sensor
- 170° L/R Viewing Angle
- Power Supply DC 12 Volts
- Mirror Dimensions: 10.78"W x 3.03"H x 0.98"D
- Camera Dimensions: 0.59" Dia x 0.82" D



PLCM4500 Universal 4.3" Pop-Up Stealth Monitor & Aluminum Black Chrome License Plate for Rear View Camera

Monitor:

- Screen Size: 4.3 Inches
- Universal monitor back up camera screen system sits on your dash, Monitor pop-ups out of enclosure and folds back in when not in use
- TFT-LCD Color Monitor - Contrast: 350:1
- Video Color System: NTSC
- Video sense input - turns on when video signal is received
- Rear-view Camera Priority for signal sense

- Power Supply: DC12V @ 115ma
 - Dimensions (Closed): 13.5" (W) x 11" (D) x 2.1" (H)
- #### Camera:
- 420 Line Horizontal Resolution
 - Adjustable Angle Lens Pivot
 - Built-in Distance Scale Line
 - True Color Reproduction
 - Low Lux Enhanced Night Viewing for Low Light Applications
 - Resolution: 420 TV Lines



NEW!
for 2013

PLCM4700 4.7" Window Suction Mount TFT/LCD Monitor w/ Die Cast License Plate

Monitor:

- 4.7" TFT-LCD monitor
- Window suction mount
- 16:9 wide screen
- Pal/NTsc system
- High resolution
- Wireless remote control
- Two video inputs
- Power supply: DC12V
- Cigarette lighter plug
- Brightness: 300CD
- Contrast: 200:1
- Camera: License plate mount back up rearview color camera

- Black zinc aluminum die cast chrome
- Distance scale line
- True color reproduction
- Low lux performance of 0.2 lux night vision
- Total pixels: 656 x 492 • Resolution: 420 TV lines
- Viewing angle: 170 degree
- Auto white balance
- Water proof, fog resistant
- Low light capable
- Power supply: DC12V
- 17 foot male to male RCA video cable
- Dimension: 10"W x 1.3"H x 1.26"D



NEW!
for 2013

PLCM7200 7" TFT Mirror Monitor w/ License Plate Mount Rear View Night Vision

- 7" TFT (16:9) Wide Screen
- Universal Clip on Existing Mirrors
- Wireless Remote Control
- Resolution: 480xRGBx234
- Contrast Ratio: 400 CD/M2
- Viewing Angle: U/D90° L/R120°
- Power Consumption: 6W

- Auto Switch PAL/NTSC
- Dual Video Input (DVD/CAMERA/GAME)
- Rearview Night Vision Camera
- License Plate Mount
- Anti Glare Mirror
- Screen Dimensions: 10.19"W x 4.25"H x 1.81"D
- Camera Dimensions: 8.46" W x 1.29" H x 1.37"D



2013 Complete Product Catalog

PLCM7300BT 7" TFT Mirror Monitor W/ Rear-View Night Vision Camera Built-In Bluetooth

- 7" TFT (16:9) Wide Screen
- Universal Clip On Existing Mirrors
- Wireless Remote Control
- Resolution: 480 X RGB X 234
- Contrast Ratio: 400 CD/M2
- Viewing Angle: U/D90° L/R120°
- Power Consumption: 6W
- Auto Switch PAL/NTSC

- Dual Video Input(DVD/CAMERA/GAME)
- Rearview Night Vision Camera
- Built-In Bluetooth System
- Display In-coming Calls
- License Plate Mount
- Anti Glare Mirror
- Screen Dimensions: 10.19" W X 4.25" H X 1.81"D
- Camera Dimensions: 8.46" W X 1.29" H X 1.37"D



PLCM7500 7" Window Suction Mount TFT/LCD Video Monitor w/ Universal Mount

Monitor:

- 7" TFT-LCD monitor
- With window mount bracket
- 16:9 wide screen• Pal/Ntsc system
- High resolution
- Wireless remote control
- Two video inputs• Power supply: DC12V
- Dimension: 7.60"W x 5.24"H x 0.98"D

Camera:

- License plate mount back up rearview color camera
- Black zinc aluminum die cast chrome
- Distance scale line

- True color reproduction
- Low lux performance of 0.2 lux night vision
- Total pixels: 656 x 492
- Resolution: 420 TV lines
- Viewing angle: 170 degree
- Auto white balance
- Water proof, fog resistant
- Low light capable
- Power supply: DC12V
- 17 foot male to male RCA video cable
- Dimension: 10"W x 1.3"H x 1.26"D



NEW!
for 2013

PLCM7700 7" Window Suction Mount TFT/LCD Video Monitor w/ Universal Mount

7" TFT-LCD monitor:

- Universal stand bracket included
- Window suction mount
- 16:9 wide screen
- PAL/NTSC system
- High resolution
- Wireless remote control
- Two video inputs
- Power supply: DC12V
- Dimension: 7.60"W x 5.24"H x 0.98"D
- Camera:
- Backup CMD camera 1/3"

- Water proof/Night vision
- Distance scale line camera
- 17 foot male to male RCA video cable
- Image sensors: 580x540
- Total pixels: 580x540
- Resolution: 420 TV lines
- Min. illumination: 1.0 lux
- IP rating: 68; lens angle: 170'
- Auto image adjustment
- Video output: 1.0Vpp-75Ohm
- Power supply: DC12V
- Dimension: 0.67"W x 0.67"H x 0.9L



PLCM7800 7" TFT/LCD Mirror Monitor with License Plate Mount Rearview Backup Color Camera

Monitor:

- 9.2inch TFT LCD (16:9) wide screen
- Universal clip on existing mirrors
- Wireless remote control
- Resolution: 800 x RGB x 480
- Power consumption: 7W
- Pal/Ntsc auto switch
- Dual video inputs
- Anti glare mirror

Camera:

- License plate mount back up rearview camera
- Black zinc aluminum die cast chrome
- Distance scale line

- True color reproduction
- Low lux performance of 0.2 lux night vision
- Total pixels: 656 x 492
- Resolution: 420 tv lines
- Viewing angle: 170 degree
- Auto white balance
- Water proof(IP67), fog resistant
- Low lighting capable

Accessories:

- Video output: 1.0V PP, 75 Ohm
- Power supply: DC12V, 200mA
- 17 feet male to male RCA video cable
- Dimension: 10"(W) X 1.3"(H) X 1.26"(D)

NEW!
for 2013



PLCM9200 9.2" TFT/LCD Mirror Monitor with License Plate Mount Rearview Backup Color Camera

Monitor:

- 9.2inch TFT LCD (16:9) wide screen
- Universal clip on existing mirrors
- Wireless remote control
- Resolution: 800 x RGB x 480
- Power consumption: 7W
- Pal/Ntsc auto switch
- Dual video inputs
- Anti glare mirror

Camera:

- License plate mount back up rearview color camera
- Black zinc aluminum die cast chrome

- Distance scale line
- True color reproduction
- Low lux performance of 0.2 lux night vision
- Total pixels: 656 x 492
- Resolution: 420 tv lines
- Viewing angle: 170 degree
- Auto white balance
- Water proof(IP67), fog resistant
- Low lighting capable• Video output: 1.0V PP, 75 Ohm
- Power supply: DC12V, 200mA• 17 feet male to male RCA video cable
- Dimension: 10"(W) X 1.3"(H) X 1.26"(D)

NEW!
for 2013



PYLE®

***For a complete list of detailed product information and specifics, remember to visit PyleAudio.com and search the item model number.**

PLPSE4P

4 Parking Sensor System & Led Display

- 6 Piece Rear Parking System (Sensors x 4, Brain, Display)
- 4 x 1" Diameter Wired Rear Sensors (9 Foot)
- Digital Distance Object Wired Indicator (25 Foot)
- 4 Color 7 Stage Led Indicator
- 4 Stage Built-in Beeping Alarm
- Display Distance: 2.0m ~ 0.3m

- Reverse Sensor Trigger
- Sensor Cutout Tool Included
- Dc 12v Application
- Display Dimensions: 0.75" (H) X 4.25" (W) X 1.25" (L)
- Dimensions(Brain): 1" (H) X 3.65" (W) X 2.15" (L)



PLCD42M

AM/FM-MPX Anti-Shock CD/USB/SD/MP3 Player with AUX, Input & Remote Control

- AM/FM Tuner
- CD/MP3 Player
- SD/USB Interface
- Auxiliary Input
- Anti-Theft Detachable Face
- DSP: Pop/Rock/Classic/Flat
- Auto Station Search with Memory
- Reads ID3 Tag Info

- Big LCD Display
- 30 Station Memory: 18FM/12AM
- Pause/Intro/Repeat/Random
- RCA Preamp Output
- ISO/DIN Chassis
- Remote Control Included
- 240W Maximum Total Output



PLCDUSB78MP3

AM/FM-MPX CD/MP3 Player w/USB/SD Input & Motorized Slide Down Detachable Face

- AM/FM-Tuner CD/MP3 Player
- PLL Synthesizer Tuning
- Motorized Slide Down Detachable Face
- DSP: Pop/Rock/Classic/Flat
- Auto Best Station Memory/Preset Scan
- CD-R/CD-RW for MP3 Playback
- ID3 Tag Information
- Electronic Anti-Shock for CD/MP3
- Pause/Intro Scan/Repeat/Random

- Mode Button: Radio/CD/MP3/USB/SD
- 30 Station Memory: 18FM/12AM
- Audio Control: Volume/ Balance /Bass/Treble/ Fad
- Local/ Distance/ Mono/ Stereo Button
- Loudness/ Mute/ Clock Button
- RCA Preamp Output
- Remote Control
- 240 Watts Maximum Total Output
- Unit Dimensions: 7"W x 6.75"D x 1.96"H



PLCD43MPU

AM/FM-MPX CD/MP3 Player w/USB/SD Input Detachable Face

- Auto Loading MP3/CD/CD-R/CD-RW Player
- AM/FM 2-Band PLL Tuning Radio
- Built-In USB/SD
- Aux-In on Front
- Detachable Front Panel
- Electronic Shock Protection (ESP)
- LCD Digital Display
- ID3 TAG function
- Full CD/MP3 Features: Rpt/Dn/Up

- Auto Seek - Auto Store
- Full Stereo System
- 30 Preset Memory Stations
- Bass/Tre/Bal/Fader functions
- Clock Function
- 4-Channel Output
- RCA Line Out
- Remote Control
- Preset EQ Function (Pop/Rock/Classic)

NEW!
for 2013



PLR14MPF

In-Dash AM/FM-MPX MP3 Shaft Style Dual Knob Radio w/USB/SD Card

- AM/FM-MPX/USB/SD MP3 Stereo
- Classic Car Audio Replacement Allows For Zero Dash Board Modification using Shaft Style Openings
- Built-In USB/ SD/ MMC MP3 Player (2 Gig Max)
- Volume/ Balance/ Tone Control
- 1.2 Volt RCA Line Out (Amplifier Line Output)
- 2 Channel Output 80W x 2 (160W Max)

- Adjustable Shaft Knobs from 4.65"-5.5"
- Mounting Hardware Included
- DC 12 Volt 3 Amp Power Consumption
- Unit Dimensions: 7"W x 4.72"D x 1.96"H

NEW!
for 2013



2013 Complete Product Catalog

PLR15MUA

In-Dash AM/FM Radio with USB/SD Card Readers, Aux-In & MP3 Player

- RCA Line Out
- Car MP3 Player
- Clock Function
- Built-In USB/SD
- Aux-In on Front
- 4-Channel Output

- ID3 TAG function
- LCD Digital Display
- Auto Seek *Auto Store
- 30 Preset Memory Stations
- AM/FM 2-Band PLL Tuning Radio
- Preset EQ Function (Pop/Rock/Classic)

NEW!
for 2013



PLR16MPF

In-Dash AM/FM-MPX Receiver MP3 Playback with USB/SD Card

- AM/FM-MPX Stereo Tuning
- Digital LCD Display Panel
- USB/SD/MMC MP3 Player
- Volume/Balance Control
- AM Frequency Range: 520~1710kHz

- FM Frequency Range: 87.5~108MHz
- RCA Line Out (4Ch)
- 160 Watts Total Output(4 x 40 Watts)
- Dimensions: 7"W x 4.72"D x 1.96"H

NEW!
for 2013



PLR16MUA

In-Dash AM/FM-MPX Receiver MP3 Playback with USB/SD Card

- AM/FM-MPX Stereo Tuning
- Digital LCD Display Panel
- USB/SD/MMC MP3 Player
- Auxiliary Input
- Volume/Balance Control

- AM Frequency Range: 520~1710kHz
- FM Frequency Range: 87.5~108MHz
- RCA Line Out (4Ch)
- 160 Watts Total Output(4 x 40 Watts)
- Dimensions: 7"W x 4.72"D x 1.96"H



PLR17MPUA

In-Dash AM/FM-MPX Receiver MP3 Playback w/ USB/SD Card & Aux

- AM/FM-MPX Stereo Tuning
- Digital LCD Display Panel
- USB/SD/MMC MP3 Player
- Auxiliary Input
- 30 Preset Stations (18FM/12AM)
- Volume/Balance Control

- AM Frequency Range: 530~1710kHz
- FM Frequency Range: 87.5~108MHz
- RCA Line Out (4Ch)
- 200 Watts Total Output (4 x 50 Watts)
- Dimensions: 7"W x 4.72"D x 1.96"H

NEW!
for 2013



PLR24MPM

AM/FM Receiver MP3 Playback with USB/SD/AUX-IN

- AUX-In Jack
- Tone Control
- ID3 Tag Function
- LCD Digital Display
- Last-Track Memory
- Mute & Clock Functions
- Folder Up/Down Function

- AM/FM 2-Band Radio (USA)
- Rotary Tuning/Volume Control
- Built-In Front-Loading USB/SD Ports
- 2-Channel Output 60 Watt x 4 (240 Watt Max)
- 10 Songs Skip Up/ 10 Songs Skip Down Function
- Chassis Dimensions: 7.0" W x 5.5" D x 1.96" H

NEW!
for 2013



PLR26MPU

AM/FM Radio With SD/USB/MP3 Playback, 3.5mm Aux-In

- AM/FM Tuner
- 30 Preset Station Memory
- USB/SD Compatible - Play Back Your Favorite Digital Music
- Front Auxiliary Input Jack - Connect Virtually Any Digital Music Player
- LCD Digital Display

- ID3 Tag Display
- Intro/Repeat/Random Playback Modes
- Clock/Mute Functions
- Blue Button Illumination
- RCA Line Output
- 4 x 80 Watt Output
- Treble/Bass Control

NEW!
for 2013



PLR27MPBU AM/FM Radio With SD/USB/MP3 Playback, 3.5mm Aux-In, Bluetooth

- AM/FM Tuner
- 30 Preset Station Memory
- USB/SD Compatible - Play Back Your Favorite Digital Music
- Front Auxiliary Input Jack - Connect Virtually Any Digital Music Player
- Stream Music From Your Bluetooth Device (iPhone, Android, BlackBerry, Etc.)
- LCD Digital Display
- ID3 Tag Display
- Intro/Repeat/Random Playback Modes
- Clock/Mute Functions
- Blue Button Illumination
- RCA Line Output
- 4 x 80 Watt Output
- Treble/Bass Control



PLR33MPD AM/FM Band Radio USB/SD Receiver w/ Detachable Face

- AM/FM-MPX PLL Tuning
- USB Slot & SD/MMC Card Port For MP3/WMA Music Files Playback
- Preset Equalizer
- Encoding Volume, Balance, Bass, Treble & Fader Control
- 30 Radio Preset Station Memory 18GM-12AM
- Front Auxiliary Input Jack
- Fold Down Detachable Panel
- Full Function Remote Control
- Seek/ Scan Function
- ID Tag
- AM Frequency Range: 530-1710 KHz
- FM Frequency Range: 87.5-107.9 MHz
- 4 x 60 Watts Maximum Power Output
- Dimensions: 17.8" W x 10.5" H x 5.0" D



PLR34M In-Dash AM/FM-MPX Receiver With MP3 Playback & USB/SD/Aux Inputs

- AM/FM-MPX PLL Tuning Car Radio
- Dot Matrix White LCD Display
- MP3 ID3 Tag Digital Readout Compatible
- USB Slot & SD/MMC Card Port For MP3/WMA Music Files Playback
- Encoding Volume, Balance, Bass, Treble & Fader Control
- 30 Radio Preset Station Memory 18FM-12AM
- Front Auxiliary Input Jack
- Stereo RCA Line Out Jack
- Full Function Remote Control
- Blue Button Illumination Controls
- Seek/Scan Function
- AM Frequency Range: 530~1710kHz
- FM Frequency Range: 87.5~107.9MHz
- 4 x 60 Watts Maximum Power Output
- Dimensions: 7"W x 4.72"D x 1.96"H



PLR36BTU In-Dash AM/FM-MPX Detachable Face Receiver with Bluetooth, MP3 Playback & USB/SD/Aux Inputs

- Car MP3 Player with Bluetooth function
- AM/FM 2-Band PLL Tuning Radio
- Built-In USB/SD
- Aux-In on Front
- Wireless Connect to Mobile phone
- Handsfree talk
- Receive / cancel call function
- LCD Digital Display
- Auto Seek & Auto Store
- 30 Preset Memory Stations
- Preset EQ Function (Pop/Rock/Classic)
- Clock Function
- 4-Channel Output
- Remote Control
- RCA Line Out



PLR44MU In-Dash AM/FM-MPX Detachable Face Receiver With MP3 Playback & USB/SD/Aux Inputs

- AM/FM-MPX PLL Tuning Car Radio
- Dot Matrix White LCD Display
- Detachable Face Panel
- MP3 ID3 Tag Digital Readout Compatible
- USB Slot & SD/MMC Card Port For MP3/WMA Music Files Playback
- Controls: Volume, Balance, Bass, Treble & Fader
- 30 Radio Preset Station Memory 18FM-12AM
- Front Auxiliary Input Jack
- Stereo RCA Line Out Jack
- Full Function Remote Control
- Blue Button Illumination Controls
- Seek/Scan Function
- AM Frequency Range: 530~1710kHz
- FM Frequency Range: 87.5~107.9MHz
- 4 x 60 Watts Maximum Power Output
- Dimensions: 7"W x 4.72"D x 1.96"H



PLRCS10U AM/FM 2 Band Radio Digital Car Cassette Player MP3 Compatible Built-In USB/ AUX-IN

- AM/FM 2 Band Radio
- Anti-Theft Pullout System
- Digital Display
- Clock Function
- Cassette Player
- AUX Inout Front Panel
- Built-In USB Port
- MP3 Compatible
- 4 Channel Output
- Night Illumination
- RCA Preamp Output
- Auto Antenna Lead
- 200 Watts Output
- Chassis Dimensions: 7.1" (W) x 5.5" (D) x 2" (H)



2013 Complete Product Catalog

PLR381 AM/FM/MP3/WMA Detachable Face Player W/ USB/SD Reader & Ipod

- AM/FM 2-Band Radio (USA)
- Semi-Detachable Faceplate
- Front Side IPOD Connector
- Built-In USB/SD Ports (Front)
- LCD Multi-Color Digital Display
- ID3 Tag Function
- Tone Control
- Rotary Tuning/Volume Control
- AUX-IN Jack (Front)
- Last-Track Memory
- 10 Songs Skip Up/ 10 Songs Skip Down
- Folder Up/Down Function
- Mute Function
- 2-Channel output 50W x 4 (200w Max)
- Unit Dimensions: 7"W x 5.5"D x 1.96"H



PIMPTR5R Plug In Car Gooseneck Mount FM Transmitter With Built-in SD/USB/MP3

- Flexible metallic hose can be bended and adapted for any type of autos
- 1.4" large screen display the song's name and lyrics
- Supports Usb disk & SD/MMC card
- Supports MP3/WMA format
- Supports folder switch & 6 loop mode
- Full Band With Frequency Range From 87.5-108MHZ
- Supports 12-24V voltage



PLMP3C1 Plug In Car MP3/USB/SD/Ipod Wireless FM Transmitter/Modulator

All Models Include:

- FM Transmitter with 206 channels optional :87.5-108MHZ
- 1.4" LCD Display Screen with ID3 Tag
- Supports USB Flash & SD / MMC Cards
- Line-in function supports other devices:
- Powered by 12-24V voltage
- Supports MP3 format files
- Remote Control Included

*Bluetooth Handse-Free Model:

PLMP3C21

*MP4 Compatible Model:

PLMP3C31B



Mobile SD/USB/MP3 Compatible Player

With Built-In FM Transmitter

- LCD Display Screen
- Built-In Wireless Transmitter
- with 206 Channel
- Frequency Capable: (87.5-108MHz)
- USB/SD Card Compatible
- 3.5 AUX Input Adaptor
- Adjustable Multi Angle Viewing
- Wireless Remote Control
- DC 12Volt Compatible
- Blue color Cigarette Lighter



PLV12V2 1 TO 2 Cigarette Lighter Multiplier

- Powers two 12 Volt Electronic Items
- Chrome Shafted Design
- Two Front Mount Female Cigarette Lighter Ports
- Single Rear Mount Male Cigarette Lighter Power Source
- Ultra Bright LED Indicator
- Input 12~24 Volt DC



PL12AT3C-PL12VP3C Plug In Car 1 TO 3 Cigarette Lighter Multiplier Ashtray

- Powers three 12 Volt Electronic Items
- Two Piece Unit Construction with Functional Ashtray
- Fits Securely in Most Cupholder's
- Three Top Mount Female Cigarette Lighter Ports
- Single Corded Male Cigarette Lighter Power Source
- Input 12~24 Volt DC



PL12V1 Plug In Car Cigarette Lighter Port Extension

- Powers One DC 12 Volt Item
- Single Female Cigarette Lighter corded Power Port
- Single Rear Mount Male Cigarette Lighter Power Source
- Input 12~24 Volt DC



PL12V2AC

Plug In Car 1 TO 2 Cigarette Lighter Multiplier & Adjustable AC Voltage

- Powers two 12 Volt Electronic Items
- Two Front Mount Corded Female Cigarette Lighter Ports
- Single Corded Male Cigarette Lighter Power Source
- Adjustable AC Voltage with 4 way Port
- Input 12~24 Volt DC



PL12V2CP

Plug In Car 1 TO 2 Cigarette Lighter Multiplier

- Powers Five 12 Volt Electronic Items
- Two Top Mount Female Cigarette Lighter Ports with Covers
- Single Corded Male Cigarette Lighter Power Source
- Input 12~24 Volt DC



PL12V2P

Plug In Car 1 TO 2 Cigarette Lighter Multiplier

- Powers two 12 Volt Electronic Items
- Two Front Mount Corded Female Cigarette Lighter Ports
- Single Corded Male Cigarette Lighter Power Source
- Input 12~24 Volt DC



PL12V2US

Plug In Car 1 TO 2 Cigarette Lighter Multiplier With USB Charger

- Powers two 12 Volt Electronic Items
- 5 Volt USB Fullsize Female Port
- Two Front Mount Female Cigarette Lighter Ports
- Single Corded Male Cigarette Lighter Power Source
- Ultra Bright LED Indicator
- Input 12~24 Volt DC



PL12V3P

Plug In Car 1 TO 3 Cigarette Lighter Multiplier & Power Control Station

- Powers Three 12 Volt Electronic Items
- Three Front Mount Corded Female Cigarette Lighter Ports
- Single Corded Male Cigarette Lighter Power Source
- Individual Power Control Stations
- Input 12~24 Volt DC



PL12V3US

Plug In Car 1 TO 3 Cigarette Lighter Multiplier With USB Charger

- Powers Three 12 Volt Electronic Items
- 5 Volt USB Fullsize Female Port
- Three Front Mount Female Cigarette Lighter Ports
- Single Corded Male Cigarette Lighter Power Source
- Ultra Bright LED Indicator
- Input 12~24 Volt DC



PL12V4P

Plug In Car 1 TO 4 Cigarette Lighter Multiplier & Power Control Station

- Powers Four 12 Volt Electronic Items
- Four Front Mount Corded Female Cigarette Lighter Ports
- Single Corded Male Cigarette Lighter Power Source
- Individual Power Control Stations
- Input 12~24 Volt DC



PL12V5V

1 TO 5 Cigarette Lighter Multiplier

- Powers Five 12 Volt Electronic Items
- Five Front Mount Female Cigarette Lighter Ports
- Single Corded Male Cigarette Lighter Power Source
- Input 12~24 Volt DC



2013 Complete Product Catalog

For More Products
and Detailed Information
Visit PyleAudio.com



PLA2260



PLA1200

PLA1200 1900 Watts Mono Block Mosfet Power Amplifier

- RMS Power @ 4 Ohms: 200 W
- RMS Power @ 2 Ohms: 350 W
- RMS Power @ 1.3 Ohms: 600 W
- Maximum Power Output 1900W Mono
- Variable Low Electronic Crossover Network
- Variable Input Level (Gain) Control
- Variable Bass Boost - Low Level Inputs
- 2 Ohm Stable - Sub Sonic Filter
- Thermal / Overload / Short Circuit Protection
- MOSFET PWM Power Supply
- Power And Protection LED Indicators
- RCA Inputs And Outputs
- Slim Size Amplifier Design For Easy Installation
- 2x20 Amp Maxi Type Fuse
- Dimensions: 10.63"W x 1.42"H x 12"L

PLA2200 2 Channel 1400 Watt Bridgeable Mosfet Amplifier

- 700 Watts x 2 Output
- 1400 watts x 1 Bridged Output
- Variable Hi/Lo Electronic Crossover Network
- Variable Input Level (Gain) Control
- Switchable Bass Boost
- Power And Protection LED Indicators
- Low Level Inputs
- RCA Inputs Outputs
- Slim Size Amplifier Design For Easy Installation
- Thermal / Overload / Short Circuit Protection
- Anti-Thump Turn-on - Soft Turn-On Circuit
- Remote Turn On/Off
- 2x10 Amp Maxi Type Fuse
- Freq. Response: 15Hz - 30KHz
- Dimensions: 10.63" H x 1.42" W x 8.75" L

PLA2210 2 Channel 1800 Watt Bridgeable Mosfet Amplifier

- 900 Watts x 2 Output
- 1800 watts x 1 Bridged Output
- Variable Hi/Lo Electronic Crossover Network
- Variable Input Level (Gain) Control
- Switchable Bass Boost
- Power And Protection LED Indicators
- Low Level Inputs - RCA Inputs Outputs
- Slim Size Amplifier Design For Easy Installation
- Thermal / Overload / Short Circuit Protection
- Anti-Thump Turn-on - Soft Turn-On Circuit
- Remote Turn On/Off
- S/N Ratio: 95db - T.H.D: 0.04%
- 2x15 Amp Maxi Type Fuse
- Freq. Response: 15Hz - 30KHz
- Dimensions: 10.63" H x 1.42" W x 12" L

PLA2220 2 Channel 2400 Watt Bridgeable Mosfet Amplifier

- 1200 Watts x 2 Output
- 2400 watts x 1 Bridged Output
- Variable Hi/Lo Electronic Crossover Network
- Variable Input Level (Gain) Control
- Switchable Bass Boost
- Power And Protection LED Indicators
- Low Level Inputs - RCA Inputs Outputs
- Thermal / Overload / Short Circuit Protection
- Anti-Thump Turn-on - Soft Turn-On Circuit
- Remote Turn On/Off
- S/N Ratio: 95db - T.H.D: 0.04%
- 2x20 Amp Maxi Type Fuse

PLA2230 3000 Watts 2 Channel High Power Mosfet Amplifier

- 1500 Watts x 2 Output
- 3000 Watts x 1 Bridged Output
- Variable Hi/Lo Electronic Crossover Network
- Variable Input Level (Gain) Control
- Variable Bass Boost - Sub Sonic Filter
- Thermal / Overload / Short Circuit Protection
- MOSFET PWM Power Supply
- Power And Protection LED Indicators
- Low Level Inputs - RCA Inputs And Outputs
- Slim Size Amplifier Design For Easy Installation
- 2x25 Amp Maxi Type Fuse
- Dimensions: 10.63"W x 1.42"H x 17"L

PLA2260 2 Channel 4000 Watt High Power Mosfet Amplifier

- 2000 Watts x 2 Output
- 4000 Watts x 1 Bridged Output
- Variable Hi/ Lo Electronic Crossover Network
- Variable Input Level (Gain) Control
- Variable Bass Boost - Sub Sonic Filter
- Thermal/ Overload/ Short Circuit Protection
- MOSFET PWN Power Supply
- Power And Protection LED indicators
- Low Level Inputs - RCA Inputs And Outputs
- Slim Size Amplifier Design For Easy Installation
- 2x35 Amp Maxi Type Fuse
- Dimensions: 10.63" (W) x 1.42" (H) x 21" (L)

PLA4120 1000 Watts 4 Channel High Power Mosfet Amplifier

- 250 Watt x 4 Output
- 500 Watt x 2 Bridged Out (250Wx2 + 500W x 1)
- Dual Variable Hi/Lo Electronic Crossover Network
- Dual Switchable Bass Boost
- Dual MOSFET PWM Power Supplies
- Dual Variable Input Level (Gain) Control
- Thermal / Overload / Short Circuit Protection
- Power And Protection LED Indicators
- Low Level Inputs
- RCA Inputs And Outputs
- Slim Size Amplifier Design For Easy Installation
- 2x10 Amp Maxi Type Fuse



PLA1800



PLA2378

PLA1800 1 Channel 2400 Watts Bridgeable Mosfet Amplifier

- RMS Power @ 4 Ohms: 1 x 300W
- RMS Power @ 2 Ohms: 1 x 500W
- RMS Power @ 1.3 Ohms: 1 x 700W
- Maximum Power Output 2400W Mono
- Mono Block Sub woofer Amplifier
- Frequency Response 10 Hz-300 Hz (± 3 dB)
- Output Power @ 14.4v DC, 50Hz
- MOSFET Power Supply - Soft Turn On/ Off
- PWM (Pulse-Width-Modulation) System
- Glass Epoxy PCB - Silver RCA Inputs
- Custom Terminal Block for Speaker Connection
- Thermal / Overload / Short Circuit Protection
- Variable Subsonic Filter (15Hz - 40Hz 24dB)
- Remote Bass Boost
- Input Impedance: 10K Ohms

PLA2378 2 Channel 2000 Watts Bridgeable Mosfet Amplifier

- Maximum Power Output 2 x 1000W
- Bridgeable RMS Power @ 4 Ohms: 1x2000W
- 2 Channel Bridgeable MOSFET Amplifier
- Frequency Response 20 Hz-50kHz (± 3 dB)
- Output Power @ 14.4v DC, 50Hz
- 2 Ohm Stable - Soft Turn On/ Off
- MOSFET Power Supply
- PWM (Pulse-Width-Modulation) System
- Glass Epoxy PCB - Silver RCA Inputs
- Custom Terminal Block for Speaker Connection
- Thermal / Overload / Short Circuit Protection
- Input Impedance: 47K Ohms
- Advanced Protection Circuitry
- S/N Ratio: >90dB
- Dimensions: 10.24"W x 2.21"H x 11.02"L

PLA2678 2 Channel 4000 Watts Bridgeable Mosfet Amplifier

- Maximum Power Output 2 x 2000W
- Bridgeable RMS Power @ 4 Ohms: 1x4000W
- 2 Channel Bridgeable MOSFET Amplifier
- Frequency Response 20 Hz-50kHz (± 3 dB)
- Output Power @ 14.4v DC, 50Hz
- 2 Ohm Stable - Soft Turn On/ Off
- MOSFET Power Supply
- PWM (Pulse-Width-Modulation) System
- Glass Epoxy PCB
- Silver RCA Inputs
- Custom Terminal Block for Speaker Connection
- Thermal / Overload / Short Circuit Protection
- Input Impedance: 47K Ohms
- Advanced Protection Circuitry
- S/N Ratio: >90dB

PLA2978 2 Channel 5000 Watts Bridgeable Mosfet Amplifier

- Maximum Power Output 2 x 2500W
- Bridgeable RMS Power @ 4 Ohms: 1 x 5000 W
- 2 Channel Bridgeable MOSFET Amplifier
- Frequency Response 20 Hz-50kHz (± 3 dB)
- Output Power @ 14.4v DC, 50Hz
- 2 Ohm Stable - Soft Turn On/ Off
- MOSFET Power Supply
- PWM (Pulse-Width-Modulation) System
- Glass Epoxy PCB - Silver RCA Inputs
- Custom Terminal Block for Speaker Connection
- Thermal / Overload / Short Circuit Protection
- Input Impedance: 47K Ohms
- Advanced Protection Circuitry
- S/N Ratio: >90dB
- Dimensions: 10.24"W x 2.21"H x 18.90"L

PLA4278 4 Channel 2000 Watts Bridgeable Mosfet Amplifier

- Maximum Power Output 4 x 500W
- Bridgeable RMS Power @ 4 Ohms: 2 x 1000W
- 4 Channel Bridgeable MOSFET Amplifier
- Frequency Response 20 Hz-50kHz (± 3 dB)
- Output Power @ 14.4v DC, 50Hz
- 2 Ohm Stable - Soft Turn On/ Off
- MOSFET Power Supply
- PWM (Pulse-Width-Modulation) System
- Glass Epoxy PCB - Silver RCA Inputs
- Custom Terminal Block for Speaker Connection
- Thermal / Overload / Short Circuit Protection
- Input Impedance: 47K Ohms
- Advanced Protection Circuitry
- S/N Ratio: >90dB
- Dimensions: 10.24"W x 2.21"H x 14.58"L

PLA4478 4 Channel 4000 Watts Bridgeable Mosfet Amplifier

- Maximum Power Output 4 x 1000W
- Bridgeable RMS Power @ 4 Ohms: 2 x 2000W
- 4 Channel Bridgeable MOSFET Amplifier
- Frequency Response 20 Hz-50kHz (± 3 dB)
- Output Power @ 14.4v DC, 50Hz
- 2 Ohm Stable - Soft Turn On/ Off
- PWM (Pulse-Width-Modulation) System
- Glass Epoxy PCB - Silver RCA Inputs
- Custom Terminal Block for Speaker Connection
- Thermal / Overload / Short Circuit Protection
- Advanced Protection Circuitry
- Dimensions: 10.24"W x 2.21"H x 17.72"L

PLA4600D 4600 Watts Mono Class D Amplifier

- Class D Monoblock Power Amplifier
- RMS Power @ 4 Ohms: 1 x 1200W
- RMS Power @ 2 Ohms: 1 x 1800W
- RMS Power @ 1.3 Ohms: 1 x 2400W
- Maximum Power Output 4600W Mono
- Mono Block Sub woofer Amplifier
- Frequency Response 15 Hz-150 Hz (± 3 dB)
- Output Power @ 14.4v DC, 50Hz
- MOSFET Power Supply - 1 Ohm Stable
- PWM (Pulse-Width-Modulation) System
- Glass Epoxy PCB - Silver RCA Inputs
- Custom Terminal Block for Speaker Connection
- Thermal / Overload / Short Circuit Protection
- Variable Subsonic Filter (15Hz - 55Hz 24dB)
- Protection Circuitry - Remote Bass Boost

2013 Complete Product Catalog



PLAM2001D



PLAM1200

PLAM1000 1000 Watts 2 Channel Bridgeable Amplifier

- Two Channel Bridgeable Amplification
- Tri-way Configuration: 1/2 Channels
- 2 X 500Watts Total Output @ 4 Ohms
- 1000 Watts Total System Output @ 4 Ohms
- MOSFET Pulse Width Modulated Power Supply
- 2 Ohm Stereo Stable - RCA Low Level Inputs
- Built-In Variable Subwoofer Crossover
- Speaker Output Terminal Strip
- Signal/Noise Ratio 90dB - THD <0.04%
- Frequency Response: 15Hz-30kHz

- Overload, Thermal & Short Circuit Protection
- LED Diagnostic Condition Indicator
- Automotive Type Fuse Protection
- Dimensions: 7.28"L 9.76"W 2.26"H

PLAM1200 1200 Watts 2 Channel Bridgeable Amplifier

- Two Channel Bridgeable Amplification
- Tri-way Configuration: 1/2 Channels
- 2 X 600 Watts Total Output @ 4 Ohms
- 1200 Watts Total System Output @ 4 Ohms
- MOSFET Pulse Width Modulated Power Supply
- 2 Ohm Stereo Stable - RCA Low Level Inputs
- Built-In Variable Subwoofer Crossover
- Speaker Output Terminal Strip
- Signal/Noise Ratio 90dB - THD <0.04%
- Frequency Response: 15Hz-30kHz

- Overload, Thermal & Short Circuit Protection
- Power On LED Indicator - Variable Gain Control
- LED Diagnostic Condition Indicator
- Automotive Type Fuse Protection
- Dimensions: 7.87"L 9.76"W 2.26"H

PLAM1600 1600 Watts 4 Channel Bridgeable Amplifier

- Four Channel Bridgeable Amplification
- Tri-way Configuration: 4/3/2 Channels
- 4 X 400Watts Total Output @ 4 Ohms
- 1600 Watts Total System Output @ 4 Ohms
- MOSFET Pulse Width Modulated Power Supply
- 2 Ohm Stereo Stable - RCA Low Level Inputs
- Built-In Variable Subwoofer Crossover
- Speaker Output Terminal Strip
- Signal/Noise Ratio 90dB - THD <0.04%
- Frequency Response: 15Hz-30kHz

- Overload, Thermal & Short Circuit Protection
- Power On LED Indicator - Variable Gain Control
- LED Diagnostic Condition Indicator
- Automotive Type Fuse Protection
- Dimensions: 11.02"L 9.76"W 2.26"H

PLAM2300 2300 Watts 2 Channel Bridgeable Amplifier

- Two Channel Bridgeable Amplification
- Tri-way Configuration: 1/2 Channels
- 2 X 1150 Watts Total Output @ 4 Ohms
- 2300 Watts Total System Output @ 4 Ohms
- MOSFET Pulse Width Modulated Power Supply
- Built-In Variable Subwoofer Crossover
- 2 Ohm Stereo Stable - RCA Low Level Inputs
- Speaker Output Terminal Strip
- Signal/Noise Ratio 90dB - THD Less Than 0.04%
- Frequency Response: 15Hz-30kHz

- Overload, Thermal & Short Circuit Protection
- Power On LED Indicator - Variable Gain Control
- LED Diagnostic Condition Indicator
- Automotive Type Fuse Protection
- Dimensions: 9.84"L 9.76"W 2.26"H

PLAM3000 3000 Watts 4 Channel Bridgeable Amplifier

- Four Channel Bridgeable Amplification
- Tri-way Configuration: 4/3/2 Channels
- 4 X 750 Watts Total Output @ 4 Ohms
- 3000 Watts Total System Output @ 4 Ohms
- MOSFET Pulse Width Modulated Power Supply
- 2 Ohm Stereo Stable - RCA Low Level Inputs
- Built-In Variable Subwoofer Crossover
- Speaker Output Terminal Strip
- Signal/Noise Ratio 90dB - THD < 0.04%
- Frequency Response: 15Hz-30kHz

- Overload, Thermal & Short Circuit Protection
- Power On LED Indicator - Variable Gain Control
- LED Diagnostic Condition Indicator
- Automotive Type Fuse Protection
- Dimensions: 14.17"L 9.76"W 2.26"H

PLAM2001D Class D Monoblock Power Amplifier

- Class D Monoblock Power Amplifier
- RMS Power @ 4 Ohms: 1x500 W
- RMS Power @ 2 Ohms: 1x800 W
- RMS Power @ 1.3 Ohms: 1x1500 W
- Maximum Power Output 2000W Mono
- Mono Block Sub woofer Amplifier
- Frequency Response 15 Hz-150 Hz (±3dB)
- Output Power @ 14.4v DC, 50Hz
- MOSFET Power Supply - 1 Ohm Stable
- PWM (Pulse-Width-Modulation) System

- Silver RCA Inputs - Glass Epoxy PCB
- Custom Terminal Block for Speaker Connection
- Thermal / Overload / Short Circuit Protection
- Variable Subsonic Filter (15Hz - 55Hz 24dB)
- Remote Bass Boost

PLAM3601D Class D Monoblock Power Amplifier

- Class D Monoblock Power Amplifier
- RMS Power @ 4 Ohms: 1x1000 W
- RMS Power @ 2 Ohms: 1x1500 W
- RMS Power @ 1.3 Ohms: 1x2000 W
- Maximum Power Output 3600W Mono
- Mono Block Sub woofer Amplifier
- Frequency Response 15 Hz-150 Hz (±3dB)
- Output Power @ 14.4v DC, 50Hz

- MOSFET Power Supply
- PWM (Pulse-Width-Modulation) System
- Glass Epoxy PCB - Silver RCA Inputs
- Custom Terminal Block for Speaker Connection



PLTA580



PLBA330FRD

PLBA330FRD

BLADE 4400 Watts 3 Channel Compact Class-D Full Range Hybrid Amplifier

- 2 x 300 Watt + 1 x 800 Watts RMS @ 4 Ohms
- 2 x 600 Watt + 1 x 1600 Watts MAX @ 4 Ohms
- 2 x 450 Watt + 1 x 1200 Watts RMS @ 2 Ohms
- 2 x 1200 Watt + 1 x 2000 Watts MAX @ 2 Ohms
- High Glossy Black Brushed accents Heat Sink
- New Compact Design Based Class-D
- Double Sided SMT Circuit Board
- 2 Ohms Stereo Stable
- LPF Variable Crossover : 30Hz-200Hz 24dB/Oct
- HPF Variable Crossover : 50Hz-180Hz 12dB/Oct
- Variable Bass Boost Frequency : 40Hz-100Hz dB(Variable)
- Variable Bass Boost:0-18dB - Soft Turn On/Off
- Phase Adjustable : 0° - 180°
- Dash Mount Remote Subwoofer Control
- Nickel Plated Low Level RCA Input
- Power Protection LED Indicators
- Advanced Protection Circuitry
- Frequency Response : 10 – 40K Hz
- S/N Ratio > 95 dB - Fuse : 25A x 2
- Dimension : 8.78"(L) x 7.40"(W) x 1.99"(H)

PLBA430FRD

BLADE 3600 Watts 4 Channel Compact Class-D Full Range Amplifier

- 4 x 300 Watts RMS @ 4 Ohms
- 4 x 600 Watts MAX @ 4 Ohms
- 4 x 450 Watts RMS @ 2 Ohms
- 4 x 900 Watts MAX @ 2 Ohms
- High Glossy Black Brushed accents Heat Sink
- New Compact Design Based on Class-D Tech
- Double Sided SMT Circuit Board
- 2 Ohms Stereo Stable - Soft Turn On/Off
- LPF Variable Crossover : 30Hz-200Hz 24dB/Oct
- HPF Variable Crossover : 50Hz-180Hz 12dB/Oct
- Variable Bass Boost : 0-18 dB at40Hz
- Phase Adjustable : 0° - 180°
- Nickel Plated Low Level RCA Input
- Power Protection LED Indicators
- Advanced Protection Circuitry
- Frequency Response : 10 – 40K Hz
- S/N Ratio > 95 dB - Fuse : 25A x 2
- Dimension : 7.20"(L) x 7.40"(W) x 1.99"(H)

PLBA530FRD

BLADE 6800 Watts 5 Channel Compact Class-D Full Range Hybrid

- 4 x 300 Watt + 1 x 800 Watts RMS @ 4 Ohms
- 4 x 600 Watt + 1 x 1600 Watts MAX @ 4 Ohms
- 4 x 450 Watt + 1 x 1200 Watts RMS @ 2 Ohms
- 4 x 1200 Watt + 1 x 2000 Watts MAX @ 2 Ohms
- High Glossy Black Brushed accents Heat Sink
- New Compact Design Based on Class-D Tech
- Double Sided SMT Circuit Board
- 2 Ohms Stereo Stable - Soft Turn On/Off
- LPF Variable Crossover : 30Hz-200Hz 24dB/Oct
- HPF Variable Crossover : 50Hz-180Hz 12dB/Oct
- Variable Bass Boost Frequency : 40Hz-100Hz(Variable)
- Variable Bass Boost : 0-18 dB
- Phase Adjustable : 0° - 180°
- Dash Mount Remote Subwoofer Control
- Nickel Plated Low Level RCA Input
- Power Protection LED Indicators
- Advanced Protection Circuitry
- Frequency Response : 10 – 40K Hz
- S/N Ratio > 95 dB - Fuse : 25A x 3
- Dimension : 12.72"(L) x 7.40"(W) x 1.99"(H)

PLTA180

2 Channel 800 Watt 24 Volt Truck/Bus/RV Bridgeable Mosfet Amplifier

- 2 x 200W RMS at 4 Ohms
- 2 x 400W MAX at 4 Ohms
- 1 x 800W MAX at 4 Ohms Bridged
- 2 ohm Stereo Stable
- Line Out for Left & Right Channel
- Tri-mode operation, Bridgeable
- Nickel-plated RCA connectors & Screw terminals
- Thermal, Over load & Speaker short protection
- Air Induction FAN Cooled
- Power & Protection LED Indicators
- Soft Turn-on/Turn-off - Fuse Rating: 15Ax4
- Channels/Class: 2ch. Class A/B
- Input Sensitivity: 100mV-4V
- THD 4ohm Power 0.04%
- Frequency Response: 10Hz-30KHz
- S/N Ratio (4 ohm): 90dB
- Stereo Separation: 65dB
- Sub Sonic Filter : 20Hz fixed
- Bass Boost: 0-18dB (60Hz fixed)
- DC 24-28 Voltage Input
- Dimensions : 11.42"(W) x 3.15"(H) x 15.74"(L)

PLTA580

2 Channel 2000 Watt 24Volt Truck/Bus/RV Bridgeable Mosfet Amplifier

- 2 x 500W RMS at 4 Ohms
- 2 x 1000W MAX at 4 Ohms
- 1 x 2000W MAX at 4 Ohms Bridged
- 2 ohm Stereo Stable
- Line Out for Left & Right Channel
- Tri-mode operation, Bridgeable
- Nickel-plated RCA connectors & terminals
- Thermal, Over load & Speaker short protection
- Air Induction FAN Cooled
- Power & Protection LED Indicators
- Soft Turn-on/Turn-off
- Channels/Class: 2ch. Class A/B
- Input Sensitivity: 100mV-4V
- THD 4ohm Power 0.04%
- Frequency Response: 10Hz-30KHz
- S/N Ratio (4 ohm): 90dB
- Stereo Separation: 65dB
- Sub Sonic Filter : 20Hz fixed
- Bass Boost: 0-18dB (60Hz fixed)
- DC 24-28 Voltage Input
- Dimensions : 11.42"(W) x 3.15"(H) x 21.65"(L)

2013 Complete Product Catalog

P1A2988 2 Ch 6000 Watts Bridgeable Mosfet Amplifier

- Maximum Power Output 2 x 3000W
- Bridgeable RMS Power @ 4 Ohms: 1 x 6000W
- 2 Channel Bridgeable MOSFET Amplifier
- Frequency Response 20 Hz-50kHz (± 3 dB)
- Output Power @ 14.4v DC, 50Hz
- 2 Ohm Stable
- MOSFET Power Supply
- PWM (Pulse-Width-Modulation) System
- Glass Epoxy PCB
- Silver RCA Inputs
- Custom Terminal Block for Speaker Connection
- Thermal / Overload / Short Circuit Protection
- Input Impedance: 47K Ohms
- Soft Turn On/ Off
- Advanced Protection Circuitry
- S/N Ratio: >90dB
- Dimensions: 9.76" W x 2.99" H x 15.35" L



P1A4988 4 Channel 6000 Watts Bridgeable Mosfet Amplifier

- Maximum Power Output 4 x 1500W
- Bridgeable RMS Power @ 4 Ohms: 2 x 3000 W
- 4 Channel Bridgeable MOSFET Amplifier
- Frequency Response 20 Hz-50kHz (± 3 dB)
- Output Power @ 14.4v DC, 50Hz
- 2 Ohm Stable
- MOSFET Power Supply
- PWM (Pulse-Width-Modulation) System
- Glass Epoxy PCB
- Silver RCA Inputs
- Custom Terminal Block for Speaker Connection
- Thermal / Overload / Short Circuit Protection
- Input Impedance: 47K Ohms
- Soft Turn On/ Off
- Advanced Protection Circuitry
- S/N Ratio: >90dB
- Dimensions: 9.76" W x 2.99" H x 16.93" L



Hi-Fi Stereo Amplifiers with AC Adapter Included:

PFA100



• 30 Watt

PFA200



• 60 Watt

PFA300



• 90 Watt

PFA400U



- 100 Watt
- LCD Display
- USB/SD Compatibility

All Models Include:

- 12V AC/DC Adapter
- Class-T Circuit Design
- Microphone Input Jack
- Speaker Impedance: 2-8 Ω
- 3.5mm iPod/MP3 Input Jack
- Signal to Noise Ratio: >80dB
- Input Power: DC 9 ~ 14.4V 2A
- Total harmonic distortion: <0.4%
- Frequency response: 20Hz-20kHz
- Short Cut, Overload & Overheat Protection



• Each model comes with 12V AC/DC Adapter 2A

P1E530PAI 1/2 Din 5 Band Parametric Equalizer with Built-in Crossover & Subwoofer Control

- 5-Band Graphic Equalizer
- 6-Channel 8 Volt RCA Outputs (Front/Rear/Subwoofer)
- DC 12 Volt
- 2-Channel RCA Source & Front AUX Input
- Output Volume Control
- Input Gain Adjustments
- Frequency Gain Control
- Five Frequency Band with +/- 18dB Boost/Cut (45Hz, 150Hz, 400Hz, 2.5KHz, 15KHz)
- Built in 6 channel 8 Volt Line Driver
- Selectable Source & AUX Input Selector
- Full System Fader Adjustment
- Illuminated Rotary Controls
- Half Din Dash Mount
- Mounting Hardware Included
- Dimensions: 7"W x 4.52"D x 1.10"H



NEW!
for 2013

P1E780P 1/2 Din 7 Band Parametric Equalizer with Built-in Crossover & Subwoofer

- DC 12 Volt
- Half Din Dash Mount
- Output Volume Control
- Input Gain Adjustments
- Frequency Gain Control
- 7-Band Graphic Equalizer
- Fully Adjustable crossover
- Illuminated Rotary Controls
- Full System Fader Adjustment
- Mounting Hardware Included
- Built in 6 channel 7 Volt Line Driver
- 2-Channel RCA Source & AUX Input
- Selectable Source & AUX Input Selector
- 6-Channel 7 Volt RCA Outputs (Front/Rear/Subwoofer)
- Dimensions: 7"W x 4.1"D x 1.10"H



NEW!
for 2013



PL42BL



PL63BL



PL6984BL

For More Products
and Detailed Information
Visit PyleAudio.com

PL42BL 4" 180 Watt Two-Way Speakers

- One Pair 4" Two-way Speaker Systems
- Power Handling: 90 Watts Rms / 180 Watts Max
- Non-fatiguing Butyl Rubber Surround
- 3/4" High Temperature ASV Voice Coil
- Standard 4" Size Fits OEM Locations
- Blue Poly Injection Cone
- 20 oz Magnet Structure
- 1/2" Neodymium Film Dome Tweeter
- Impedance: 4 Ohm
- Sensitivity: 88 dB
- Frequency Response: 110Hz - 20Khz
- Mounting Depth: 1.95"

PL463BL 4" x 6" 240 Watt Three-Way Speakers

- One Pair 4" x 6" Three-Way Triaxial Speaker Systems
- Power Handling: 120 Watts Rms / 240 Watts Max
- Non-fatiguing Butyl Rubber Surround
- 1" High Temperature ASV Voice Coil
- Standard 4" X 6" Size Fits Oem Locations
- Blue Poly Injection Cone
- 20 Oz Magnet Structure
- 1" Neodymium Film Dome Midrange
- 3/4" Piezo Tweeter
- Impedance: 4 Ohm
- Sensitivity: 89 dB
- Frequency Response: 100Hz - 20Khz
- Includes Grills, Wires And Mounting Hardware
- Mounting Depth: 1.9"

PL53BL 5.25" 200 Watt Three-Way Speakers

- One Pair 5.25" Three-Way Triaxial Speaker Systems
- Power Handling: 100 Watts Rms / 200 Watts Max
- Non-fatiguing Butyl Rubber Surround
- 1" High Temperature ASV Voice Coil
- Standard 5.25" Size Fits Oem Locations
- Blue Poly Injection Cone
- 20 oz Magnet Structure
- 1" Neodymium Film Dome Midrange
- 3/4" Piezo Tweeter
- Impedance: 4 Ohm
- Sensitivity: 89 dB
- Frequency Response: 100Hz - 20Khz
- Includes Grills, Wires And Mounting Hardware
- Mounting Depth: 1.9"

PL573BL 5" x 7" & 6" x 8" 300 Watt Three-Way Speakers

- One Pair 5" x 7" 6" x 8" Three-Way Triaxial Speaker Systems
- Power Handling: 150 Watts Rms / 300 Watts Max
- Non-fatiguing Butyl Rubber Surround
- 1" High Temperature ASV Voice Coil
- Standard 5" x 7"/6" X 8" Size Fits OEM Locations
- Blue Poly Injection Cone
- 20 oz Magnet Structure
- 1" Neodymium Film Dome Midrange
- 3/4" Piezo Tweeter
- Impedance: 4 Ohm
- Sensitivity: 90 dB
- Frequency Response: 80Hz - 20Khz
- Includes Grills, Wires And Mounting Hardware
- Mounting Depth: 2.25"

PL63BL 6.5" 360 Watt Three-Way Speakers

- One Pair 6.5" Three-Way Triaxial Speakers
- Power Handling: 180 Watts Rms / 360 Watts Max
- Non-fatiguing Butyl Rubber Surround
- 1" High Temperature ASV Voice Coil
- Standard 6.5" Size Fits OEM Locations
- Blue Poly Injection Cone
- 20 oz Magnet Structure
- 1" Neodymium Film Dome Midrange
- 3/4" Piezo Tweeter
- Impedance: 4 Ohm
- Sensitivity: 89 Db
- Frequency Response: 90Hz - 20Khz
- Includes Grills, Wires And Mounting Hardware
- Mounting Depth: 1.9"

PL683BL 6" x 8" 360 Watt Three-Way Speakers

- One Pair 6" x 8" Three-Way Triaxial Speakers
- Power Handling: 180 Watt Rms / 360 Watt Max
- Non-fatiguing Butyl Rubber Surround
- 1" High Temperature ASV Voice Coil
- Standard 6" x 8" Size Fits OEM Locations
- Blue Poly Injection Cone
- 40 oz Magnet Structure
- 1" Neodymium Film Dome Midrange
- 3/4" Piezo Tweeter
- Impedance: 4 Ohm
- Sensitivity: 91 Db
- Frequency Response: 70Hz - 20Khz
- Includes Grills, Wires And Mounting Hardware
- Mounting Depth: 2.35"

PL6984BL 6" x 9" 400 Watt Four-Way Speakers

- One Pair 6" X 9" Four-Way Quadriaxial Speakers
- Power Handling: 200 Watts Rms / 400 Watts Max
- Non-fatiguing Butyl Rubber Surround
- 1.25" High Temperature ASV Voice Coil
- Standard 6" X 9" Size Fits OEM Locations
- Blue Poly Injection Cone - 50 Oz Magnet Structure
- 1-1/2" Film Dome Midrange
- 1" Film Dome Tweeter - 3/4" Piezo Tweeter
- Impedance: 4 Ohm - Sensitivity: 92 Db
- Frequency Response: 50Hz - 20Khz
- Includes Grills, Wires And Mounting Hardware
- Mounting Depth: 3.65"

2013 Complete Product Catalog



PIC32



PIC413



PIC54

PIC32 3.5" 120 Watt Two-Way Speakers

- Standard 3.5" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 0.5" Neodymium Dome Tweeter
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Coated Steel Basket
- 20 oz. Magnet Structure - Impedance: 4 Ohms

- Rubber Magnet Cover
- Power Handling: 60 Watts RMS /120 Watts Peak
- Frequency Response: 100-20KHz
- Includes Wires and Installation Hardware

PIC42 4" 140 Watt Two-Way Speakers

- Standard 4" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 0.5" Neodymium Dome Tweeter
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Coated Steel Basket
- 20 oz. Magnet Structure - Rubber Magnet Cover

- Power Handling: 70 Watts RMS /140 Watts Peak
- Frequency Response: 90-20KHz
- Impedance: 4 Ohms
- Includes Grills, Wires Installation Hardware

PIC413 4" x 10" 300 Watt Three-Way Speakers

- Standard 4"x10" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 2" Polymer Cone Midrange
- 0.5" Neodymium Dome Tweeter
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Coated Steel Basket - 45 oz. Magnet

- Rubber Magnet Cover - Impedance: 4 Ohms
- Power Handling: 150 Watts RMS /300 Watts Peak
- Frequency Response: 60-22KHz
- Includes Grills, Wires and Installation Hardware

PIC462 4" x 6" 180 Watt Two-Way Speakers

- Standard 4"x6" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 0.5" Neodymium Dome Tweeter
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Coated Steel Basket - Impedance: 4 Ohms
- 30 oz. Magnet Structure - Rubber Magnet Cover

- Power Handling: 90 Watts RMS /180 Watts Peak
- Frequency Response: 70-20KHz
- Includes Grills, Wires and Installation Hardware
- Mounting Depth: 2"

PIC463 4" x 6" 180 Watt Three-Way Speakers

- Standard 4"x6" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 0.5" Neodymium Dome Midrange
- Super Film Tweeter
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Coated Steel Basket - Impedance: 4 Ohms

- 30 oz. Magnet Structure - Rubber Magnet Cover
- Power Handling: 90 Watts RMS /180 Watts Peak
- Frequency Response: 70-20KHz
- Includes Grills, Wires and Installation Hardware

PIC52 5.25" 140 Watt Two-Way Speakers

- Standard 5.25" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 0.5" Neodymium Dome Tweeter
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Coated Steel Basket - Impedance: 4 Ohms
- 30 oz. Magnet Structure - Rubber Magnet Cover

- Power Handling: 70 Watts RMS /140 Watts Peak
- Frequency Response: 80-20KHz
- Includes Grills, Wires and Installation Hardware
- Mounting Depth: 2"

PIC53 5.25" 140 Watt Three-Way Speakers

- Standard 5.25" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 0.5" Neodymium Dome Midrange
- Super Film Tweeter
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Coated Steel Basket
- 30 oz. Magnet Structure
- Rubber Magnet Cover

- Power Handling: 70 Watts RMS /140 Watts Peak
- Frequency Response: 80-20KHz
- Impedance: 4 Ohms
- Includes Custom Grills, Wires and Installation Hardware

PIC54 5" 200 Watt Mid Bass Woofer

- Yellow CD P.P. Cone
- Specially Treated Rubber Surround
- Edge Suspension
- 1.0" High Temperature Aluminum Voice Coil
- Magnet Weight: 30 Oz
- Impedance: 4 OHM

- 200 Watts Peak Power
- Mounting Depth: 2.20"
- Cut-out Size: Φ113 mm



PLG64



PLG69.3



PLG64

PLG57.2 5" x 7" / 6" x 8" 240 Watt Two-Way Speakers

- Standard 5"x7"/6"x8" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 0.5" Neodymium Dome Tweeter
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Steel Basket - Impedance: 4 Ohms
- 30 oz. Magnet Structure - Rubber Magnet Cover
- Power Handling: 120 Watt RMS /240 Watt Peak
- Frequency Response: 75-22KHz
- Includes Grills, Wires and Installation Hardware
- Mounting Depth: 2.10"

PLG57.3 5" x 7" / 6" x 8" 240 Watt Three-Way Speakers

- Standard 5"x7"/6"x8" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 0.5" Neodymium Dome Midrange
- Super Film Tweeter - Mounting Depth: 2.10"
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Steel Basket - Impedance: 4 Ohms
- 30 oz. Magnet Structure - Rubber Magnet Cover
- Power Handling: 120 Watt RMS /240 Watt Peak
- Frequency Response: 75-22KHz
- Includes Grills, Wires and Installation Hardware

PLG62 6.5" 240 Watt Two-Way Speakers

- Standard 6.5" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 0.5" Neodymium Dome Tweeter
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Steel Basket - Impedance: 4 Ohms
- 30 oz. Magnet Structure - Rubber Magnet Cover
- Power Handling: 120 Watt RMS /240 Watt Peak
- Frequency Response: 65-20KHz
- Includes Grills, Wires and Installation Hardware
- Mounting Depth: 2.25"

PLG63 6.5" 280 Watt Three-Way Speakers

- Standard 6.5" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 0.5" Neodymium Dome Midrange
- Super Film Tweeter
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Steel Basket - Impedance: 4 Ohms
- 40 oz. Magnet Structure - Rubber Magnet Cover
- Power Handling: 140 Watt RMS /280 Watt Peak
- Frequency Response: 60-20KHz
- Includes Grills, Wires and Installation Hardware

PLG64 6.5" 300 Watt Four-Way Speakers

- Standard 6.5" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 1.75" Polymer Cone Midrange
- 0.5" Neodymium Dome Tweeter
- Super Film Tweeter - Mounting Depth: 2.25"
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Steel Basket - Impedance: 4 Ohms
- 40 oz. Magnet Structure - Rubber Magnet Cover
- Power Handling: 150 Watt RMS /300 Watt Peak
- Frequency Response: 60-20KHz

PLG64 6.5" 300 Watt Mid Bass Woofer

- Yellow CD P.P. Cone
- Specially Treated Rubber
- Edge Suspension
- 1.0" High Temperature Voice Coil
- Aluminum Voice Coil - Magnet Weight: 30 Oz
- Rubber Magnet Boot Cover
- 300 Watts Peak Power - Impedance: 4 OHM
- Mounting Depth: 2.84" - Cut-out Size: Φ140 mm

PLG68.3 6" x 8" 280 Watt Four-Way Speakers

- Standard 6"x8" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 1.75" Polymer Cone Midrange
- 0.5" Neodymium Dome Tweeter
- Super Film Tweeter
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Steel Basket - Rubber Magnet Cover
- 40 oz. Magnet Structure - Impedance: 4 Ohms
- Power Handling: 140 Watt RMS /280 Watt Peak
- Frequency Response: 65-20KHz
- Includes Grills, Wires and Installation Hardware
- Mounting Depth: 2.45"

PLG69.3 6" x 9" 360 Watt Three-Way Speakers

- Standard 6"x9" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 2" Polymer Cone Midrange
- 0.5" Neodymium Dome Tweeter
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Steel Basket - Impedance: 4 Ohms
- 100 oz. Magnet Structure - Rubber Magnet Cover
- Power Handling: 180 Watt RMS /360 Watt Peak
- Frequency Response: 45-22KHz
- Includes Grills, Wires and Installation Hardware
- Mounting Depth: 3.5"

2013 Complete Product Catalog



PLG8.3



PLG6C



PLG71.4

PLG69.4 6" x 9" 400 Watt Four-Way Speakers

- Standard 6"x9" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 2" Polymer Cone Midrange
- 0.5" Neodymium Dome Tweeter
- Super Film Tweeter - Impedance: 4 Ohms
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Steel Basket - Mounting Depth: 3.5"
- 100 oz Magnet - Rubber Magnet Cover
- Power Handling: 200 Watt RMS /400 Watt Peak
- Frequency Response: 45-22KHz

PLG69.5 6" x 9" 450 Watt Five-Way Speakers

- Standard 6"x9" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 2" Polymer Cone Midrange
- 0.5" Neodymium Dome Tweeter
- 2 x Super Film Tweeter
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Steel Basket - Impedance: 4 Ohms
- 120 oz. Magnet Structure - Rubber Magnet Cover
- Power Handling: 225 Watt RMS /450 Watt Peak
- Frequency Response: 45-22KHz
- Includes Grills, Wires and Installation Hardware
- Mounting Depth: 3.5"

PLG69.8 6" x 9" 500 Watt Eight-Way Speakers

- Standard 6"x9" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 2" Polymer Cone Midrange
- 0.5" Neodymium Dome Tweeter
- 5 x Super Film Tweeter
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Steel Basket - Impedance: 4 Ohms
- 120 oz. Magnet - Rubber Magnet Cover
- Power Handling: 250 Watt RMS /500 Watt Peak
- Frequency Response: 45-22KHz
- Includes Grills, Wires and Installation Hardware
- Mounting Depth: 3.55"

PLG6C 6.5" 400 Watt 2-Way Custom Component System

- This Custom Kit Contains
- One Pair 6.5" Mid Bass Speaker
- Standard 6.5" Size Fits OEM Locations
- Yellow Color Poly Injection Cone
- Non-Fatiguing Butyl Rubber Surround
- High Temperature Aluminum Voice Coil
- Special Electroplated Steel Basket
- 40 Oz. Magnet Structure
- Power Handling: 200 Watt RMS / 400 Watt MAX
- Impedance: 4 Ohm - Neodymium Magnet
- Frequency response: 50Hz-5KHz
- Mounting Depth: 2.65"
- One Pair 0.5" Tweeter: 0.5" Silk Dome Tweeter
- 3 Mounting Options: Flush, Surface or Angle
- 50 Watts RMS / 100 Watts peak
- Frequency response: 1.3-22KHz
- Impedance: 4 Ohm
- One Pair Passive Crossover Network:
- Two - Way Passive Crossover
- 12 dB Octave Slope

PLG71.4 7" x 10" 450 Watt Four-Way Speakers

- Standard 7"x10" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 2" Polymer Cone Midrange
- 0.5" Neodymium Dome Tweeter
- Super Film Tweeter
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Coated Steel Basket
- 120 oz. Magnet Structure
- Rubber Magnet Cover
- Power Handling: 225 Watts RMS /450 Watts Peak
- Frequency Response: 40-22KHz
- Impedance: 4 Ohms
- Includes Custom Grills, Wires and Installation

PLG8.3 8" 400 Watt Three-Way Speakers

- Standard 8" Size Fits OEM Locations
- Yellow Color Poly Injected Cone
- Non-Fatiguing Butyl Rubber Surround
- 2.5" Polymer Cone Midrange
- 0.5" Neodymium Dome Tweeter
- High Temperature Aluminum Voice Coil
- Strong Capacitor for Excellent Performance
- Yellow Coated Steel Basket - Rubber Magnet
- 120 oz. Magnet Structure - Impedance: 4 Ohms
- Power Handling: 200 Watt RMS /400 Watt Peak
- Frequency Response: 37-22KHz
- Includes Grills, Wires and Installation Hardware
- Mounting Depth: 3.25"



PIR442



PIR452



PIR462

PIR442 4" 140 Watt Two-Way Speakers (Pair)

- 4" Electroplated Polypropylene Cone Rubber
- 1" High Temp Ferro Fluid Enhanced Voice Coil
- 1" Mylar Dome Tweeter
- 70 Watts RMS/140 Watts Peak Power
- 4 Ohm Impedance
- Freq. Response: 66Hz - 20kHz
- Rubber Magnet Boot Cover
- Mounting Depth: 2"
- Includes Grills, Wires and Installation Hardware

PIR462 4" x 6" 180 Watt Two-Way Speakers (Pair)

- Pair 4" x 6" Two-Way Speaker System
- Electroplated Red Polypropylene Cone Butyl Rubber Surround
- 1" High Temp Ferro Fluid Enhanced Voice Coil
- 1" Mylar Dome Tweeter - 4 Ohm Impedance
- 90 Watts RMS/180 Watts Peak Power
- Freq. Response: 66Hz - 20kHz
- Rubber Magnet Boot - Mounting Depth: 1.85"
- Includes Grills, Wires and Installation Hardware

PIR452 5.25" 160 Watt Two-Way Speakers (Pair)

- 5.25" Electroplated Red Polypropylene Cone Rubber Edge
- 1" High Temp Ferro Fluid Enhanced Voice Coil
- 1" Mylar Dome Tweeter - 4 Ohm Impedance
- 80 Watts RMS/160 Watts Peak Power
- Freq. Response: 55Hz - 20kHz
- Rubber Magnet Boot Cover
- Includes Grills, Wires and Installation Hardware
- Mounting Depth: 2"

PIR452 5"x 7" & 6" X 8" 200 Watt Two-Way Speakers

- Pair 5" x 7" Two-Way Speaker System
- Electroplated Red Polypropylene Cone Rubber Edge - Mounting Depth: 2.25"
- 1" High Temp Ferro Fluid Enhanced Voice Coil
- 1" Mylar Dome Tweeter - 4 Ohm Impedance
- 100 Watts RMS/200 Watts Peak Power
- Freq. Response: 50Hz - 20kHz
- Rubber Magnet Boot Cover
- Includes Grills, Wires Installation Hardware

PIR462 6.5" 200 Watt Two-Way Speakers

NEW!
for 2013

- Pair 6.5" Two-Way Speaker System
- Electroplated Red Polypropylene Cone
- 1" High Temp Ferro Fluid Enhanced Voice Coil
- 1" Mylar Dome Tweeter - 4 Ohm Impedance
- 100 Watts RMS/200 Watts Peak Power
- Freq. Response: 66Hz - 20kHz
- Rubber Magnet Boot - Mounting Depth: 2"

PIR463 6" x 9" 400 Watt Three-Way Speakers

- Pair 6" x 9" Three-Way Speaker System
- Electroplated Red Polypropylene Cone
- Butyl Rubber Surround
- 1" High Temp Ferro Fluid Enhanced Voice Coil
- 2" Pole Mounted Aluminum Midrange
- 1" Mylar Dome Tweeter
- 200 Watts RMS/400 Watts Peak Power
- 4 Ohm Impedance
- Freq. Response: 45Hz - 22kHz
- Rubber Magnet Boot Cover
- Includes Grills, Wires Installation Hardware
- Mounting Depth: 3.04"

PIG442 4" 140 Watt 2-Way Speaker System

PIG452 5.25" 160 Watt 2-Way Speaker System

PIG462 6.5" 240 Watt 2-Way Speaker System

PIG463 6" x 9" 360 Watt 3-Way Speaker System

More Products
and Information
@
PyleAudio.com



2013 Complete Product Catalog



PLX42



PLX4102

For More Products
and Detailed Information
Visit PyleAudio.com



PLX62

PLX32 3.5" 100 Watt Two-Way Speakers

- 3.5" Polypropylene Woofer Cone
- 0.75" Hi-Temp Ferro Fluid Enhanced Voice Coil
- 1" Mylar Dome Tweeter
- 50 Watts RMS/100 Watts Max Power
- Frequency Response: 66 - 20k hz
- 4 Ohms Impedance
- Rubber Boot Magnet Cover
- Includes Wires and Mounting Hardware
- Mounting Depth: 1.5"

PLX4102 4" x 10" 300 Watt Two-Way Speakers

- 4" x 10" Polypropylene Woofer Cone
- 1" Hi-Temp Ferro Fluid Enhanced Voice Coil
- 1" Mylar Dome Tweeter
- 150 Watts RMS/300 Watts Max Power
- Frequency Response: 60 - 20k hz
- 4 Ohms Impedance
- Rubber Boot Magnet Cover
- Includes Grills, Wires and Mounting Hardware
- Mounting Depth: 2.5"

PLX42 4" 120 Watt Two-Way Speakers

- 4" Polypropylene Woofer Cone
- 1" Hi-Temp Ferro Fluid Enhanced Voice Coil
- 1" Mylar Dome Tweeter
- 60 Watts RMS/120 Watts Max Power
- Frequency Response: 66 - 20k hz
- 4 Ohms Impedance
- Rubber Boot Magnet Cover
- Includes Grills, Wires and Mounting Hardware
- Mounting Depth: 2"

PLX462 4" x 6" 160 Watt Two-Way Speakers

- 4" x 6" Polypropylene Woofer Cone
- 1" Hi-Temp Ferro Fluid Enhanced Voice Coil
- 1" Mylar Dome Tweeter
- 80 Watts RMS/160 Watts Max Power
- Frequency Response: 66 - 20k hz
- 4 Ohms Impedance
- Rubber Boot Magnet Cover
- Includes Grills, Wires and Mounting Hardware
- Mounting Depth: 1.9"

PLX52 5.25" 120 Watt Two-Way Speakers

- 5.25" Polypropylene Woofer Cone
- 1" Hi-Temp Ferro Fluid Enhanced Voice Coil
- 1" Mylar Dome Tweeter
- 60 Watts RMS/120 Watts Max Power
- Frequency Response: 55 - 20k hz
- 4 Ohms Impedance
- Rubber Boot Magnet Cover
- Includes Grills, Wires and Mounting Hardware
- Mounting Depth: 2"

PLX572 5" x 7"/6" x 8" 180 Watt Two-Way Speakers

- 5" x 7" Polypropylene Woofer Cone
- 1" Hi-Temp Ferro Fluid Enhanced Voice Coil
- 1" Mylar Dome Tweeter
- 90 Watts RMS/180 Watts Max Power
- Frequency Response: 50 - 20k hz
- 4 Ohms Impedance
- Rubber Boot Magnet Cover
- Includes Grills, Wires and Mounting Hardware
- Mounting Depth: 2.25"

PLX62 6.5" 160 Watt Two-Way Speakers

- 6.5" Polypropylene Woofer Cone
- 1" Hi-Temp Ferro Fluid Enhanced Voice Coil
- 1" Mylar Dome Tweeter
- 80 Watts RMS/160 Watts Max Power
- Frequency Response: 66 - 20k hz
- 4 Ohms Impedance
- Rubber Boot Magnet Cover
- Includes Grills, Wires and Mounting Hardware
- Mounting Depth: 2"

PLX63 6.5" 180 Watt Three-Way Speakers

- 6.5" Polypropylene Woofer Cone
- 1" Hi-Temp Ferro Fluid Enhanced Voice Coil
- 2" Pole Mounted Aluminum Midrange
- 1" Mylar Dome Tweeter
- 90 Watts RMS/180 Watts Max Power
- Frequency Response: 50 - 22k hz
- 4 Ohms Impedance
- Rubber Boot Magnet Cover
- Includes Grills, Wires and Mounting Hardware

PL1090BL

PL1290BL

PL1590BL

PL1890BL



blue wave
SERIES

More Products
and Information
@
PyleAudio.com

PL1090BL 10" 1000 Watt DVC Subwoofer

- Blue Injection Molded Cone
- Non-Fatiguing Big Rubber Suspension
- Blue Chrome-Plated Steel Basket
- Bumped Vented Extended Pole Piece
- Silver Plated Terminal
- Flat Progressive Spider
- New Wave-Like Rubber Gasket
- Rubber Magnet Boot - SPL: 83.5dB
- 2" High Temperature Dual Kapton Voice Coil
- Magnet Weight: 2x70 oz
- 1000 Watt Max Power Handling
- Impedance: 4 Ohm (Per Coil)
- Fs:26.9, Qms:5.23, Qes:0.89, Qts:0.76, Vas (Cu ft) 2.394
- Diameter: 10.16" - Mounting Depth: 6.20"

PL1290BL 12" 1200 Watt DVC Subwoofer

- Blue Injection Molded Cone
- Non-Fatiguing Big Rubber Suspension
- Blue Chrome-Plated Steel Basket
- Bumped Vented Extended Pole Piece
- Silver Plated Terminal
- Flat Progressive Spider
- New Wave-Like Rubber Gasket
- Rubber Magnet Boot - SPL: 85dB
- 2.5" High Temperature Dual Kapton Voice Coil
- Magnet Weight: 2x90 oz
- 1200 Watt Max Power Handling
- Impedance: 4 Ohm (Per Coil)
- Fs:23.2, Qms:4.92, Qes:0.84, Qts:0.72, Vas (Cu ft) 4.908
- Diameter: 12.20" - Mounting Depth: 6.52"

PL1590BL 15" 1400 Watt DVC Subwoofer

- Blue Injection Molded Cone
- Non-Fatiguing Big Rubber Suspension
- Blue Chrome-Plated Steel Basket
- Bumped Vented Extended Pole Piece
- Silver Plated Terminal
- Flat Progressive Spider
- New Wave-Like Rubber Gasket
- Rubber Magnet Boot - SPL: 84dB
- 2.5" High Temperature Dual Kapton Voice Coil
- Magnet Weight: 2x90 oz
- 1400 Watt Max Power Handling
- Impedance: 4 Ohm (Per Coil)
- Fs:21.2, Qms:5.0, Qes:0.90, Qts:0.75, Vas (Cu ft) 5.204
- Diameter: 15.84" - Mounting Depth: 8.52"

PL1890BL 18" 1800 Watt DVC Subwoofer

- Blue Injection Molded Cone
- Non-Fatiguing Big Rubber Suspension
- Blue Chrome-Plated Steel Basket
- Bumped Vented Extended Pole Piece
- Silver Plated Terminal
- Flat Progressive Spider
- New Wave-Like Rubber Gasket
- Rubber Magnet Boot - SPL: 86dB
- 3" High Temperature Dual Kapton Voice Coil
- Magnet Weight: 2x100 oz
- 1800 Watt Max Power Handling
- Impedance: 4 Ohm (Per Coil)
- Fs:20, Qms:4.8, Qes:1.2, Qts:0.70, Vas (Cu ft) 6.025
- Diameter: 18.32" - Mounting Depth: 8.80"

PLDV6K 6.5" 240 Watt 2-Way Component System

- This Custom Kit Contains:
- One Pair 6.5" Mid Bass Speaker
- Standard 6.5" Size OEM Locations
- Poly Injection Cone
- Non-Fatiguing Butyl Rubber Surround
- 1" High Temperature ASV Voice Coil
- 25 Oz Magnet Structure
- Rubber Magnet Cover
- Power Handling: 120 Watts RMS /240 Watts Peak
- Frequency Response: 55-6KHz
- Impedance: 4 Ohms
- Mounting Depth: 2.85"
- One Pair 1" Tweeter:
- 1" Silk Dome Tweeter
- Neodymium Magnet
- 3 Mounting Options: Flush/ Swivel / Surface Angle Mount
- 50 Watts RMS / 100 Watts peak
- Frequency response: 1.4-24KHz
- Impedance: 4 Ohm
- One Pair Passive Crossover Network:
- Two - Way Passive Crossover
- 12 dB Octave Slope
- Accessories
- Includes Grills Wires Installation Hardware
- Wiring Kit
- Wiring Diagram Template



PLDV62 6.5" 240 Watt Two-Way Speaker

- One Pair 6.5" Two-Way Coaxial Speaker Systems
- Power Handling: 120 Watts RMS 240 Watts MAX
- Non-Fatiguing Butyl Rubber Surround
- 1" High Temperature ASV Voice Coil
- Standard 6.5" Size OEM Locations
- Poly Injection Cone
- 20 Oz Magnet Structure
- Rubber Magnet Cover
- 1/2" Neodymium Dome Tweeter
- Impedance: 4 Ohm
- Sensitivity: 90 dB
- Frequency Response: 80Hz - 20KHz
- Includes Grills, Wires and Mounting Hardware
- Mounting Depth: 2.25"



2013 Complete Product Catalog



PLSL4602 4" x 6" 160 Watt Slim Mount Two-Way Coaxial Speakers

- 4" x 6" Poly Mica Paper Cone -Foam Edge
- 1" High Temperature Voice Coil
- 1/2" Neodymium PEI Dome Tweeter
- Power 80 Watt RMS/160 Watt Peak Power
- Impedance: 4 Ohms
- Frequency Response: 110-20KHz
- Concealment Magnet
- Strong Capacitor for Excellent Performance
- Includes Grills, Wires and Installation Hardware

PLSL502 5.25" 160 Watt Slim Mount Two-Way Coaxial Speakers

- 5.25" Poly Mica Coated Paper Cone -
- 1" High Temperature Voice Coil
- 1/2" Neodymium PEI Dome Tweeter
- Power 80 Watts RMS/160 Watt Peak Power
- Frequency Response: 95-20KHz
- Concealment Magnet - Impedance: 4 Ohms
- Strong Capacitor for Excellent Performance
- Includes Grills, Wires and Installation Hardware
- Mounting Depth: 1-5/8"

PLSL5702 5" x 7" / 6" x 8" 180 Watt Slim Mount Two-Way Coaxial Speakers

- 5" x 7"/6" x 8" Poly Mica Paper Cone
- 1" High Temperature Voice Coil
- 1/2" Neodymium PEI Dome Tweeter
- Power: 90 Watts RMS/180 Watts Peak Power
- Frequency Response: 75-20KHz
- Concealment Magnet - Impedance: 4 Ohms
- Strong Capacitor for Excellent Performance
- Includes Grills, Wires and Installation Hardware
- Mounting Depth: 1-5/8"

PLSL650K 6.5" 300 Watt Slim Mount Two-Way Component System

This Custom Kit Contains:

- One Pair 6.5" Mid Bass Speakers
- 6.5" Poly Mica Paper Cone with Foam Edge
- 1" High Temperature Voice Coil
- Concealment Magnet
- Power: 150 Watts RMS / 300 Watts MAX
- Impedance: 4 Ohm
- Frequency response: 75Hz-8KHz
- Mounting Depth: 1-3/4"
- One Pair 3/4" Silk dome Tweeters:
- Neodymium Magnet
- 3 Mounting Options: Flush, Surface Angle

- 75 Watts RMS / 150 Watts peak
- One Pair Passive Crossover Network:
- Two - Way Passive Crossover
- 12 dB Octave Slope
- Includes Grills Wires Installation Hardware

PLSL6502 6.5" 200 Watt Slim Mount Two-Way Coaxial Speakers

- 6.5" Poly Mica Coated Paper Cone
- 1" High Temperature Voice Coil
- 1/2" Neodymium PEI Dome Tweeter
- Power: 100 Watt RMS/200 Watts Peak Power
- Impedance: 4 Ohms
- Frequency Response: 85-20KHz
- Concealment Magnet
- Strong Capacitor for Excellent Performance

- Includes Grills, Wires and Installation Hardware
- Mounting Depth: 1-3/4"

PLSL6503 6.5" 200Watt Slim Mount Three-Way Coaxial Speakers

- 6.5" Poly Mica Coated Paper Cone
- 1" High Temperature Voice Coil
- 1/2" Neodymium PEI Dome Tweeter
- Power: 100 Watt RMS/200 Watts Peak Power
- Impedance: 4 Ohms
- Frequency Response: 85-20KHz
- Concealment Magnet
- Strong Capacitor for Excellent Performance

- Includes Grills, Wires and Installation Hardware
- Mounting Depth: 1-3/4"

PLSL6902 6" x 9" 240Watt Slim Mount Two-Way Coaxial Speakers

- 6" x 9" Poly Mica Coated Paper Cone
- 1" High Temperature Voice Coil
- 1" Neodymium PEI Dome Tweeter
- Power Handling: 120 Watts RMS/240 Watts
- Impedance: 4 Ohms
- Frequency Response: 65-20KHz
- Concealment Magnet
- Strong Capacitor for Excellent Performance

- Includes Grills, Wires and Installation Hardware
- Mounting Depth: 2-1/8"

PLBSK30BK=PLBSK30S Portable Bicycle & Sport Speaker With Up To 8gb Storage

- High Quality Stereo Sound
- Supports Micro SD (Up To 8 GB) Playback Mp3s
- Built-In Rechargeable Lithium Battery
- Headphone Jack for Private Listening
- Charges over USB — Connect To Your Computer
- Battery Capacity: 800mah
- Speaker Power: 20 Watts
- Construction Material: Metal
- Dimensions: 3.5" X 3.5" X 3.7"

• Accessories Included



PLBSK30BK



PLBSK30S

PLST6 1/2" 150 Watt Mylar Dome Tri-Mount Tweeter

- 0.5" Mylar Dome
- High Density Neodymium Magnet
- Tri-Mounting System: Flush/Swivel/Surface
- Ferro Fluid Cooling
- 12Db Crossover Network
- Frequency Response: 1.3Khz-22khz
- Spl: 92db @ 1w/1m
- Power Handling: 75 Watts RMS/150 Watts Max
- Includes Custom Mounts, Wires and Installation Hardware



PLST7 1" 150 Watt Mini Dome Tweeter

- 1" Super Mini Dome Tweeter
- High Density Neodymium Magnet
- Flexible Omni-Directional Mounting Base
- Ferro Fluid Cooling
- 12Db Crossover Network
- Frequency Response: 1.3Khz-22khz
- Spl: 92db @ 1w/1m
- Power Handling: 75 Watts RMS/150 Watts Max
- Includes Custom Mount, Wires and Installation Hardware



PLWT3 1" 120 Watt Mini Mylar Dome Tri-Mount Tweeter

- 1" Mylar Dome
- High Density Neodymium Magnet
- Tri-Mounting System: Pivot/Angle/Surface
- Ferro Fluid Cooling
- Integrated Crossover System
- Frequency Response: 2khz-24khz
- Spl: 100db @ 1w/1m
- Power Handling: 60 Watts RMS/120 Watts Max
- Includes Custom Mounts, Wires and Installation Hardware



PLWT4 1.5" 200 Watt Surface Mount Piezo Tweeter

- Extended High Frequency 1.5" Piezo Driver
- Surface Mounting System
- Frequency Response: 3Khz-30Khz
- Sensitivity: 87db @ 1w/1m
- Power Handling: 100 Watts RMS/200 Watts Max
- Includes Custom Mount, Wires and Installation Hardware



PLTWS 6-Way Sunvisor Mount 200 Watt Tweeter System

- Designed For Many Cars
- Over-All Height 14.5mm (0.57")
- 60mm Piezo-Type Midrange x 4
- 40mm Piezo-Type Tweeter x 2
- Power Handling: 100 Watts RMS/200 Watts Max
- Impedance: 4 Ohm
- Sensitivity: 90 dB
- Frequency Response: 2.5KHz - 20KHz
- Includes Wires and Installation Hardware (Mounting Straps)
- Dimensions : 11.75"(W) x 4.75"(H) x 0.57"(D)



PSP8 All Weather 5" PA Mono Extension Horn Speaker

- 5" Reflex ABS Horn
- 15 Watts RMS Nominal Power
- 25 Watts Peak Maximum Power
- 8 Ohms Impedance
- Frequency Response: 450~5,000Hz
- Output: 112db
- 180° Swiveling Adjustable Bracket
- 10' Pre Wired Cord with 3.5mm Mono Connector



2013 Complete Product Catalog

PLBW84 8" 600 Watt DVC Subwoofer

- Blue Injection Molded Cone
- Non-Fatiguing Big Rubber Suspension
- Blue Chrome-Plated Steel Basket
- Bumped Vented Extended Pole Piece
- Silver Plated Terminal
- Flat Progressive Spider
- New Wave-Like Rubber Gasket
- Rubber Magnet Boot
- 1.5" High Temperature Dual Kapton Voice Coil
- Magnet Weight: 60 oz
- 600 Watt Max Power Handling
- Impedance: 4 Ohm (Per Coil)
- Fs: 60, Qms: 5.23, Qes: 0.89, Qts: 0.76, Vas (Cu ft) 2.394
- SPL: 83.5dB
- Overall Diameter: 8.8"
- Mounting Depth: 4.28"



PLBW104 10" 1000 Watt DVC Subwoofer

- Blue Injection Molded Cone
- Non-Fatiguing Big Rubber Suspension
- Blue Chrome-Plated Steel Basket
- Bumped Vented Extended Pole Piece
- Silver Plated Terminal
- Flat Progressive Spider
- New Wave-Like Rubber Gasket
- Rubber Magnet Boot
- 2" High Temperature Dual Kapton Voice Coil
- Magnet Weight: 70 oz
- 1000 Watt Max Power Handling
- Impedance: 4 Ohm (Per Coil)
- Fs: 50, Qms: 4.92, Qes: 0.84, Qts: 0.72, Vas (Cu ft) 4.908
- SPL: 85dB
- Overall Diameter: 10.6"
- Mounting Depth: 5.12"



PLBW124 12" 1200 Watt DVC Subwoofer

- Blue Injection Molded Cone
- Non-Fatiguing Big Rubber Suspension
- Blue Chrome-Plated Steel Basket
- Bumped Vented Extended Pole Piece
- Silver Plated Terminal
- Flat Progressive Spider
- New Wave-Like Rubber Gasket
- Rubber Magnet Boot
- 2" High Temperature Dual Kapton Voice Coil
- Magnet Weight: 70 oz
- 1200 Watt Max Power Handling
- Impedance: 4 Ohm (Per Coil)
- Fs: 40, Qms: 5.0, Qes: 0.90, Qts: 0.75, Vas (Cu ft) 5.204
- SPL: 86dB
- Overall Diameter: 12.8"
- Mounting Depth: 5.76"



PLBW154 15" 1500 Watt DVC Subwoofer

- Blue Injection Molded Cone
- Non-Fatiguing Big Rubber Suspension
- Blue Chrome-Plated Steel Basket
- Bumped Vented Extended Pole Piece
- Silver Plated Terminal
- Flat Progressive Spider
- New Wave-Like Rubber Gasket
- Rubber Magnet Boot
- 2.5" High Temperature Dual Kapton Voice Coil
- Magnet Weight: 80 oz
- 1500 Watt Max Power Handling
- Impedance: 4 Ohm (Per Coil)
- Fs: 30, Qms: 5.0, Qes: 0.91, Qts: 0.70, Vas (Cu ft) 5.100
- SPL: 86dB
- Overall Diameter: 15.8"
- Mounting Depth: 6.84"



PLSQ10D 10" 1200 Watt Square DVC Subwoofer

- Silver Special Treated Polypropylene Cone
- Wide Rubber Surround
- Black Square Steel Basket
- Bumped Vented Extended Pole Piece
- 2.5" High Temperature Kapton Dual Voice Coil
- 4 Ohm Impedance (Per Coil)
- 70 + 70 oz. Magnet Structure
- SPL: 88 dB
- 1200 Watts Peak Power
- Overall Diameter: 11.81"
- Mounting Depth: 5.91"



PLSQ12D 12" 1400 Watt Square DVC Subwoofer

- Silver Special Treated Polypropylene Cone
- Wide Rubber Surround
- Black Square Steel Basket
- Bumped Vented Extended Pole Piece
- 3" High Temperature Kapton Dual Voice Coil
- 4 Ohm Impedance (Per Coil)
- 70 + 70 oz. Magnet Structure
- Fs: 26, Qms: 5.81, Qes: 0.90, Qts: 0.7, Vas (Cu ft) 4.146
- SPL: 90 dB
- 1400 Watts Peak Power
- Overall Diameter: 13"
- Mounting Depth: 6.34"



P1CHW10 10" 1400 Watt DVC Subwoofer

- Titanium Injected Polypropylene Cone
- Non-Fatiguing Big Rubber Suspension
- Chrome-Platted Dome Steel Basket
- Magnet Sealed Within Basket
- Allen Key Magnet Bolts
- 2" High Temperature Dual Kapton Voice Coil
- 1400 Watts Peak Power
- Impedance: Dual 4 Ohm
- 50 + 50 oz. Magnet Structure
- Fs:26.9, Qms:5.23, Qes:0.89, Qts:0.76, Vas (Cu ft)2.394
- SPL: 83.5 dB
- Overall Diameter: 10.16"
- Mounting Depth: 6.20"



P1CHW12 12" 2400 Watt DVC Subwoofer

- Titanium Injected Polypropylene Cone
- Non-Fatiguing Big Rubber Suspension
- Chrome-Platted Dome Steel Basket
- Magnet Sealed Within Basket
- Allen Key Magnet Bolts
- 2" High Temperature Dual Kapton Voice Coil
- 2400 Watts Peak Power
- Impedance: Dual 4 Ohm
- 60 + 60 oz. Magnet Structure
- Fs:23.2, Qms:4.92, Qes:0.84, Qts:0.72, Vas (Cu ft)4.908
- SPL: 85 dB
- Overall Diameter: 12.60"
- Mounting Depth: 6.60"



P1CHW15 15" 3600 Watt DVC Subwoofer

- Titanium Injected Polypropylene Cone
- Non-Fatiguing Big Rubber Suspension
- Chrome-Platted Dome Steel Basket
- Magnet Sealed Within Basket
- Allen Key Magnet Bolts
- 2.5" High Temperature Dual Kapton Voice Coil
- 3600 Watts Peak Power
- Impedance: Dual 4 Ohm
- 70 + 70 oz. Magnet Structure
- Fs:21.2, Qms:5.0, Qes:0.90, Qts:0.75, Vas (Cu ft)5.204
- SPL: 84 dB
- Overall Diameter: 15.84"
- Mounting Depth: 8.52"



P1D12WD 12" 3200 Watt DVC Subwoofer

- Custom Titanium Moulded Poly Cone
- Custom Grooved Specially Treated Rubber Surround
- Diamond Cut Aluminum Die-Cast Basket
- Dual Stacked Magnet Structure
- Chrome Mesh Magnet Vent
- 2" 4 Layer Dual Voice Coil
- Moulded Plastic Gasket
- Spring Loaded Wire Connectors
- 3200 Watts Peak Power
- Magnet Weight: 2 x 100 oz.
- Nominal Impedance: Dual 4 Ohms
- Fs:25, Qms:2.68, Qes:0.90, Qts:0.68, Vas (Cu ft)2.730
- SPL: 92 dB
- Overall Diameter: 13.20"
- Mounting Depth: 5.20"



P1D15WD 15" 4000 Watt DVC Subwoofer

- Custom Titanium Moulded Poly Cone
- Custom Grooved Specially Treated Rubber Surround
- Diamond Cut Aluminum Die-Cast Basket
- Dual Stacked Magnet Structure
- Chrome Mesh Magnet Vent
- 2.5" 4 Layer Dual Voice Coil
- Moulded Plastic Gasket
- Spring Loaded Wire Connectors
- 4000 Watts Peak Power
- Magnet Weight: 2 x 100 oz.
- Nominal Impedance: Dual 4 Ohms
- Fs:20, Qms:5.03, Qes:0.89, Qts:0.66, Vas (Cu ft)8.689
- SPL: 92 dB
- Overall Diameter: 16"
- Mounting Depth: 6.40"



P1NCH10D 10" 1000 Watt Ultra Slim DVC Subwoofer

- 10" High Quality Poly Mica Cone
- Butyl Foam Surround
- Dual 2" High Temperature Kapton Voice Coil
- Independently Fused 20 Amp Speaker Terminals
- 60 Oz Magnet Structure
- Power Handling: 500Watts RMS/1000 Watts Peak
- Frequency Response: 30 Hz - 2.2K Hz
- Impedance (Per coil) : 4 Ohm
- Fs:31.7, Qms:4.07, Qes:0.46, Qts:0.41, Vas (L)49.69
- Efficiency: 90 dB
- Overall Diameter: 10.6"
- Mounting Depth: 3.08"
- Includes Installation Template



2013 Complete Product Catalog

PLW12D 12" 1200 Watt Ultra Slim DVC Subwoofer

- 12" High Quality Poly Mica Cone
- Butyl Foam Surround
- Dual 2.5" High Temperature Kapton Voice Coil
- Independently Fused 20 Amp Speaker Terminals
- 75 Oz Magnet Structure
- Power Handling: 600Watts RMS/1200 Watts Peak
- Frequency Response: 28 Hz - 2.2K Hz
- Impedance (Per coil) : 4 Ohm
- Fs:29.1, Qms:4.08, Qes:0.44, Qts:0.396, Vas (L)102.18
- Efficiency: 92 dB
- Overall Diameter: 12.6"
- Mounting Depth: 3.28"
- Includes Installation Template



PLW10B1 10" 600 Watt Subwoofer

- Blue CD Wave Electro-Plated Cone
- Wide Butyl Rubber Surround w/New Pattern
- Red steel Basket
- Bumped Vented Extended Pole Piece
- 1.5" High Temperature Kapton Voice Coil
- 4 Ohms Impedance
- 70 oz. Magnet Structure
- 600 Watts Peak Power
- Fs:35.9, Qms:5.72, Qes:0.83
- Qts:0.73, Vas (Cu ft)1.932
- SPL: 86.7dB
- Overall Diameter: 10.16"
- Mounting Depth: 4.45"



PLW10RD 10" 600 Watt Subwoofer

- Red CD Wave Electro-Plated Polypropylene Cone
- Wide Butyl Rubber Surround w/New Pattern
- Red steel Basket
- Bumped Vented Extended Pole Piece
- 1.5" High Temperature Kapton Voice Coil
- 4 Ohms Impedance
- 70 oz. Magnet Structure
- 600 Watts Peak Power
- Fs:35.9, Qms:5.72, Qes:0.83, Qts:0.73, Vas (Cu ft)1.932
- SPL: 86.7dB
- Overall Diameter: 10.16"
- Mounting Depth: 4.45"



PLW12B1 12" 800 Watt Subwoofer

- Blue CD Wave Electro-Plated Cone
- Wide Butyl Rubber Surround w/New Pattern
- Blue steel Basket
- Bumped Vented Extended Pole Piece
- 2" High Temperature Kapton Voice Coil
- 4 Ohms Impedance
- 90 oz. Magnet Structure
- 800 Watts Peak Power
- Fs:26.2, Qms:5.81, Qes:0.90
- Qts:0.78, Vas (Cu ft)4.146
- SPL: 85.5dB
- Overall Diameter: 12.20"
- Mounting Depth: 5.34"



PLW12RD 12" 800 Watt Subwoofer

- Red CD Wave Electro-Plated Cone
- Wide Butyl Rubber Surround w/New Pattern
- Red steel Basket
- Bumped Vented Extended Pole Piece
- 2" High Temperature Kapton Voice Coil
- 4 Ohms Impedance
- 90 oz. Magnet Structure
- 800 Watts Peak Power
- Fs:26.2, Qms:5.81, Qes:0.90
- Qts:0.78, Vas (Cu ft)4.146
- SPL: 85.5dB
- Overall Diameter: 12.20"
- Mounting Depth: 5.08"



PLW12DREN 12" 2000 Watt Aluminum Die-Cast Subwoofer

- Red Aluminum Cone
- Heavy Duty High Power Handling Driver
- Wide Butyl Rubber Surround
- Aluminum Die-Cast Basket
- Ultra Sleek and Modern Design
- Dual Stacked Magnet Structure
- Chrome Mesh Magnet Vent
- 2.5" 4 Layer Dual Voice Coil
- Allen Key Connection Terminals
- Red Powder coat insets on Die-Cast Frame
- 2000 Watts Peak Power
- Magnet Weight: 2 x 40 oz.
- Nominal Impedance: Dual 4 Ohms
- Qms: 5.205
- Qes: 0.601
- Qts: 0.539
- X-Max (in): 0.4
- SPL: 85dB



PIW15BL 15" Blue Cone High Performance Woofer

- Blue CD Wave Electro-Plated Polypropylene Cone
- Wide Butyl Rubber Surround with New Pattern
- Blue Steel Basket
- Bumped & Vented Extended Pole Piece
- 2.5" High Temperature Kapton Voice Coil
- 4 Ohm Impedance
- 70 Oz Magnet structure
- 1000 Watts Peak Power



PIW15RD 15" Red Cone High Performance Woofer

- Red CD wave Electro-Plated Polypropylene Cone
- Wide Butyl Rubber Surround with New Pattern
- Red Steel Basket
- Bumped & Vented Extended Pole Piece
- 2.5" High Temperature Kapton Voice Coil
- 4 Ohm Impedance
- 70 Oz Magnet Structure
- 1000 Watts Peak Power



PIBASS8 8-Inch Low-Profile Super Slim Active Amplified Subwoofer System

- 8" Low Profile Subwoofer System Suitable for Under-seat Installations.
- Low Level RCA Input
- High Level Speaker Line Input
- Green LED Power Status Indicator
- Red LED Protection Status Indicator
- Remote Bass Boost Level Control
- Phase Shift Switch: 0 or 180°
- Adjustable Input Sensitivity: 0.2V-3V
- 0 to +12dB Variable Bass Boost (@45Hz)
- Low Pass Filter (50-150 Hz)
- Remote Turn-On Soft Start/Stop Delay
- Thermal, and Overload Protection Circuits
- Fuse: 2 x 15A
- Max Power: 600 Watt
- RMS Power: 300 Watt
- Dimension: 14.5"(D) x 9.5"(W) x 3"(H)
- Weight 10.5 Lbs



PIBASS10 10" Low-Profile Super Slim Active Amplified Subwoofer System

- 10" Slim Woofer
- RCA Low Level Input
- High Level Input
- Green & Red LED Power Status Indicator
- Remote Level Control
- Phase Shift Switch: 0 or 180°
- Adjustable Input Sensitivity: 0.2V-3V
- 0 to +12dB Variable Bass Boost (@45Hz)
- Low Pass Filter (50-150 Hz)
- Soft Delay Remote Turn-On
- Thermal, Short And Overload Protection Circuits
- Fuse: 2 x 20A
- Max Power: 1000 Watts
- RMS Power: 100Watt
- Slim woofer: 250Watt
- Dimension: 15" X 11.8" X 3"
- Weight: 15.5 LBS.



PIBASS28 8" Super Slim Active Amplified Subwoofer System

- RCA Low Level Input
- High Level Input
- Green & Red LED Power Status Indicator
- Phase shift Switch: 0 or 180°
- Soft delay remote Turn-On
- Thermal, Short And Overload Protection Circuits
- Fuse: 2x15A
- RMS Power: 150Wx2 + 300Wx1
- MXA Power: 300Wx2 + 600Wx1
- Subwoofer Gain Control
- Subsonic Filter (20-50Hz)
- 0 to +12dB Variable Bass Boost (@45Hz)
- Low Pass Filter (50-150 Hz)
- Subwoofer Gain Remote Control
- CH 1/2 Gain Control
- High Pass Filter (50-150 Hz)
- Dimensions: 14.5"(L) x 9.5"(W) x 3"(H)
- Weight: 11.6 LBS

NEW!
for 2013



PI10SS Single 10" Slim Designed Subwoofer Bass Box Enclosure System

- 10" High Power 4 Ohm Subwoofer
- Black Flame PP Cone with Foam Edge
- 2.0" Aluminum Voice Coil
- Rear Vented Design
- 1200 Watts MAX Power Handling
- Dimension: 19"W x 13"H x 1.2"D



2013 Complete Product Catalog

PL12SS Single 12" Slim Designed Subwoofer Bass Box Enclosure System

- 12" High Power 4 Ohm Subwoofer
- Black Flame PP Cone with Foam Edge
- 2.0" Aluminum Voice Coil
- Rear Vented Design
- 1200 Watts MAX Power Handling
- Dimension: 19"W x 13"H x 1.2"D



PL210DS Dual 10" Slim Designed Bass Box Speaker System

- Double 10" High Power 4 Ohm Subwoofer
- Black Flame PP Cone with Foam Edge
- 1.5" Aluminum Voice Coil
- Rear Vented Design
- 2400 Watts MAX Power Handling
- Dimension: 29.8"W x 13"H x 11.2"D



PL212DS Dual 12" Slim Designed Subwoofer Bass Box Enclosure System

- Double 12" High Power 4 Ohm Subwoofer
- Black Flame PP Cone with Foam Edge
- 2.0" Aluminum Voice Coil
- Rear Vented Design
- 3000 Watts MAX Power Handling
- Dimension: 34"W x 15"H x 12"D



PL310TS Triple 10" Slim Designed Subwoofer Bass Box Enclosure System

- Three 10" High Power 4 Ohm Subwoofer
- Black Flame PP Cone with Foam Edge
- 2.0" Aluminum Voice Coil
- Rear Vented Design
- 3600 Watts MAX Power Handling
- Dimension: 41"W x 13"H x 1.2"D



PLBN102 Dual 10" 2 Way 1000 Watt Bandpass w/Blue Woofer Rings

- Two 10" High Power 4 Ohm Subwoofers
- Silver Polypropylene Cone
- Specially Treated Black Rubber Edge Suspension
- 2" Aluminum Voice Coil
- Bandpass Alignment For Extra Deep Bass
- Plexi Glass Front Window
- Blue LED Woofer Rings
- 4 Tuned Ports
- 1000 Watts Max Power Handling
- Dimensions: 30"W x 13.6"H x 14.8"D



PLBN122 Dual 12" 2 Way 1200 Watt Bandpass w/Blue Woofer Rings

- Two 12" High Power 4 Ohm Subwoofers
- Silver Polypropylene Cone
- Specially Treated Black Rubber Edge Suspension
- 2" Aluminum Voice Coil
- Bandpass Alignment For Extra Deep Bass
- Plexi Glass Front Window
- Blue LED Woofer Rings
- 4 Tuned Ports
- 1200 Watts Max Power Handling
- Dimensions: 31.8"W x 15.6"H x 16.8"D



P1BS10 10" 400 Watt Bandpass subwoofer

- One 10" High Power 4 Ohm Subwoofers
- Blue Flame Polypropylene Cone
- Specially Treated Black Rubber Edge Suspension
- 2" Aluminum Voice Coil
- Blue LED Lights
- Rear Vented Design
- 400 Watts Max Power Handling
- Dimensions: 13.6"W x 12.2"H x 12.8"D



P1BS102 Dual 10" 800 Watt Bass Box Enclosure System

- Two 10" High Power 4 Ohm Subwoofers
- Blue Flame Polypropylene Cone
- Specially Treated Black Rubber Edge Suspension
- 2" Aluminum Voice Coil
- Rear Vented Design
- Blue LED Lights
- 800 Watts Max Power Handling
- Dimensions: 26"W x 12.2"H x 12.8"D



P1BS12 12" 500 Watt Bandpass Speaker Enclosure System

- One 12" High Power 4 Ohm Subwoofers
- Blue Flame Polypropylene Cone
- Specially Treated Black Rubber Edge Suspension
- 2" Aluminum Voice Coil
- Blue LED Lights
- Rear Vented Design
- 500 Watts Max Power Handling
- Dimensions: 15.6"W x 14.2"H x 14"D



P1BS122 Dual 12" 1000 Watt Bass Box Speaker system

- Two 12" High Power 4 Ohm Subwoofers
- Blue Flame Polypropylene Cone
- Specially Treated Black Rubber Edge Suspension
- 2" Aluminum Voice Coil
- Rear Vented Design
- Blue LED Lights
- 1000 Watts Max Power Handling
- Dimensions: 30"W x 14.2"H x 14"D



P1BWS210 Dual 10" 1000 Watt Bandpass w/Neon Woofer Rings Enclosure System

- Two 10" High Power 4 Ohm Subwoofer
- Silver Polypropylene Cone
- 2" Aluminum Voice Coil
- Specially Treated Black Rubber Edge Suspension
- Blue Neon Speaker Ring
- Bandpass Alignment For Extra Deep Bass
- Plexiglass Front Window
- 2 Tuned Ports
- 1000 Watts Max Power Handling
- Frequency Response: 35Hz-1k Hz
- Dimensions: 13"H x 25.5"W x 14"D



P1BWS212 Dual 12" 1200 Watt Bandpass w/Neon Woofer Rings Enclosure System

- Two 12" High Power 4 Ohm Subwoofer
- Silver Polypropylene Cone
- 2" Aluminum Voice Coil
- Specially Treated Black Rubber Edge Suspension
- Blue Neon Speaker Rings
- Bandpass Alignment For Extra Deep Bass
- Plexiglass Front Window
- 2 Tuned Ports
- 1000 Watts Max Power Handling
- Frequency Response: 35Hz-1k Hz
- Dimensions: 15.5"H x 29.5"W x 15.5"D



2013 Complete Product Catalog

PLHB10 Dual 10" 800 Watt Hatchback Speaker Enclosure System

- Two 10" High Power 4 Ohm Subwoofer
- Non-Press Paper Cone with Rubber Edge
- Specially Treated Black Rubber Edge Suspension
- 2" Aluminum Voice Coil
- Two 2" x 5" Piezo Tweeters
- Vented Design
- Two Handles for Easy Portability
- 800 Watts Max Power Handling
- Frequency Response: 25Hz-20k Hz
- 2 Tuned Ports
- Dimensions: 14.25"H x 32.5"W x 14.25"D



PLHB12 Dual 12" 1000 Watt Hatchback Speaker Enclosure System

- Two 12" High Power 4 Ohm Subwoofer
- Non-Press Paper Cone with Rubber Edge
- Specially Treated Black Rubber Edge Suspension
- 2" Aluminum Voice Coil
- Two 2" x 5" Piezo Tweeters
- Vented Design
- Two Handles for Easy Portability
- 1000 Watts Max Power Handling
- Frequency Response: 25Hz-20k Hz
- 2 Tuned Ports
- Dimensions: 16.5"H x 36"W x 16.5"D



PLPPS110 10" Single Slim Design Foward Vented Enclosure System

- 10" High Power Subwoofer
- Black Molded Polypropylene Cone
- 2" Voice Coil
- Foward Firing Slot Port
- 30 Oz Magnet Structure
- 4 Ohm Impedance
- 200 Watts RMS / 400 Watts Peak
- Frequency Response: 40Hz-4KHz
- SPL: 90dB
- Dimensions: 18"W x 14"H x 13.6"D



PLPPS112 Single 12" Slim Design Foward Vented Enclosure System

- 12" High Power Subwoofer
- Black Molded Polypropylene Cone
- 2" Voice Coil
- Foward Firing Slot Port
- 40 Oz Magnet Structure
- 4 Ohm Impedance
- 250 Watts RMS / 500 Watts Peak
- Frequency Response: 30Hz-3KHz
- SPL: 91dB
- Dimensions: 20"W x 15.6"H x 14.4"D



PLPPS210 Dual 10" Slim Design Foward Vented Enclosure System

- Dual 10" High Power Subwoofer
- Black Molded Polypropylene Cone
- 2" Voice Coil
- Foward Firing Slot Port
- 30 Oz Magnet Structure
- 4 Ohm Impedance
- 400 Watts RMS / 800 Watts Peak
- Frequency Response: 40Hz-4KHz
- SPL: 90dB



PLPPS212 Dual 12" Slim Design Foward Vented Enclosure System

- Dual 12" High Power Subwoofer
- Black Molded Polypropylene Cone
- 2" Voice Coil
- Foward Firing Slot Port
- 40 Oz Magnet Structure
- 4 Ohm Impedance
- 500 Watts RMS / 1,000 Watts Peak
- Frequency Response: 30Hz-3KHz
- SPL: 91dB
- Dimensions: 30.4"W x 14"H x 13.6"D



PLPR10A 10" Slim Design Powered Enclosure System

- 10" High Power Subwoofer
- Black Poly Coated Cone
- 1.5" Voice Coil
- Vinyl Wrapped Amplified Enclosure
- 30 Oz Magnet Structure
- 4 Ohm Impedance
- 150 Watts RMS / 300 Watts Peak
- Frequency Response: 40Hz-400hz
- SPL: 90dB
- RCA/Speaker Line Input
- Dimensions: 16.8"W x 13.6"H x 10.8"D



PLPR12A 12" Slim Design Powered Enclosure System

- 12" High Power Subwoofer
- Black Poly Coated Cone
- 2" Voice Coil
- Vinyl Wrapped Amplified Enclosure
- 40 Oz Magnet Structure
- 4 Ohm Impedance
- 200 Watts RMS / 400 Watts Peak
- Frequency Response: 30Hz-300hz
- SPL: 91dB
- RCA/Speaker Line Input
- Dimensions: 19.2"W x 15.6"H x 11.2"D



PLPR210A Dual 10" Slim Design Powered Enclosure System

- Dual 10" High Power Subwoofer
- Black Poly Coated Cone
- 1.5" Voice Coil
- Vinyl Wrapped Amplified Enclosure
- 30 Oz Magnet Structure
- 4 Ohm Impedance
- 300 Watts RMS / 600 Watts Peak
- Frequency Response: 40Hz-400hz
- SPL: 90dB
- RCA/Speaker Line Input
- Dimensions: 28.8"W x 13.6"H x 10.8"D



PLPR212A Dual 12" Slim Design Powered Enclosure System

- Dual 12" High Power Subwoofer
- Black Poly Coated Cone
- 2" Voice Coil
- Vinyl Wrapped Amplified Enclosure
- 40 Oz Magnet Structure
- 4 Ohm Impedance
- 400 Watts RMS / 800 Watts Peak
- Frequency Response: 30Hz-300hz
- SPL: 91dB
- RCA/Speaker Line Input
- Dimensions: 33.2"W x 15.6"H x 11.2"D



PLSQBS102 Dual 10" 1000 Watts Subwoofer Enclosure

- Dual Square 10" High Power Subwoofer System
- 3" Aluminum Voice Coil
- 4 Ohm Subwoofer
- PP Cone With Large Rubber Edge
- Rear Vent Design
- 1000 Watts Max Power
- Dimension: 14"H x 28"W x 14"D



PLSQBS122 Dual 12" 2000 Watts Subwoofer Enclosure

- Dual Square 12" High Power Subwoofer System
- 3" Aluminum Voice Coil
- 4 Ohm Subwoofer
- PP Cone With Large Rubber Edge
- Rear Vent Design
- 2000 Watts Max Power
- Dimension: 16" H x 32"W x 16"D



2013 Complete Product Catalog

PLPW6D 6.5" 600 Watt Dual Voice Coil 4 Ohm Subwoofer

- Black Steel Basket
- Non-Press Paper Cone
- Specially Treated Foam Surround
- 1.5" 4 Layer Dual Voice Coil
- Dual 4 Ohm Impedance
- 30 OZ Magnet
- 300 Watts RMS / 600 Watts Max Power
- SPL: 89 dB
- Spring Loaded Push Down Speaker Terminals
- Dimensions: 6.6" (Diameter) x 2.9" (Depth)



PLPW8D 8" 800 Watt Dual Voice Coil 4 Ohm Subwoofer

- SPL: 89dB
- 40 Oz. Magnet
- Black Steel Basket
- Non-Press Paper Cone
- Dual 4 Ohm Impedance
- 1.5" 4-Layer Dual Voice Coil
- Specially Treated Foam Surround
- 400 Watt RMS / 800 Watt Max Power
- Spring Loaded Push Down Speaker Terminals
- Dimensions: 8.2" (Diameter) x 3.7" (Depth)



PLPW10D 10" 1000 Watt Dual Voice Coil 4 Ohm Subwoofer

- SPL: 90dB
- 50 Oz. Magnet
- Black Steel Basket
- Non-Press Paper Cone
- Dual 4 Ohm Impedance
- 2-Inch 4-Layer Dual Voice Coil
- Specially Treated Foam Surround
- 500 Watt RMS / 1,000 Watt Max Power
- Spring Loaded Push Down Speaker Terminals
- Dimensions: 10" (Diameter) x 4.7" (Depth)



PLPW12D 12" 1600 Watt Dual Voice Coil 4 Ohm Subwoofer

- SPL: 90dB
- 60 Oz. Magnet
- Black Steel Basket
- Non-Press Paper Cone
- Dual 4 Ohm Impedance
- 2-Inch 4-Layer Dual Voice Coil
- Specially Treated Foam Surround
- 800 Watt RMS / 1,600 Watt Max Power
- Spring Loaded Push Down Speaker Terminals
- Dimensions: 12.2" (Diameter) x 5.1" (Depth)



PLPW15D 15" 2000 Watt Dual Voice Coil 4 Ohm Subwoofer

- SPL: 92dB
- 95 Oz. Magnet
- Black Steel Basket
- Non-Press Paper Cone
- Dual 4 Ohm Impedance
- 2.5-Inch 4-Layer Dual Voice Coil
- Specially Treated Foam Surround
- 1,000 Watt RMS / 2,000 Watt Max Power
- Spring Loaded Push Down Speaker Terminals
- Dimensions: 15.3" (Diameter) x 6.3" (Depth)



PLQB8

- One 8" High Power 4 Ohm Subwoofer
- Blue Polypropylene Cone
- 2" Aluminum Voice Coil
- Bandpass Alignment For Deep Bass
- Plexiglass Front Window
- 400 Watts Max Power Handling
- Frequency Response: 35Hz-800k Hz
- Dimensions: 10"H x 10"W x 17"D

PLQB10

- One 10" High Power 4 Ohm Subwoofer
- Blue Polypropylene Cone
- 2" Aluminum Voice Coil
- Bandpass Alignment For Deep Bass
- Plexiglass Front Window
- 500 Watts Max Power Handling
- Frequency Response: 30Hz-700k Hz
- Dimensions: 12"H x 12"W x 17"D

PLQB12

- One 12" High Power 4 Ohm Subwoofer
- Blue Polypropylene Cone
- 2" Aluminum Voice Coil
- Bandpass Alignment For Deep Bass
- Plexiglass Front Window
- 600 Watts Max Power Handling
- Frequency Response: 25Hz-600k Hz
- Dimensions: 14"H x 14"W x 17"D



P4TA8N 8" 250 Watt Amplified Subwoofer Tube

- One 8" High Power 4 Ohm Subwoofer
- Built-In High Output Amplifier
- Blue LED Light Behind The Grill
- Silver Electroplated Polypropylene Cone
- Specially Treated Black Rubber Edge Suspension
- 1.5" Aluminum Voice Coil
- Bass Reflex Vent for Added Sub-Bass Response
- High Quality Vinyl Wrapped Construction
- 250 Watts Max Power Handling
- RCA/Speaker Line Input
- Dimensions: 10.4"H x 20"W x 9.6"D



P4TA10N 10" 500 Watt Amplified Subwoofer Tube

- One 10" High Power 4 Ohm Subwoofer
- Built-In High Output Amplifier
- Blue LED Light Behind The Grill
- Silver Electroplated Polypropylene Cone
- Specially Treated Black Rubber Edge Suspension
- 1.5" Aluminum Voice Coil
- Bass Reflex Vent for Added Sub-Bass Response
- High Quality Vinyl Wrapped Construction
- 500 Watts Max Power Handling
- RCA/Speaker Line Input
- Dimensions: 12"H x 19.8"W x 12"D



P4TA12N 12" 800 Watt Amplified Subwoofer Tube

- One 12" High Power 4 Ohm Subwoofer
- Built-In High Output Amplifier
- Blue LED Light Behind The Grill
- Silver Electroplated Polypropylene Cone
- Specially Treated Black Rubber Edge Suspension
- 2" Aluminum Voice Coil
- Bass Reflex Vent for Added Sub-Bass Response
- High Quality Vinyl Wrapped Construction
- 800 Watts Max Power Handling
- RCA/Speaker Line Input
- Dimensions: 15.4"H x 22.8"W x 13.8"D



P4TAB8 8" 250 Watt Amplified Subwoofer Tube

- One 8" High Power 4 Ohm Subwoofer
- Built-In High Output Amplifier
- Blue LED Light Behind The Grill
- Blue Polypropylene Cone
- Specially Treated Black Rubber Edge Suspension
- 1.5" Aluminum Voice Coil
- Bass Reflex Vent for Added Sub-Bass Response
- 250 Watts Max Power Handling
- RCA/Speaker Line Input
- Dimensions: 10.4"H x 20"W x 9.6"D



P4TAB10 10" 500 Watt Amplified Subwoofer Tube

- One 10" High Power 4 Ohm Subwoofer
- Built-In High Output Amplifier
- Blue LED Light Behind The Grill
- Blue Polypropylene Cone
- Specially Treated Black Rubber Edge Suspension
- 1.5" Aluminum Voice Coil
- Bass Reflex Vent for Added Sub-Bass Response
- 500 Watts Max Power Handling
- RCA/Speaker Line Input
- Dimensions: 12"H x 19.8"W x 12"D



P4TAB12 12" 800 Watt Amplified Subwoofer Tube

- One 12" High Power 4 Ohm Subwoofer
- Built-In High Output Amplifier
- Blue LED Light Behind The Grill
- Blue Polypropylene Cone
- Specially Treated Black Rubber Edge Suspension
- 2" Aluminum Voice Coil
- Bass Reflex Vent for Added Sub-Bass Response
- 800 Watts Max Power Handling
- RCA/Speaker Line Input
- Dimensions: 15.4"H x 22.8"W x 13.8"D



2013 Complete Product Catalog

PLTB8 8" 400 Watt Carpeted Subwoofer Tube Enclosure System

- One 8" High Power 4 Ohm Subwoofer
- Blue Polypropylene Cone
- Specially Treated Black Rubber Edge Suspension
- 2" Aluminum Voice Coil
- Bass Reflex Vent for Added Sub-Bass Response
- High Quality Carpeted Construction
- 400 Watts Max Power Handling
- Frequency Response: 30Hz-700k Hz
- Dimensions: 11.5" Diam. x 19.5" Length



PLTB10 10" 500 Watt Carpeted Subwoofer Tube Enclosure System

- One 10" High Power 4 Ohm Subwoofer
- Blue Polypropylene Cone
- Specially Treated Black Rubber Edge Suspension
- 2" Aluminum Voice Coil
- Bass Reflex Vent for Added Sub-Bass Response
- High Quality Carpeted Construction
- 500 Watts Max Power Handling
- Frequency Response: 30Hz-700Hz
- Dimensions: 13.6" Diam. x 19.5" Length



PLTB12 12" 600 Watt Carpeted Subwoofer Tube Enclosure System

- One 12" High Power 4 Ohm Subwoofer
- Blue Polypropylene Cone
- Specially Treated Black Rubber Edge Suspension
- 2" Aluminum Voice Coil
- Bass Reflex Vent for Added Sub-Bass Response
- High Quality Carpeted Construction
- 600 Watts Max Power Handling
- Frequency Response: 25Hz-600k Hz
- Dimensions: 16.8" Diam. x 19.5" Length



PLCAP18 1.8 Farad Digital Power Capacitor

- 1.8 Farad Digital Display Power Capacitor
- Capacitance $\pm$ 5%. 20-24 Volt Surge, 105oC
- Blue Digital Display and blue LED flash
- Strong Finishing For A Better Installation Result
- 1 Pair Clear Brackets Included
- Chrome Plated Post Kits
- DC 12- 24 volt
- Electronic Polarity Protection Circuit
- Over Voltage Protection Circuit
- Includes Mounting Charging Hardware
- Aluminum Brushed Case
- Dimensions: 8.66"H 2.99"W



PLCAP50 5.0 Farad Digital Power Capacitor

- 5.0 Farad Digital Display Power Capacitor
- Capacitance $\pm$ 5%. 20-24 Volt Surge, 105oC
- Blue Digital Display and blue LED flash
- Strong Finishing For A Better Installation Result
- 1 Pair Clear Brackets Included
- Chrome Plated Post Kits
- DC 12- 24 volt
- Electronic Polarity Protection Circuit
- Over Voltage Protection Circuit
- Includes Mounting Charging Hardware
- Aluminum Brushed Case
- Dimensions: 8.86"H 3.5"W



PLIAN20 4 Gauge Amplifier Installation Kit

- 21ft. 4 Gauge Red Power Cable
- 4ft. 4 AWG Clear Black Ground Cable
- In-Line Water Resistant Fuse Holder
- 80 Amp AGU Fuse Included
- 20ft. Clear Green Twisted Pair Stereo RCA Interconnect Cable
- 20ft. 16 AWG Clear Stereo Speaker Cable
- 17ft. Blue Remote Cable
- 6ft. Split Loom Cable Conduit
- Power Distribution Block, Gold
- 4 AGW Ring Terminal, 2 pcs
- 4 Spade Terminal, 2 pcs
- 2- 4 AGW Ring Terminals
- 16-14 AGW Spade Terminals 4 pcs
- 10- Cable Ties, 7"



PLDN35T 3.5mm / 1/8" To 3.5mm / 1/8" Stereo Audio Ground Loop Isolator/ Audio Line Driver

- 3.5mm / 1/8" Female Stereo (Left/Right) Audio Input
- 3.5mm / 1/8" Male Stereo (Left/Right) Audio Output
- 6 Volt Audio Line Driver
- Wide Input Signal Range 50mv-6v
- Designed to filter out engine noise emitted from devices while on charge
- Breaks Ground Loops to Eliminate Engine Interference.
- Designed for use with all audio players with 3.5mm / 1/8" audio outputs mp3, Ipod, etc.



PLDN36I Ipod Direct To 3.5mm / 1/8" Stereo Audio Ground Loop Isolator/ Audio Line Driver

- Ipod Direct Stereo (Left/Right) Audio Input
- 3.5mm / 1/8" Male Stereo (Left/Right) Audio Output
- 6 Volt Audio Line Driver
- Wide Input Signal Range 50mv-6v
- Designed to filter out engine noise emitted from devices while on charge
- Breaks Ground Loops to Eliminate Engine Interference.
- Designed for use with Ipod to devices with 3.5mm / 1/8" Stereo Aux input



PLDS20 Dual 40 Amp In-Line Circuit Breaker/ Power Distribution Block

- Power Distribution Block
- Built In Circuit Breaker
- 3 In (4 Gauge)
- 2 Out (8Gauge)
- Allen Screw Terminals
- 40 Amp Power Surge
- Dimensions: 3.60"L x 3.10"W x 1.15"H



PLDS30 Triple 40 Amp In-Line Circuit Breaker

- Power Distribution Block
- Built In Circuit Breaker
- 3 In (4 Gauge)
- 3 Out (8Gauge)
- Allen Screw Terminals
- 40 Amp Power Surge
- Dimensions: 3.90"L x 4.10"W x 1.25"H



PLIPA2 2 Channel 300 Watt Mini Amplifier w/Ipod Direct Input

- 2 Channel IC Mini Amplifier w/Ipod Direct Input Plug
- 2 x 15 Watts RMS @ 4 Ohms/ 2 x 150 Watts Peak
- 3 way Selectable Electronic Crossover Network
- Adjustable Gain Control
- Ipod Direct Audio Inputs
- Power Protection Circuitry
- T.H.D. 1%
- 4 Ohm Stereo Stable
- Anti-Thump Turn On
- Soft Turn On/Off
- Dc: 12-14.8 Volt
- Size: 3.94"L x 2.99"W x 1.49"H



PLIPG1 iPod 3.5mm Stereo to RCA Adaptor

- 3.5mm Stereo (Female) to RCA (Male) 3 Foot Adaptor
- Allows Direct Connection Of Any Headphone Equipped Audio Device To Your existing RCA Aux Input on the Head Unit
- Easily mounted under dash for convenience
- Stereo 3 Foot 3.5mm(Male) To 3.5mm(Male) Audio Cable Included



2013 Complete Product Catalog

PLDN37R Ipod Direct To RCA Stereo Audio Ground Loop Isolator/ Audio Line Driver

- Ipod Direct (Left/Right) Audio Input
- RCA Male Stereo (Left/Right) Audio Output
- 6 Volt Audio Line Driver
- Wide Input Signal Range 50mv-6v
- Designed to filter out engine noise emitted from devices while on charge

- Breaks Ground Loops to Eliminate Engine Interference.
- Designed for use with Ipod to devices with RCA Stereo Aux Input



PLDN38R Ipod Direct To RCA Stereo Audio Ground Loop Isolator/ Audio Line Driver

- Ipod Direct Stereo (Left/Right) Audio Input
- RCA Male Stereo (Left/Right) Audio Output
- 6 Volt Audio Line Driver
- Wide Input Signal Range 50mv-6v
- Designed to filter out engine noise emitted from devices while on charge

- Breaks Ground Loops to Eliminate Engine Interference.
- Designed for use with Ipod to devices with RCA Stereo Aux input



PLG35T 3.5MM / 1/8" Stereo Audio Ground Loop Isolator

- 3.5mm / 1/8" Female Stereo (Left/Right) Audio Input
- 3.5mm / 1/8" Female Stereo (Left/Right) Audio Output
- Designed to filter out engine noise emitted from devices while on charge

- Breaks Ground Loops to Eliminate Engine Interference.
- Designed for use with all audio players with 3.5mm /1/8" audio outputs mp3, Ipod, etc.



PLG36R 3.5MM - 1/8" To RCA Stereo Audio Ground Loop Isolator

- RCA Male Stereo (Left/Right) Audio Output
- 3.5mm - 1/8" Female Stereo (Left/Right) Audio Input
- Breaks Ground Loops to Eliminate Engine Interference
- Filters out engine noise emitted from devices while on charge

- Designed for use with all audio players with 3.5mm /1/8"(ipod, MP3 player, etc.) Into Radio / Source units with RCA ports audio inputs



PLG37I Ipod Direct To 3.5mm / 1/8" Stereo Audio Ground Loop Isolator

- Ipod Direct Stereo (Left/Right) Audio Input
- 3.5mm / 1/8" Male Stereo (Left/Right) Audio Output
- Designed to filter out engine noise emitted from devices while on charge

- Breaks Ground Loops to Eliminate Engine Interference.
- Designed for use with Ipod to devices with 3.5mm / 1/8" Stereo Aux input



PLG38R Ipod Direct to RCA Stereo Audio Ground Loop Isolator/ Audio Line Driver

- Ipod Direct Stereo (Left/Right) Audio Input
- RCA Male Stereo (Left/Right) Audio Output
- 6 Volt Audio Line Driver
- Wide Input Signal Range 50mv-6v
- Designed to filter out engine noise emitted from devices while on charge

- Breaks Ground Loops to Eliminate Engine Interference.
- Designed for use with Ipod to devices with RCA Stereo Aux input



PLAM40 20ft 4 Gauge 1600 Watt Amplifier Hookup For Battery Head Unit & Speakers Installation Kit

- 20ft. 4 Gauge Red Power Wire
- 4ft. 4 Gauge Black Ground Wire
- 20ft. 16 Gauge Blue Remote Turn-On
- 20ft. 12 Gauge Stereo Speaker Wire
- 20ft. Stereo RCA Audio Cable (Male to Male)
- 6ft. Black Split Loom Cable Conduit
- AGU Type 60A Gold Plated Fuse
- In-Line Water Resistant Fuse Holder
- 2 Ring Terminals: 4G
- 2 Spade Terminals: 4G
- 5 Spade Terminals: 16-18G
- 3 Butt Connectors
- 20 Cable Ties
- 1 Black Grommet



PLAM14 20ft 8 Gauge 1000 Watts Amplifier Hookup For Battery Head Unit & Speakers Installation Kit

- 20ft. 8 Gauge Red Power Wire
- 4ft. 8 Gauge Black Ground Wire
- 20ft. 16 Gauge Blue Remote Turn-On
- 20ft. 12 Gauge Stereo Speaker Wire
- 20ft. Stereo RCA Audio Cable (Male to Male)
- 6ft. Black Split Loom Cable Conduit
- AGU Type 60A Gold Plated Fuse
- In-Line Water Resistant Fuse Holder
- 2 Ring Terminals: 8G
- 2 Spade Terminals: 8G
- 5 Spade Terminals: 14-16G
- 3 Butt Connectors
- 20 Cable Ties
- 1 Black Grommet



PLRC3 3ft Stereo RCA Cable

- 3' Dual Stereo RCA Spiral Braid Cable
- OFHC (Oxygen Free Hyper Conductor)
- Gold Contact RCA Connectors
- Ultra Flexible Insulator
- Male to Male Ends
- 36" Inch (91.44cm)



PLRC6 6ft Stereo RCA Cable

- 6' Dual Stereo RCA Spiral Braid Cable
- OFHC (Oxygen Free Hyper Conductor)
- Gold Contact RCA Connectors
- Ultra Flexible Insulator
- Male to Male Ends
- 72" Inch (182.88cm)



PLRC12 12ft Stereo RCA Cable

- 12' Dual Stereo RCA Spiral Braid Cable
- OFHC (Oxygen Free Hyper Conductor)
- Gold Contact RCA Connectors
- Ultra Flexible Insulator
- Male to Male Ends
- 144" Inch (365.76cm)



PLRC18 18ft Stereo RCA Cable

- 18' Dual Stereo RCA Spiral Braid Cable
- OFHC (Oxygen Free Hyper Conductor)
- Gold Contact RCA Connectors
- Ultra Flexible Insulator
- Male to Male Ends
- 216" Inch (548.64cm)



PLRC18 8ft Stereo Shielded RCA Cable

- 8' Dual Shielding RCA Spiral Braided Cable
- 100% Foil Plus An Outer Braid Shield
- Bright Red Colored RCA Plugs
- Low Noise High Definition Cable
- Gold Contact RCA Connectors
- Ultra Flexible Insulator
- Male to Male Ends
- Transparent Red Jacket
- 96" Inch (243.84cm)



2013 Complete Product Catalog

*For a complete list of detailed product information and specifics, remember to visit PyleAudio.com and search the item model number.

PSCBL100

100Ft 12 AWG Spool Speaker Cable With Rubber Jacket



PSCBL300

300Ft 12 AWG Spool Speaker cable With Rubber Jacket



PSCBL500

500Ft 12 AWG Spool Speaker cable With Rubber Jacket



PLVH40

2-Channel HI Level To Low Level Converter with 12V Remote Turn-On

- Full DC Isolation
- Adjustable Attenuation
- Dual Channel• MAX Input: 45 Watts per Channel
- Output Adjustment: 50%
- Freq Response : 20Hz-20KHz
- Gray: R(+)* Gray/ White R(-)* Green L(+)* Green/ White L(-)

Trigger wire Connctions:

- Red +12V DC Constant Power
- Black Ground
- Blue +12V DC Output (when head unit is turned on)



PLV2

1 Into 4 Mobile Video Signal Distribution Amplifier

- 1 Into 4 Mobile Video Amplifier
- One Rca Video Gold Plated Input Jack
- Four Rca Video Gold Plated Output Jacks
- Individual Variable Video Level Controls
- Power On Indicator
- Video Input Level: 2.0Vp-p

- Output Level: 0.5-1.5Vp-p
- Output Impedance: 75 Ohm
- With 4 Mounting Tabs
- Dc 12V Power Input
- Dimensions: 1" X 4.1" X 2.9" L



PLVH60

2 Channel Speaker to RCA Converter

- 2 Channel Hi/Low Level RCA Converter
- Level Adjustable
- Ground Loop Isolation and Noise Elimination
- Aluminum Housing

- Max Input: 50W
- 2 x Female RCA Outputs
- Dimensions: 3.6" L x 2.6" W x 1.08" H



PSC1250

12 Gauge 50 ft. Spool
High Quality Speaker Zip Wire



PSC12100

12 Gauge 100 ft. Spool
High Quality Speaker Zip Wire



PSC12250

12 Gauge 250 ft. Spool
High Quality Speaker Zip Wire



PSC12500

12 Gauge 500 ft. Spool
High Quality Speaker Zip Wire



PSC1450

14 Gauge 50 ft. Spool
High Quality Speaker Zip Wire



PSC14100

14 Gauge 100 ft. Spool
High Quality Speaker Zip Wire



PSC14250

14 Gauge 250 ft. Spool
High Quality Speaker Zip Wire



PSC14500

14 Gauge 500 ft. Spool
High Quality Speaker Zip Wire



PSC1650

16 Gauge 50 ft. Spool
High Quality Speaker Zip Wire



PSC16100

16 Gauge 100 ft. Spool
High Quality Speaker Zip Wire



PSC16250

16 Gauge 250 ft. Spool
High Quality Speaker Zip Wire



PSC16500

16 Gauge 500 ft. Spool
High Quality Speaker Zip Wire



PSC1850

18 Gauge 50 ft. Spool
High Quality Speaker Zip Wire



PSC18100

18 Gauge 100 ft. Spool
High Quality Speaker Zip Wire



PSC18250

18 Gauge 250 ft. Spool
High Quality Speaker Zip Wire



PSC18500

18 Gauge 500 ft. Spool
High Quality Speaker Zip Wire



PSC181000

18 Gauge 1000 ft. Spool
High Quality Speaker Zip Wire



2013 Complete Product Catalog

PWD603RS 4-Button Remote Start/Door Lock Vehicle Security System

- Two 4-button extended range transmitters
- Four 30 amp relays for starter, ignition 1, ignition 2, (programmable), and accessories outputs
- 15 amp relay for parking lights
- Programmable door lock outputs
- Compatible with diesel and gasoline vehicles
- Programmable adjustable crank settings
- Tach or voltage sense
- Built-in LED/Valet switch into the remote receiver
- Parking light and LED diagnostics
- Ground while running output
- Hybrid Vehicle Mode
- Factory alarm arm & disarm outputs
- Panic Mode
- Programmable run time
- Programmable cold start 2, 3, 4 hours
- Comfort Closure
- Auxiliary output
- Horn output
- Car finder



PWD701 4-Button Car Remote Door Lock Vehicle Security System

- 2 Four Button Transmitters
- Status indicator LED
- Valet / override switch
- 120dB 6-tone siren
- Dual stage impact detector
- Remote panic mode
- Remote chirp mute
- Remote sensor bypass
- Passive or active arming
- Flashing parking lights
- Anti-carjack
- 2 Auxiliary outputs
- Limited Lifetime Warranty
- Optional Features
 - Starter defeat
 - Horn honk output
 - Remote keyless entry
 - Illuminated entry
 - Remote trunk release
 - Hood and trunk protection
 - Remote auto start
 - Power window roll up



PWD901 LCD 2-Way Remote Start Security System w/Advanced Impact Sensor

- One 2-way LCD Transmitter
- One 4-Button Water Resistant Transmitter
- Extended Range Transceiver
- Encrypted Coded Transmission
- LED Status Indicator
- 125 db Siren
- Starter Defeat
- Remote Engine Start
- Electronic Impact Sensor with light Impact Response
- Remote Panic Mode
- Remote Valet Mode
- Auxiliary Output
- Remote Chirp Defeat
- Remote Sensor Bypass
- Passive or Active Arming
- Ignition controlled Door Lock/Unlock
- Automatic Sensor Bypass for Defective Zones
- Tamper Alert
- Non-Volatile Memory
- limited lifetime Warranty
- Optional Features
 - Remote Keyless Entry
 - Remote Trunk Release
 - Illuminated Entry
 - Trunk/Hatch Release
 - Horn Honk Output
 - Back-Up Battery
 - Power Window Rollup



PLGLF18A 300 Watt Motorcycle/ATV/Snowmobile Marine FM Receiver w/MP3/iPod Stereo Input, SD & USB

- FM Radio/AUX/Clock Modes
- Built in FM Radio with Electric Tuning
- Up/Down Auto-scan Tuning System
- FM Coverage : 87.5-108.0MHZ
- FM Stereo/Mono Operation
- Dot Matrix LCD FM Frequency
- Volume/Treble/Bass Digital Control
- Mute Function - Clock Time Display
- POWER Switch and Indicator
- 3.5mm Stereo Input Jack, Easy Connection to the Output of Other Audio Devices Like CD/MD/MP3/Ipod, etc
- Remote Control Unit
- Mini Amplifier Suitable for 12 Volts Motorcycles/ Scooters/Boat/snowmobile/ATV/Waverunner
- 50 Watts x 2 @ 2 Ohm 10%THD
- Frequency Response 20Hz-20KHz
- S/N: >50dB
- 3" Dual weatherproof Speakers
- Channel Balance:<2dB
- FM Sensitivity:10V @ S/N 30dB
- Easy Mounting Brackets and Accessories included
- Amplifier Dimensions: 4.37"H X 3.14"W X 1.77"D
- Speaker Dimensions: 4.46"H X 4.09"W X 4.09"D



PLATV18A 300 Watt Motorcycle/ATV/Snowmobile Marine FM Receiver w/MP3/iPod Stereo Input, SD & USB

- FM Radio/AUX/Clock Modes
- Built in FM Radio with Electric Tuning
- Up/Down Auto-scan Tuning System
- FM Coverage : 87.5-108.0MHZ
- FM Stereo/Mono Operation
- Dot Matrix LCD FM Frequency
- Volume/Treble/Bass Digital Control
- Mute Function - Clock Time Display
- POWER Switch and Indicator
- 3.5mm Stereo Input Jack, Easy Connection to the Output of Other Audio Devices Like CD/MD/MP3/Ipod, etc
- Remote Control Unit
- Mini Amplifier Suitable for 12 Volts Motorcycles/ Scooters/Boat/snowmobile/ATV/Waverunner
- 50 Watts x 2 @ 2 Ohm 10%THD
- Frequency Response 20Hz-20KHz
- S/N: >50dB
- 3" Dual weatherproof Speakers
- Channel Balance:<2dB
- FM Sensitivity:10V @ S/N 30dB
- Easy Mounting Brackets and Accessories included
- Amplifier Dimensions: 4.37"H X 3.14"W X 1.77"D
- Speaker Dimensions: 4.46"H X 4.09"W X 4.09"D



PLMCA20 100 Watt Motorcycle/ATV Amplifier w/ Weatherproof speakers w/MP3/Ipod Input

- Mini Amplifier Suitable for 12 Volts Motorcycles/Scooters/Boat/snowmobile/ATV/Waverunner
- 3" Dual weatherproof Speakers
- 3.5mm/RCA Stereo Input Jack, Easy Connection to the Output of Other Audio Devices Like CD/MD/Mp3/Ipod, etc
- Volume Control - Mute Function
- POWER Switch and Indicator

- Easy Mounting Accessories included
- Remote Control Power on/off
- 50 Watts x 2 @ 2 Ohm 10%THD
- Frequency Response: 20Hz-20KHz
- Channel Balance: <2dB - S/N: >50dB
- FM Sensitivity: 10V @ S/N 30dB
- Amplifier Dimensions: 3.74"H X 3.14"W X 1.57"D
- Speaker Dimensions: 4.46"H X 4.09"W X 4.09"D



PLMCA30 400 Watt Motorcycle/ATV Amplifier w/ Weatherproof speakers w/MP3/Ipod Input

- 200 Watts X 2 micro amplifier with Wire harness
- Dual 2.25" Bullet style Weatherproof speakers
- Universal handlebar mount rotary volume control
- 12 Volt T-TAP

- Easy Chrome Stainless Mounting Brackets and Accessories included
- Speaker Dimensions : 2.5"(W) x 2.5"(H) x 3.75"(L)
- Amplifier Dimensions : 3.25"(W) x 1.25"(H) x 2"(L)



PLMCA40 300 Watts Motorcycle/ATV/Snowmobile Mount MP3/Ipod/USB Amplifier

- FM Radio/AUX Modes
- Built in FM Radio Electric Auto-scan Tuning
- Up/Down Auto-scan Tuning System
- FM Coverage : 87.5-108.0MHZ
- Dot Matrix LCD FM Frequency
- Volume Digital Control
- Mute Function
- POWER On/Off Switch
- 3.5mm Stereo Input Jack, Easy Connection to the Output of Other Audio Devices Like CD/MD/Mp3/Ipod, etc
- Remote Control Unit
- Mini Amplifier Suitable for 12 Volts Motorcycles/Scoot-

- ers/Boat/snowmobile/ATV/Waverunner
- 50 Watts x 2 @ 2 Ohm 10%THD
- Frequency Response 20Hz-20KHz
- S/N: >50dB
- 3" Dual weatherproof Speakers
- Channel Balance: <2dB
- FM Sensitivity: 10uV @ S/N 30dB
- USB port: support USB Flash Memory
- SD slot: support 128MB, 256MB, 512MB, 1GB, 2GB/4GB.
- Easy Mounting Brackets and Accessories included
- Amplifier Dimensions: 5.2"H X 3.15"W X 1.86"D
- Speaker Dimensions: 4.8"H X 4.13"W X 4.13"D



PLMCA60 300 Watts Motorcycle/ATV/Snowmobile Mount Amplifier w/Dual

- 300 Watts Micro Amplifier with wire harness
- 3.5mm Stereo Input Jack, Easy Connection to the Output of Other - 12 Volt T-TAP Audio Devices Like CD/MD/Mp3/Ipod, etc
- Dual chrome aluminum bullet style 2.25" speakers
- Universal handlebar mount rotary volume control

- Chrome Stainless Universal handlebar audio mount
- USB charger & Satellite 5V plug
- Easy Chrome Stainless Mounting Brackets and Accessories included
- Speaker Dimensions : 2.5"(W) x 2.5"(H) x 3"(L)
- Amplifier Dimensions : 3.25"(W) x 1.5"(H) x 2"(L)



PLMCA61 600 Watts Motorcycle/ATV/Snowmobile Mount Amplifier w/Dual handle-

- 300 Watts x 2 Channel Micro Amplifier with wire harness
- 3.5mm Stereo Input Jack, Easy Connection to the Output of Other Audio Devices Like CD/MP3/Ipod
- Dual Chrome Aluminum Die-Cast Bullet Style 2.25" Speakers / Strontium Magnet Structure
- Pair of Clamps
- Universal Handlebar Mount Rotary Volume Control

- Chrome Stainless Universal Handlebar Audio Mount
- 12 Volt T-TAP
- USB Charger & Satellite 5V Plug
- Easy Chrome Stainless Mounting Brackets and Accessories included
- Speaker Dimensions : 2.5"(W) x 2.5"(H) x 3"(L)
- Amplifier Dimensions : 3.25"(W) x 1.25"(H) x 2"(L)
- Sold as: Unit



PLMCA70 (4) Speakers - 800 Watt Weatherproof Speaker Kit for Motorcycle, ATV,

- 12 Volt T-TAP
- iPod/MP3 Player Compatible
- Neodymium Magnet Structure • 200 Watts X 4 Micro Amplifier with Wire Harness
- Universal Handlebar Mount Rotary Volume Control
- Easy Chrome Stainless Mounting Brackets and Accessories Included

- Quad Chrome 2.25" Bullet Style Weatherproof Speakers • Speaker Dimensions : 2.5"(W) x 2.5"(H) x 3.75"(L) • Amplifier Dimensions : 3.05"(W) x 1.19"(H) x 5.71"(L)



2013 Complete Product Catalog

PIMCA64 600 Watts Motorcycle/ATV/Snowmobile Mount 2 Channel Amplifier w/ Handlebar Mount

- FM Radio / AUX Models
- Built In FM Radio Electric Up/Down Auto-Scan Tuning System
- Dot Matrix LCD FM Frequency
- 2 Channel Micro Amplifier(300W of each Speaker Output) with Wire Harness
- 150 Watts x 2 @ 4 ohms or 150 Watts x 4 @ 4 ohms
- 3.5mm Stereo Input Jack, Easy Connection to the Output of Other Audio Devices Like CD/MP3/Ipod
- Dual 2.25" Aluminum Die-cast Bullet Speakers

- Kapton Voice Coil
- Pair of Chrome Clamps
- Chrome Universal Handlebar Mount Rotary Volume Control
- Chrome Stainless Universal Handlebar Audio Mount
- 12 Volt T-TAP - Chrome USB Charger
- Easy Chrome Stainless Mounting Brackets and Accessories Included
- Speaker Dimensions : 2.5"(W) x 2.5"(H) x 3"(L)
- Amplifier Dimensions : 3.25"(W) x 1.25"(H) x 2"(L)



PIMCA76 800 Watts Motorcycle/ATV/Snowmobile Mount Amplifier w/Dual handle-bar Mount

- 200 Watts X 4 Micro Amplifier with Wire Harness
- Quad Black Shiny 2.25" Bullet style Weatherproof speakers / Neodymium Magnet Structure
- Universal Handlebar Mount Rotary Volume Control
- 12 Volt T-TAP

- Easy Chrome Stainless Mounting Brackets and Accessories included
- Speaker Dimensions : 2.5"(W) x 2.5"(H) x 3.75"(L)
- Amplifier Dimensions : 3.05"(W) x 1.19"(H) x 5.71"(L)
- Sold as: Unit



PIMCA90 1200 Watts Motorcycle/ATV/Snowmobile Mount Amplifier w/Dual handle-bar Mount

- 300 Watts X 4 Channel Micro Amplifier with Wire Harness
- 3.5mm Stereo Input Jack, Easy Connection to the Output of Other Audio Devices Like D/MP3/Ipod
- Quad Chrome Aluminum Bullet Style 3" Speakers / Neodymium Magnet Structure
- Two Pairs of Chrome Clamps
- Universal Handlebar Mount Rotary Volume Control

- Chrome Stainless Universal Handlebar Audio Mount
- 12 Volt T-TAP
- USB charger & Satellite 5V plug
- Easy Chrome Stainless Mounting Brackets and Accessories included
- Speaker Dimensions: 3.25"(W) x 3.25"(H) x 4.375"(L)
- Amplifier Dimensions : 3.05"(W) x 1.19"(H) x 5.71"(L)
- Sold as: Unit



PIMCA98 600 Watts Motorcycle/ATV/Snowmobile Mount 4 Channel Amplifier w/ Handlebar Mount

- FM Radio / AUX Input
- Built In FM Radio Electric Up/Down Auto-Scan Tuning System
- Dot Matrix LCD FM Frequency
- Digital Volume Control & Mute Function
- Power On / Off Switch
- 4 Channel Micro Amplifier(300W of each Speaker Output) with Wire Harness
- 300 Watts x 2 @ 4 ohms or 150 Watts x 4 @ 4 ohms
- 3.5mm Stereo Input Jack, Easy Connection to the Output of Other Audio Devices Like CD/MD/Mp3/Ipod
- 3" Dual Aluminum Die-cast Bullet Speakers with

- Kapton Voice Coil
- Two Pairs of Chrome Handlebar Clamps
- Chrome Universal Handlebar Mount Rotary Volume Control
- Chrome Stainless Universal Handlebar Audio Mount
- 12 Volt T-TAP
- Chrome USB 5 Volt Charger
- Easy Chrome Stainless Mounting Brackets and Accessories Included
- Speaker Dimensions: 3.25"(W) x 3.25"(H) x 4.375"(L)
- Amplifier Dimensions: 3.50"(W) x 1.375"(H) x 3"(L)



PIMCA31BT 400 Watt Motorcycle/ATV Weatherproof speakers w/ Bluetooth

- 200 Watt X 2 micro amplifier with wire harness
- Dual 2.25" Bullet style Weatherproof speakers
- Universal handlebar mount rotary volume control
- 12 Volt T-TAP
- Easy Chrome Stainless Mounting Brackets and Accessories included

- Control console with 3.5mm Stereo Input Jack, Easy Connection to the Output of Other Audio Devices Like i-Phone, i-Pad, i-Pod, Cell Phone and MP3 etc
- Bluetooth 3.0 technology
- Easy and quick installed handle-bar mount bracket is included
- Speaker Dimensions : 2.5"(W) x 2.5"(H) x 3.75"(L)



PIMCA6BT 600 Watt Motorcycle/ATV Weatherproof Speaker Wire Harness w/ Bluetooth

- 300 Watt 2 Channel Micro Amplifier
- Dual chrome aluminum bullet style 2.25" speakers
- Pair of clamps
- Universal handlebar mount rotary volume control
- Chrome Stainless Universal handlebar audio mount
- USB charger & Satellite 5V plug - 12 Volt T-TAP
- Easy Chrome Stainless Mounting Brackets

- Environment resistance and water proof Bluetooth and in-line volume control
- Console with 3.5mm Stereo Input Jack, Easy Connection to the Output of Other Audio Devices Like i-Phone, i-Pad, i-Pod, Cell Phone and MP3 etc
- Bluetooth 3.0 technology
- Speaker Dimensions : 2.5"(W) x 2.5"(H) x 3"(L)



PLMCA10 100 Watts Motorcycle/ATV/Snowmobile Mount MP3/Ipod Amplifier with Dual handle-bar Mount

- FM Radio/AUX/Clock Modes
- Built in FM Radio with Electric Tuning
- Up/Down Auto-scan Tuning System
- FM Coverage : 87.5-108.0MHZ
- FM Stereo/Mono Operation
- Dot Matrix LCD FM Frequency and Time Display
- Volume/Treble/Bass Digital Control
- POWER Switch and Indicator
- 3.5mm Stereo Input Jack,
- Audio Devices Like CD/MD/Mp3/Ipod, etc

- Mini Amplifier Suitable for 12 Volts Motorcycles/Scooters/Boat/snowmobile/ATV/Waverunner
- 50 Watts x 2 @ 2 Ohm 10%THD
- Frequency Response 20Hz-20KHz
- 3" Dual weatherproof Speakers
- Channel Balance:<2dB
- FM Sensitivity:10V @ S/N 30dB
- Easy Mounting Brackets and Accessories included
- Amplifier Dimensions: 4.37"H X 3.14"W X 1.77"D
- Speaker Dimensions: 4.46"H X 4.09"W X 4.09"D



PLMCS32 400 Watts Motorcycle/ATV/Snowmobile Mount w/Dual handle-bar Mount Weatherproof 2.25"

- Chrome Bullet Style Cabinet
- 2.25" High Quality Poly Mica Cone
- Full Range Water Resistant Construction Design
- 3/4" High Temperature Voice Coil
- Neodymium Magnet Structure
- 400 Watts Rated Peak Power
- Frequency Response : 250-20K Hz

- 4 Ohm Impedance
- Pair of clamps
- Easy Chrome Stainless Mounting Brackets and Accessories included
- Speaker Dimensions : 2.5"(W) x 2.5"(H) x 3.75"(L)



PLMCS36 400 Watt Motorcycle/ATV/Snowmobile Mount w/Dual handle-bar Mount Weatherproof 2.25"

- Black Shiny Bullet Style Cabinet
- 2.25" High Quality Poly Mica Cone
- Full Range Water Resistant Construction Design
- 3/4" High Temperature Voice Coil
- Neodymium Magnet Structure
- 400 Watts Rated Peak Power
- Frequency Response : 250-20K Hz

- 4 Ohm Impedance
- Pair of clamps
- Easy Chrome Stainless Mounting Brackets and Accessories included
- Speaker Dimensions : 2.5"(W) x 2.5"(H) x 3.75"(L)
- Sold as: Pair



PLMCS62 600 Watt 2.25" Speaker Pair with Dual Handle-Bar Mounts - Weatherproof, Aluminum Die-Cast Cabinets

- 4 Ohm Impedance
- Neodymium Magnet Structure
- Mounting Hardware Included
- Peak Power Output: 600 Watt
- 1" High Temperature Voice Coil
- 2.5" High Quality Poly Mica Cone
- Frequency Response: 200-20K Hz

- Aluminum Die-Cast Bullet-Style Cabinets
- Full Range Water Resistant Construction Design
- Easy Chrome Stainless Mounting Brackets and Accessories included
- Speaker Dimensions : 2.5"(W) x 2.5"(H) x 3"(L)



PLMCS64 600 Watt 2.25" Speaker Pair with Dual Handle-Bar Mounts - Weatherproof, Aluminum Die-Cast Cabinets

- 4 Ohm Impedance
- Strontium Magnet Structure
- Mounting Hardware Included
- Peak Power Output: 600 Watt
- 1" High Temperature Voice Coil
- 2.5" High Quality Poly Mica Cone

- Frequency Response: 200-20K Hz
- Aluminum Die-Cast Bullet-Style Cabinets
- Full Range Water Resistant Construction Design
- Easy Chrome Stainless Mounting Brackets and Accessories included
- Speaker Dimensions : 2.5"(W) x 2.5"(H) x 3"(L)



PLMCS92 800 Watt 3" Speaker Pair with Dual Handle-Bar Mounts - Weatherproof, Aluminum Die-Cast Cabinets

- 4 Ohm Impedance
- Neodymium Magnet Structure
- Mounting Hardware Included
- Peak Power Output: 800 Watt
- 1" High Temperature Voice Coil
- 3" High Quality Poly Mica Cone

- Frequency Response: 180-20K Hz
- Aluminum Die-Cast Bullet-Style Cabinets
- Full Range Water Resistant Construction Design
- Easy Chrome Stainless Mounting Brackets and Accessories included
- Speaker Dimensions : 3.35"(W) x 3.35"(H) x 4.8"(L)



PLMCS94 800 Watt 3" Speaker Pair with Dual Handle-Bar Mounts - Weatherproof, Aluminum Die-Cast Cabinets

- 4 Ohm Impedance
- Strontium Magnet Structure
- Mounting Hardware Included
- Peak Power Output: 800 Watt
- 1" High Temperature Voice Coil
- 3" High Quality Poly Mica Cone

- Frequency Response: 180-20K Hz
- Aluminum Die-Cast Bullet-Style Cabinets
- Full Range Water Resistant Construction Design
- Easy Chrome Stainless Mounting Brackets and Accessories included
- Speaker Dimensions : 3.35"(W) x 3.35"(H) x 4.8"(L)





Single Beam HID Xenon Driving Light Systems

Bulb Number	3,000K Yellow	4,300K Yellow/White	6,000K White	8,000K White/Blue	10,000K Blue/Purple	12,000K Purple
880	PHD880K3K	PHD880K4.3K	PHD880K6K	PLHID880K	PHD880K10K	PHD880K12K
9005	PHD9005K3K	PHD9005K4.3K	PHD9005K6K	PLHID9005K	PHD9005K10K	PHD9005K12K
9006	PHD9006K3K	PHD9006K4.3K	PHD9006K6K	PLHID9006K	PHD9006K10K	PHD9006K12K
H10	PHDH10K3K	PHDH10K4.3K	PHDH10K6K	PLHIDH10K	PHDH10K10K	PHDH10K12K
H11	PHDH11K3K	PHDH11K4.3K	PHDH11K6K	PLHIDH11K	PHDH11K10K	PHDH11K12K
H1	PHDH1K3K	PHDH1K4.3K	PHDH1K6K	PLHIDH1K	PHDH1K10K	PHDH1K12K
H3	PHDH3K3K	PHDH3K4.3K	PHDH3K6K	PLHIDH3K	PHDH3K10K	PHDH3K12K
H7	PHDH7K3K	PHDH7K4.3K	PHDH7K6K	PLHIDH7K	PHDH7K10K	PHDH7K12K
5202	PHD5202K3K	PHD5202K4.3K	PHD5202K6K	PLHID5202K	PHD5202K10K	PHD5202K12K

Plug and Play Wire Harness Adapter Included
 No Permanent Modifications to Vehicle
 Long Lasting 3000hr Lifetime
 Safety with Protection Functions
 Connection Circuit Protection Test
 Short Circuit Protection Test

Power: 35W
 Standard Input Current: 3.2A
 Normal Operating Voltage: 80V
 Luminous Flux > 3200lm
 EMC Anti-jamming
 Installation Instructions Included

Dual (Low/High) Beam HID Xenon Driving Lights

Bulb Number	3,000K Yellow	4,300K Yellow/White	6,000K White	8,000K White/Blue	10,000K Blue/Purple	12,000K Purple
9004	PHD9004K3K	PHD9004K4.3K	PHD9004K6K	PLHID9004K	PHD9004K10K	PHD9004K12K
9007	PHD9007K3K	PHD9007K4.3K	PHD9007K6K	PLHID9007K	PHD9007K10K	PHD9007K12K
H13	PHDH13K3K	PHDH13K4.3K	PHDH13K6K	PLHIDH13K	PHDH13K10K	PHDH13K12K
H4	PHDH4K3K	PHDH4K4.3K	PHDH4K6K	PLHIDH4K	PHDH4K10K	PHDH4K12K

Functional High and Low Beam Circuit
 Plug and Play Wire Harness Adapter Included
 No Permanent Modifications to Vehicle
 Long Lasting 3000hr Lifetime
 Safety with Protection Functions
 Connection Circuit Protection Test
 Short Circuit Protection Test

Power: 35W
 Standard Input Current: 3.2A
 Normal Operating Voltage: 80V
 Luminous Flux > 3200lm
 EMC Anti-jamming
 Installation Instructions Included



Slim Ballast Single Beam HID Xenon Driving Light Systems

Bulb Number	6,000K White	8,000K White/Blue	10,000K Blue/Purple	12,000K Purple
880	PSB880K6K	PSB880K8K	PSB880K10K	PSB880K12K
9005	PSB9005K6K	PSB9005K8K	PSB9005K10K	PSB9005K12K
9006	PSB9006K6K	PSB9006K8K	PSB9006K10K	PSB9006K12K
H10	PSBH10K6K	PSBH10K8K	PSBH10K10K	PSBH10K12K
H11	PSBH11K6K	PSBH11K8K	PSBH11K10K	PSBH11K12K
H1	PSBH1K6K	PSBH1K8K	PSBH1K10K	PSBH1K12K
H3	PSBH3K6K	PSBH3K8K	PSBH3K10K	PSBH3K12K
H7	PSBH7K6K	PSBH7K8K	PSBH7K10K	PSBH7K12K
5202	PSB5202K6K	PSB5202K8K	PSB5202K10K	PSB5202K12K

Slim Ballast Takes Up Less Room
 Plug and Play Wire Harness Adapter Included
 No Permanent Modifications to Vehicle
 Long Lasting 3000hr Lifetime
 Safety with Protection Functions
 Connection Circuit Protection Test
 Short Circuit Protection Test

Power: 35W
 Standard Input Current: 3.2A
 Normal Operating Voltage: 80V
 Luminous Flux > 3200lm
 EMC Anti-jamming
 Installation Instructions Included

Slim Ballast Dual (Low/High) Beam HID Xenon Driving Lights

Bulb Number	6,000K White	8,000K White/Blue	10,000K Blue/Purple	12,000K Purple
9004	PSB9004K6K	PSB9004K8K	PSB9004K10K	PSB9004K12K
9007	PSB9007K6K	PSB9007K8K	PSB9007K10K	PSB9007K12K
H13	PSBH13K6K	PSBH13K8K	PSBH13K10K	PSBH13K12K
H4	PSBH4K6K	PSBH4K8K	PSBH4K10K	PSBH4K12K

Slim Ballast Takes Up Less Room
 Functional High and Low Beam Circuit
 Plug and Play Wire Harness Adapter Included
 No Permanent Modifications to Vehicle
 Long Lasting 3000hr Lifetime
 Safety with Protection Functions
 Connection Circuit Protection Test

Short Circuit Protection Test
 Power: 35W
 Standard Input Current: 3.2A
 Normal Operating Voltage: 80V
 Luminous Flux > 3200lm
 EMC Anti-jamming
 Installation Instructions Included

2013 Complete Product Catalog

NEW!
for 2013



PLMR17BTB AM/FM-MPX In-Dash Marine Detachable Face Radio w/SD/MMC/USB Player & Bluetooth

- AM/FM-MPX PLL Tuning
- USB Slot & SD/MMC Card Port For MP3/WMA Music File Playback
- Encoding: Volume, Balance, Bass, Treble & Fader Control
- 30 Station Memory: 18FM/12AM

- Front Auxiliary Input Jack
- Fold-Down Detachable Panel
- Full Function Remote Control
- Seek/Scan Function
- ISO Connector
- ID3 Tag

- AM Frequency Ranges: 350-1710 KHz
- FM Frequency Range: 87.5-107.9 MHz
- 4X60 Watts Maximum Power Output
- Bluetooth Function
- Dimensions: 7"W x 4.72"D x 1.96"H

NEW!
for 2013



For More Products
and Detailed Information
Visit PyleAudio.com

PLMR17BTS AM/FM-MPX In-Dash Marine Detachable Face Radio w/SD/MMC/USB Player & Bluetooth

- AM/FM-MPX PLL Tuning
- USB Slot & SD/MMC Card Port For MP3/WMA Music File Playback
- Encoding: Volume, Balance, Bass, Treble & Fader Control
- 30 Station Memory: 18FM/12AM

- Front Auxiliary Input Jack
- Fold-Down Detachable Panel
- Full Function Remote Control
- Seek/Scan Function
- ISO Connector
- ID3 Tag

- AM Frequency Ranges: 350-1710 KHz
- FM Frequency Range: 87.5-107.9 MHz
- 4X60 Watts Max Power Output
- With Bluetooth
- Dimensions: 7"(W) x 4.72"(D) x 1.96"(H)

PLCD5MRBTB Detachable In-Dash Marine AM/FM-MPX Radio - Plays CDs, MP3 &

- RCA Preamp Output
- ID3 Tag Information
- Negative LCD Display
- PLL Synthesizer Tuning
- Wireless Remote Control
- Fold-Down Detachable Panel
- AM/FM-Tuner CD/MP3 Player
- CD-R/CD-RW for MP3 Playback

- 30 Station Memory: 18FM/12AM
- Electronic Anti-shock for CD/MP3
- 240 Watts Maximum Total Output
- Mode Button: Radio/CD/MP3/USB/SD
- Detachable Face & Carry Case Included
- Built-In Bluetooth Wireless Technology
- Dimensions: 7"W x 4.72"D x 1.96"H

NEW!
for 2013



PLCD5MRBTS AM/FM Marine In-Dash Fold Down Detachable Face Radio w/CD/

- With Built-in 2.0 Bluetooth Technology you can stream audio directly from your hand-held A2DP bluetooth enabled device with crystal clear wireless performance (iPhone, Droid, BlackBerry, Tablets, Etc.)
- AM/FM MPX PLL Synthesizer Stereo Tuner
- CD/CDR/CD-RW Compatible
- Full Size USB Port & SD/MMC Card port for MP3/WMA Digital Music file playback
- Digital Volume/Balance/Bass/Treble & Fader Control

- 30 Station Pre-Set Memory 18FM/12AM
- Front Auxiliary 3.5mm / 1/8" Input jack (Direct headphone input from a portable MP3/CD/ipod/etc)
- Fold-Down Anti-Theft Detachable Face Plate
- Full Function Wireless Remote Control
- Seek/Scan Function
- Blue Illumination with LCD Digital Display & ID3 Tag
- 240 watt total output (60w x 4)
- Dimensions: 7"W x 4.72"D x 1.98"H



NEW!
for 2013



PLDMR3U In-Dash Marine CD/DVD Receiver with 3" Built In Monitor

- DVD/VCD/MPEG4/CD/CD-R/CDRW Compatible
- Slide Down Detachable Face
- Treble/Bass/Balance/Fader/Encoder/Volume
- PLL Synthesizer Tuner
- Marine Coded
- Auto Store / Preset Scan
- AM/FM 2 Band Radio
- 30 Station Memory (18FM / 12AM)
- Built-In 3" (16:9) TFT Color Monitor
- PAL / NTSC Color
- On Screen Display Title/Time/Chapter/Subtitle Angle
- Anti-Shock Mechanism
- RCA Line Out
- Selectable View Angle
- A/V Input A/V Output
- Remote Control
- Rear Camera Output
- 240 Watts (4 x 60 W)
- Last Position Memory
- Dual Zone Function
- Telephone Mute Hands Free Function
- Full Function Remote Control
- Weather Band
- Digital Audio Output



PLDMR87 1.5-Din AM/FM Receiver / CD/DVD/MP3/AM-FM Marine Grade Player

- DVD-Video/DVD±R/DVD±RW/CD-DA/CD-R/RW
- MP3, WMA with ID3-TAG Display
- Splash-proof to IPX5 standards
- Watertight Flip-down Front panel
- AM/FM MPX Electronic Tuning Receiver
- USA - EURO Tuner
- Designed to withstand salt and UV exposure with conformal-coated PCB
- 18 FM/ 12 AM Presets Memory Station
- 24-Bit D/A Converter
- Digital Compact Disc Player
- 3-Beam Laser Tracking
- 8 x Over-sampling
- Anti-Skip Mechanism
- Auto Power Loading
- Minute, Second Track Display
- BBE MP for Compressed Audio Sound Improvement
- 4 X 90 Watts (360 watts total)
- 2 Channel 2 Volt RCA Line output
- RCA Video Output
- Full Function LCD Display
- Auto Best Station Memory
- Loudness Mute Button
- Built-in IR Eye
- Remote Included



PLCDMR97 1.5-Din AM/FM Receiver / CD/CDR/MP3/AM-FM Marine Grade Player

- CD-DA/CD-R/RW Ready
- MP3,WMA with ID3-TAG Display
- Splash-proof to IPX5 standards
- Watertight Flip-down Front panel
- AM/FM MPX Electronic Tuning Receiver
- USA - EURO Tuner
- Designed to withstand salt and UV exposure with conformal-coated PCB
- 18 FM/ 12 AM Presets Memory Station
- Digital Compact Disc Player
- 3-Beam Laser Tracking
- 8 x Over-sampling
- Anti-Skip Mechanism
- Auto Power Loading
- Minute, Second Track Display
- BBE MP for Compressed Audio Sound Improvement
- 4 x 90 Watts (360 watts total)
- 2 Channel 2 Volt RCA Line output
- Full Function LCD Display
- Auto Best Station Memory
- Loudness Mute Button
- Built-in IR Eye
- Remote Included



PLCD9MR AM/FM-MPX In-Dash Marine CD Player w/Full Face Detachable Panel

- In-Dash Marine CD/CDR/CDRW Player
- PLL Synthesizer Stereo Radio
- Anti-Theft Detachable Face
- AM/FM MPX Electronic Tuning Receiver (USA)
- Program CD Tracks
- Full Function Wireless Remote Control
- Digital Compact Disc Player
- Bit D/A Converter
- 3-Beam Laser Tracking
- 8x Oversampling
- Anti-Skip Mechanism
- Auto Power Loading
- Auxiliary Input Function
- Minute, Second Track Display
- 30 Station Memory (18FM/12AM)
- Full Function LCD Display
- Auto Best Station Memory
- Loudness Mute Button
- Full Illumination Carrying Case
- 4 x 40 Watts Maximum Total Output
- Chassis Dimensions: 7"W x 7"D x 1.96"H



PLCD3MR AM/FM-MPX IN -Dash Marine CD/MP3 Player/USB & SD Card Function

- 8x Oversampling
- Bit D/A Converter
- Program CD Tracks
- Auto Power Loading
- Anti-Skip Mechanism
- Loudness Mute Button
- 3-Beam Laser Tracking
- Full Function LCD Display
- Digital Compact Disc Player
- PLL Synthesizer Stereo Radio
- Minute, Second Track Display
- Auto Station Memory Function
- CD-R & CD-RW Disc Compatible
- 30 Station Memory (18FM/12AM)
- USB, SD & Auxiliary Input Functions
- 4 x 40 Watts Maximum Total Output
- Full Function Wireless Remote Control
- AM/FM MPX Electronic Tuning Receiver
- Chassis Dimensions: 7.0" W x 7.0" D x 1.96" H



2013 Complete Product Catalog

PLCD36MRW AM/FM-MPX IN-Dash Marine CD/MP3 Player/Weatherband/USB & SD Card Function

- In-Dash Marine CD/MP3 Player
- PLL Synthesizer Stereo Radio
- AM/FM MPX Electronic Tuning Receiver
- Program CD Tracks
- Built-in Weatherband
- Full Function Wireless Remote Control
- Digital Compact Disc Player
- Bit D/A Converter
- 3-Beam Laser Tracking
- 8x Oversampling
- Anti-Skip Mechanism

- Auto Power Loading
- Auxiliary Input Function
- USB & SD Card Function
- Minute, Second Track Display
- 30 Station Memory (18FM/12AM)
- Full Function LCD Display
- Auto Best Station Memory
- Loudness Mute Button
- Full Illumination Carrying Case
- 4 x 50 Watts Maximum Total Output
- Chassis Dimensions: 7"W x 7"D x 1.96"H



PLCD35MR AM/FM-MPX IN-Dash Marine CD/MP3 Player/USB & SD Card Function

- In-Dash Marine CD/MP3 Player
- PLL Synthesizer Stereo Radio
- AM/FM MPX Electronic Tuning Receiver
- Program CD Tracks
- Full Function Wireless Remote Control
- Digital Compact Disc Player
- Bit D/A Converter
- 3-Beam Laser Tracking
- 8x Oversampling
- Anti-Skip Mechanism
- Auto Power Loading

- Auxiliary Input Function
- USB & SD Card Function
- Minute, Second Track Display
- 30 Station Memory (18FM/12AM)
- Full Function LCD Display
- Auto Best Station Memory
- Loudness Mute Button
- Full Illumination Carrying Case
- 4 x 50 Watts Maximum Total Output
- Chassis Dimensions: 7"W x 7"D x 1.96"H



PLCD34MRW AM/FM-MPX IN-Dash Marine CD/MP3 Player/Weatherband/USB & SD Card Function

- In-Dash Marine CD/MP3 Player
- PLL Synthesizer Stereo Radio
- AM/FM MPX Electronic Tuning Receiver
- Program CD Tracks
- Built-in Weatherband
- Full Function Wireless Remote Control
- Digital Compact Disc Player
- Bit D/A Converter
- 3-Beam Laser Tracking
- 8x Oversampling
- Anti-Skip Mechanism

- Auto Power Loading
- Auxiliary Input Function
- USB & SD Card Function
- Minute, Second Track Display
- 30 Station Memory (18FM/12AM)
- Full Function LCD Display
- Auto Best Station Memory
- Loudness Mute Button
- Full Illumination Carrying Case
- 4 x 50 Watts Maximum Total Output
- Chassis Dimensions: 7"W x 7"D x 1.96"H



PLCD33MR AM/FM-MPX IN-Dash Marine CD/MP3 Player/USB & SD Card Function

- In-Dash Marine CD/MP3 Player
- PLL Synthesizer Stereo Radio
- AM/FM MPX Electronic Tuning Receiver
- Program CD Tracks
- Full Function Wireless Remote Control
- Digital Compact Disc Player
- Bit D/A Converter
- 3-Beam Laser Tracking
- 8x Oversampling
- Anti-Skip Mechanism
- Auto Power Loading

- Auxiliary Input Function
- USB & SD Card Function
- Minute, Second Track Display
- 30 Station Memory (18FM/12AM)
- Full Function LCD Display
- Auto Best Station Memory
- Loudness Mute Button
- Full Illumination Carrying Case
- 4 x 50 Watts Maximum Total Output
- Chassis Dimensions: 7"W x 7"D x 1.96"H



PLMR18 AM/FM-MPX PLL Tuning Radio w/SD/MMC & USB

- AM / FM -MPX PLL Tuning Radio
- 30 Station Memory
- Dot Matrix LCD Display
- Encoder Volume ,Bass ,Treble, Balance ,Fader Control
- Power output 4 x 50 Watts
- 2 Channel RCA Line Out
- USB Interface (Decode MP3 WMA)

- SD/MMC Slot
- Aux Input
- Remote Control
- Marine Coating
- Blue Illumination
- Dimensions: 7.0"W X 6.29"D X 1.9"H



PLMR19W AM/FM-MPX PLL Tuning Radio w/SD/MMC/USB & Weather Band

- AM / FM -MPX PLL Tuning Radio
- 30 Station Memory
- Dot Matrix LCD Display
- Volume ,Bass ,Treble, Balance ,Fader Control
- Power output 4 x 50 Watts
- 2 Channel RCA Line Out
- USB Interface (Decode MP3 WMA)

- SD/MMC Slot
- Aux Input
- Remote Control
- Marine Coating
- Blue Illumination
- Weather Band
- Dimensions: 7.0"W X 6.29"D X 1.9"H



PLMR20W In-Dash AM/FM/MP3 & USB/SD/AUX Inputs

- AM / FM -MPX PLL Tuning Radio
- 30 Station Memory
- Dot Matrix LCD Display
- Volume ,Bass ,Treble, Balance ,Fader Control
- Power output 4 x 50 Watts
- 2 Channel RCA Line Out
- USB Interface (Decode MP3 WMA)

- SD/MMC Slot
- Aux Input
- Remote Control
- Marine Coating
- Blue Illumination
- Weather Band
- Dimensions: 7.0"W X 6.29"D X 1.9"H

NEW!
for 2013



PLMR86B AM/FM-MPX IN-Dash Marine MP3 Player/Weatherband/USB & SD Card Function

- Electronic Volume/Bass/Treble/Fader/Balance Control
- Digital Green LCD Display Panel
- RCA Line Output
- Mute/Clock
- Seek/Scan Function
- 30 Radio Preset Station Memory 18FM-12AM
- EQ Preset (Flat,Classic,Rock,Pop)
- USB/SD/MMC MP3 Player

- Front Aux Input
- 160 Watts Total Output (4 X 40 Watts)
- One pair RCA Line out
- AM Frequency Range: 530~1710kHz
- FM Frequency Range: 87.5~107.9MHz
- Wireless Remote control
- Dimensions: 7"W x 4.72"D x 1.96"H



PLMR87WB AM/FM-MPX IN-Dash Marine MP3 Player/Weatherband/USB & SD Card Function

- Electronic Volume/Bass/Treble/Fader/Balance Control
- Digital Green LCD Display Panel
- Built-in Weatherband
- RCA Line Output
- Mute/Clock
- Seek/Scan Function
- 30 Radio Preset Station Memory 18FM-12AM
- EQ Preset (Flat,Classic,Rock,Pop)

- USB/SD/MMC MP3 Player
- Front Aux Input
- 160 Watts Total Output (4 X 50 Watts)
- One pair RCA Line out
- AM Frequency Range: 530~1710kHz
- FM Frequency Range: 87.5~107.9MHz
- Wireless Remote control
- Dimensions: 7"W x 4.72"D x 1.96"H



PLMR88W AM/FM-MPX IN-Dash Marine MP3 Player/USB & SD Card Function

- Electronic Volume/Bass/Treble/Fader/Balance Control
- Digital Green LCD Display Panel
- RCA Line Output
- Mute/Clock
- Seek/Scan Function
- 30 Radio Preset Station Memory 18FM-12AM
- EQ Preset (Flat,Classic,Rock,Pop)
- USB/SD/MMC MP3 Player

- Front Aux Input
- 160 Watts Total Output (4 X 40 Watts)
- One pair RCA Line out
- AM Frequency Range: 530~1710kHz
- FM Frequency Range: 87.5~107.9MHz
- Wireless Remote control
- Dimensions: 7"W x 4.72"D x 1.96"H



PLMR89WW AM/FM-MPX IN-Dash Marine MP3 Player/Weatherband/USB & SD Card Function

- Electronic Volume/Bass/Treble/Fader/Balance Control
- Digital Green LCD Display Panel
- Built-in Weatherband
- RCA Line Output
- Mute/Clock
- Seek/Scan Function
- 30 Radio Preset Station Memory 18FM-12AM
- EQ Preset (Flat,Classic,Rock,Pop)
- USB/SD/MMC MP3 Player

- Front Aux Input
- 160 Watts Total Output (4 X 40 Watts)
- One pair RCA Line out
- AM Frequency Range: 530~1710kHz
- FM Frequency Range: 87.5~107.9MHz
- Wireless Remote control
- Dimensions: 7"W x 4.72"D x 1.96"H



2013 Complete Product Catalog

PLMRKIT105 AM/FM In-Dash Marine CD Player W/CD/CDR/CDRW/MP3 & Splash Proof Radio Cover

- In Dash Single CD Player
- AM/FM-MPX Tuning Receiver
- CD/CDR/CDRW/MP3/WMA Compatible
- Full Function Remote Control
- 3 Beam Laser Tracking
- 8 x Oversampling
- Anti-Skip Mechanism
- Auto Power Loading
- Auxiliary Input Function
- Minute Second & Track Display

- 24 Station Memory
- Full Function LCD Display
- Auto Best Station Memory
- Full Illumination & Carrying Case
- ISO/DIN Chassis
- Splash Proff Radio Housing
- Transparent Smoke Tint Face Cover
- 4 x 50 Watts maxium Power Output
- 2 Pairs 6.5" Speaker System



PLMRKIT106 AM/FM In-Dash Marine CD Player W/CD/CDR/CDRW/MP3 & Splash Proof Radio Cover

- In Dash Single CD Player
- AM/FM-MPX Tuning Receiver
- CD/CDR/CDRW/MP3/WMA Compatible
- Full Function Remote Control
- 3 Beam Laser Tracking
- 8 x Oversampling
- Anti-Skip Mechanism
- Auto Power Loading
- Auxiliary Input Function
- Minute Second & Track Display

- 24 Station Memory
- Full Function LCD Display
- Auto Best Station Memory
- Full Illumination & Carrying Case
- ISO/DIN Chassis
- Splash Proff Radio Housing
- Transparent Smoke Tint Face Cover
- 4 x 50 Watts maxium Power Output
- 2 Pairs 6.5" Speaker System



PLMRKIT109 Complete Marine Water Proof 4 Speaker CD/USB/Mp3/Combo

- AM/FM-MPX IN -Dash Marine CD/MP3 Player/USB & SD Card Function
- In-Dash Marine CD/MP3 Player
- PLL Synthesizer Stereo Radio
- AM/FM MPX Electronic Tuning Receiver
- Program CD Tracks
- Full Function Wireless Remote Control
- Digital Compact Disc Player
- Bit D/A Converter
- 3-Beam Laser Tracking
- 8x Oversampling
- Anti-Skip Mechanism
- Auto Power Loading
- Auxiliary Input Function

- USB & SD Card Function
- Minute, Second Track Display
- 30 Station Memory (18FM/12AM)
- Full Function LCD Display
- Auto Best Station Memory
- Loudness Mute Button
- Full Illumination Carrying Case
- 4 x 25 Watts Maximum Total Output
- Chassis Dimensions: 7"W x 7"D x 1.96"H
- 6.5" Dual Cone Full-Range Speakers
- White Water Resistant Radio Shield
- USB Drive: Easy plug and play installation, no external power required



PLMRKIT12BK IN-Dash Marine AM/FM PLL Tuning Radio w/ USB/SD/MMC Reader

- AM/FM-MPX PLL Tuning Radio
- LCD Display
- Volume/Bass/Treble/Fader Control
- 30 Station Memory
- Power Output 4 x 50 Watts
- 2 Channel RCA Linea Out
- USB Interface (Decode MP3 WMA)

- SD/MMC Slot
- AUX Input
- Remote Control
- Marine Coating
- Blue Illumination
- Clock Function
- 5.25" Speaker System



PLMRKIT13BK In-Dash Marine AM/FM PLL Tuning Radio w/ USB/SD/MMC Reader

- AM/FM-MPX PLL Tuning Radio
- LCD Display
- Volume/Bass/Treble/Balance/Fader Control
- 30 Station Memory
- Power Output 4 x 50 Watts
- 2 Channel RCA Line Out
- USB Interface (Decode MP3 WMA)
- SD/MMC Slot

- Aux Input
- Remote Control Marine COating
- Blue Illumination
- Clock Function
- 6.5" Speaker System
- Weather Band Function



PLMRK14BK

In-Dash Marine AM/FM PLL Tuning Radio w/ USB/SD/MMC Reader

- AM/FM-MPX PLL Tuning Radio
- LCD Display
- Volume/Bass/Treble/Balance/Fader Control
- 30 Station Memory
- Power Output 4 x 50 Watts
- 2 Channel RCA Line Out
- USB Interface (Decode MP3 WMA)
- SD/MMC Slot
- Aux Input
- Remote Control Marine COating
- Blue Illumination
- Clock Function
- 2 Pairs of 6.5" Speakers System
- Weather Band Function



PLMRK132WT

In-Dash Marine AM/FM PLL Tuning Radio w/ USB/SD/MMC Reader

- AM/FM-MPX PLL Tuning Radio
- LCD Display
- Volume/Bass/Treble/Balance/Fader Control
- 30 station Memory
- Power Output 4 x 50 Watts
- 2 Channel RCA Line Out
- USB Interbase (decode MP2 WMA)
- SD/MMC Slot
- AUX Input
- Remote Control
- Marine Coating
- Blue Illumination
- Clock Function
- 5.25" Speaker System



PLMRK133WT

In-Dash Marine AM/FM PLL Tuning Radio w/ USB/SD/MMC Reader

- AM/FM-MPX PLL Tuning Radio
- LCD Display
- Volume/Bass/Treble/Balnce/Fader Control
- 30 Station Memory
- Power Output 4 x 50 Watts
- 2 Channel RCA Line Out
- USB Interface (Decode MP3 WMA)
- SD/MMC Slot
- AUX Input
- Remote Input
- Marine Coating
- Blue Illumination
- Clock Function
- 6.5" Speaker System
- Weather Band Function



PLMRK134WT

In-Dash Marine AM/FM PLL Tuning Radio w/ USB/SD/MMC Reader

- AM/FM-MPX PLL Tuning Radio
- LCD Display
- Volume/Bass/Treble/Balance/Fader Control
- 30 Station Memory
- Power Output 4 x 50 Watts
- 2 Channel RCA Line Out
- USB Interface (Decode MP3 WMA)
- SD/MMC Slot
- Aux Input
- Remote Control Marine COating
- Blue Illumination
- Clock Function
- 2 Pairs of 6.5" Speakers System
- Weather Band Function



PLCD15MR

AM/FM-MPX In-Dash Marine CD/MP3 Player w/Full Face Detachable

- In-Dash Marine CD/MP3 Player
- Anti-Theft Full Detachable Front Panel
- AM/FM MPX Electronic Tuning Receiver
- USA Tuner
- MP3/CD-R/CDRW Compatible
- Full Function Wired Remote Control
- Digital Compact Disc Player
- Bit D/A Converter
- 3-Beam Laser Tracking
- 8 x Oversampling
- Anti-Skip Mechanism
- Auto Power Loading
- Minute, Second Track Display
- Auxiliary Input Function
- Dual RCA
- 30 Station Memory (18FM/12AM)
- Full Function LCD Display
- Auto Best Station Memory
- Loudness Mute Button
- Subwoofer Output
- PCB & Front Panel w Conformal & UV Coating
- Full Illumination & Carry Case
- ISO/DIN Chassis
- 4x60 Watts Maximum Total Output
- Chassis Dimensions: 7"W x 7"D x 1.96"H



2013 Complete Product Catalog

PLCD14MRKT Waterproof Marine CD/MP3 Player Receiver w/ Speaker & Splash Proof Radio

- In-Dash Marine CD/MP3 Player
- Anti-Theft Detachable Face
- AM/ FM/ MPX Electronic Tuning Receiver (USA)
- CD/ CDR/ CDRW/ MP3/WMA Compatible
- Full Function Wireless Remote Control
- 3 Beam Laser Tracking
- 8 x Oversampling
- Anti-Skip Mechanism
- Auto Power Loading
- Minute/ Second Track Display

- 25 Station Memory
- Full Function LCD Display
- Auto Best Station Memory
- Full Illumination Carrying Case
- Pair of 5.25" Waterproof Speakers
- Auxiliary Input on Face Plate
- Splash Proof Radio Housing
- Transparent Smoke Tint Face Cover
- 4 x 25 Watts Maximum Total Output
- Chassis Dimension: 7" W x 7" D x 1.96"H



PLCD4MRKT Complete Marine Water Proof 4 Speaker CD/USB/Mp3/Combo w/ Stereo Cover (Black)

- In-Dash Marine CD/MP3 Player
- PLL Synthesizer Stereo Radio
- AM/FM MPX Electronic Tuning Receiver
- Program CD Tracks
- Full Function Wireless Remote Control
- Digital Compact Disc Player
- Bit D/A Converter
- 3-Beam Laser Tracking
- 8x Oversampling
- Anti-Skip Mechanism
- Auto Power Loading
- Auxiliary Input Function

- USB & SD Card Function
- Minute, Second Track Display
- 30 Station Memory (18FM/12AM)
- Full Function LCD Display
- Auto Best Station Memory
- Loudness Mute Button
- Full Illumination Carrying Case
- 4 x 50 Watts Maximum Total Output
- Chassis Dimensions: 7"W x 7"D x 1.96"H
- 2 Pairs 150 Watts 6.5" 2 Way White Marine Speakers
- Complete with Wires Mounting Hardware
- White Water Resistant Radio Shield



PLCD6MRKT Waterproof Marine AM/FM/CD Player Receiver W/ 4 X 5.25" Speakers & Splash Proof Radio

- In-Dash Marine CD Player
- Anti-Theft Detachable Face
- AM/FM/ MPX Tuning Receiver (USA)
- CD/CDR/CDRW/ Compatible
- Full Function Wireless Remote Control
- 3 Beam Laser Tracking
- 8 X Oversampling
- Ant-Skip Mechanism
- Auto Power Loading
- Auxiliary Input On Face Plate

- Minute/ Second Track Display
- 24 Station Memory
- Full Function LCD Display
- Auto Best Station Memory
- Full Illumination Carrying Case
- 2 Pairs Of 5.25" Waterproof Speakers
- Splash Proof Radio Housing
- Transparent Smoke Tint Cover Face
- 4 X 50 Watts Maximum Total Output
- Chassis Dimensions: 7"W X 7"D X 1.96"H



PLCD7MRKT Waterproof Marine AM/FM/CD Player Receiver W/ 4 X 5.25" Speakers & Splash Proof Radio

- In-Dash Marine CD Player
- Anti-Theft Detachable Face
- AM/FM/ MPX Tuning Receiver (USA)
- CD/CDR?CDRW/WMA Compatible
- Full Function Wireless Remote Control
- 3 Beam Laser Tracking
- 8 X Oversampling
- Ant-Skip Mechanism
- Auto Power Loading
- Auxiliary Input On Face Plate

- Minute/ Second Track Display
- 24 Station Memory
- Full Function LCD Display
- Auto Best Station Memory
- Full Illumination Carrying Case
- 2 Pairs Of 5.25" Waterproof Speakers
- Transparent Smoke Tint Cover Face
- 4 X 25 Watts Maximum Total Output
- Chassis Dimensions: 7"W X 7"D X 1.96"H



PLCD8MRKT Complete Marine Water Proof 4 Speaker CD/USB/Mp3/Combo w/ Stereo Cover (White)

- In-Dash Marine CD/MP3 Player
- PLL Synthesizer Stereo Radio
- AM/FM MPX Electronic Tuning Receiver
- Program CD Tracks
- Full Function Wireless Remote Control
- Digital Compact Disc Player
- Bit D/A Converter
- 3-Beam Laser Tracking
- 8x Oversampling
- Anti-Skip Mechanism
- Auto Power Loading
- Auxiliary Input Function
- USB & SD Card Function

- Minute, Second Track Display
- 30 Station Memory (18FM/12AM)
- Full Function LCD Display
- Auto Best Station Memory
- Loudness Mute Button
- Full Illumination Display
- 4 x 50 Watts Maximum Total Output
- Chassis Dimensions: 7"W x 7"D x 1.96"H
- 2 Pairs 120 Watts 6.5" 2 Way White Marine Speakers
- Complete with Wires Mounting Hardware
- Mounting Depth: 2.5"
- White Water Resistant Radio Shield



PLCD1MRKT Waterproof Marine CD/MP3 Player Receiver w/5.25" Speakers & Splash Proof Radio Cover

- In-Dash Marine CD/MP3 Player
- Anti-Theft Detachable Face
- AM/ FM/ MPX Tuning Receiver (USA)
- CD/ CDR/ CDRW/ MP3/WMA Compatible
- Full Function Wireless Remote Control
- 3 Beam Laser Tracking
- 8 x Oversampling
- Anti-Skip Mechanism
- Auto Power Loading
- Auxiliary Input on Face Plate

- Minute/ Second Track Display
- 24 Station Memory
- Full Function LCD Display
- Auto Best Station Memory
- Full Illumination Carrying Case
- Pair of 5.25" Waterproof Speakers
- Splash Proof Radio Housing
- Transparent Smoke Tint Face Cover
- 4 x 25 Watts Maximum Total Output
- Chassis Dimensions: 7" W x 7" D x 1.96" H



PLMRCB3 Universal Marine Stereo Housing w/Full Chassis Wired Casing (Black)

- Universal Marine Stereo Housing
- Protect your Stereo from Harsh Marine Environment
- Includes a 2 Position Hinged Front Door
- Sealed with a Neoprene Gasket
- Accommodate Dual Post/ Removable & DIN Style Stereos
- Fits Din Style or Removable Stereos
- U shaped Mounting Bracket for Deck or Overhead

- Installation
- Stainless Steel Mounting Hardware
- Polycarbonate Bracket
- Support Shelf for Radio in Rear of Housing
- Pre-Wired Power(3 Wire), Speaker (8 Wire), RCA (2 Wire), Antenna
- UV Resistant Plastic
- Dimensions: 4"(H) x 9.1/8"(W) x 1/2"(D)



PLMRCB1 Black Water Resistant Radio Shield

- Protects Your Stereo From The Elements
- Smoke Colored Housing Window
- Spring Loaded Flip-Up Door
- Support Shelf In Rear Of Housing For Radio

- UV Resistant Plastic
- Black Base Color
- Mounting Gasket Included
- Dimensions: 9" W x 1.95" D x 4.10"H



PLMRCW1 White Water Resistant Radio Shield

- Protects Your Stereo From The Elements
- Smoke Colored Housing Window
- Spring Loaded Flip-Up Door
- Support Shelf In Rear Of Housing For Radio

- UV Resistant Plastic
- White Base Color
- Mounting Gasket Included
- Dimensions: 9" W x 1.95" D x 4.10"H



PLMRCW2 White Water Resistant Radio Shield

- Protects Your Stereo From The Elements
- Smoke Colored Housing Window
- Spring Loaded Slide-up Door
- Support Shelf In Rear Of Housing For Radio

- UV Resistant Plastic
- White Base Color
- Mounting Gasket Included
- Dimensions: 9.5" W x 1" Outside(4.5" Overall) D x 4"H



PLMRIPWG iPod/MP3 Waterproof 3.5mm Stereo to RCA Adaptor

- Waterproof 3.5mm Stereo To RCA 3 Foot Adaptor
- Allows Direct Connection Of Any Headphone Equipped Audio Device To Your Existing RCAs On The Head Unit

- Easily Mounted Under Dash For Convenience
- Stereo 3.5mm Audio Cable Male to Male 3 Foot
- Dimensions: 2"L x 2"W x 0.85"H



2013 Complete Product Catalog

P1MRA120 iPod/MP3 Waterproof 3.5mm Stereo to RCA Adaptor

- Waterproof 3.5mm Stereo To RCA Adaptor 12 Foot
- Allows Direct Connection Of Any Headphone Equipped Audio Device To Your Existing RCSs On The Head Unit
- Mounting Diagram For A Factory Finish Installation
- Stereo 3.5mm Audio Cable Male to Male 3 Foot
- 0.75" Diameter x 1.5" Length



P1MRA121 Marine Wire Antenna

- Weather Resistant AM/FM Marine Antenna
- Provides excellent Radio reception
- 22" Braided Cable



P1MRA120 2 Channel 240 Watt Waterproof Marine Amplifier

- IC Power 120 Watts x 2 Output
- Variable Input Gain Control
- Power ON LED Indicator
- High/Low Level Input
- Remote Turn On/Off
- Speaker Output Connector
- Gold Plated RCA Inputs
- Thermal / Overload / Short Circuit Protection
- Heavy Duty Aluminum Alloy Heatsink
- Load Dump Over Voltage Thermal Shutdown AC/DC Short Circuit Protector
- Dimensions: 7.87"W x 2"H x 5.20"L
- Weight: 2.30 (lbs)



P1MRA200 2 Channel 400 Watt Bridgeable Waterproof Marine Amplifier

- 200 Watts x 2 Output
- 400 Watts x 1 Bridged Output
- Variable Hi/Lo Electronic Crossover Network
- MOSFET Power Supply
- Variable Input Gain Control
- Power ON LED Indicator
- Protection LED Indicator
- High/Low Level Input
- Remote Turn On/Off
- Speaker Output Connector
- Gold Plated RCA Inputs
- Soft Turn-On Circuit
- Thermal / Overload / Short Circuit Protection
- Heavy Duty Aluminum Alloy Heatsink
- Dimensions: 7.87"W x 2"H x 10"L
- Weight: 4.20 (lbs)



P1MRA400 4 Channel 400 Watt Waterproof Marine Amplifier

- IC Power 100 Watts x 4 Output
- Variable Input Gain Control
- Power ON LED Indicator
- High/Low Level Input
- Remote Turn On/Off
- Speaker Output Connector
- Gold Plated RCA Inputs
- Thermal / Overload / Short Circuit Protection
- Heavy Duty Aluminum Alloy Heatsink
- Load Dump Over Voltage
- Dimensions: 7.87"W x 2"H x 8.0"L
- Weight: 3.30 (lbs)



P1MRA220 2 Channel 600 Watt Waterproof Marine Bridgeable Mosfet Amplifier

- 300 Watts x 2 Output
- 600 Watts x 1 Bridged Output
- Variable Hi/Lo Electronic Crossover Network
- Variable Bass Boost
- Power On LED Indicator
- LED Protection Indicator
- Blue LED Level Display
- Variable Input Level (Gain) Control
- Thermal, Overload, Short Circuit Protection
- Dimensions: 10.9"W x 2.7"H x 8.25"L



*Visit PyleAudio.com and search item model number for more detailed information and specifics



NEW!
for 2013



Hydra Series Waterproof iPod/MP3 Marine Power Amplifiers

Model	Total Watt Output	Channels	Compact Micro Amplifier	Color
PLMRMP1A	200	2	Yes	White
PLMRMP1B	200	2	Yes	Black
PLMRMP2A	400	4	Yes	White
PLMRMP2B	400	4	Yes	Black
PLMRMP3A	400	4	No	White
PLMRMP3B	400	4	No	Black

All Models Include:

- iPod/MP3 Waterproof 3.5mm Stereo to RCA Connector
- iPod/MP3 Waterproof Poly Bag
- Adjustable High / Low Level Inputs
- Electronic Crossover Network
- Power Protection Circuitry
- 2 Ohm Stereo Stable

- Frequency Response: 10Hz - 40 kHz
- Volume Gain Remote Control
- Channel Separation: > 65 dB
- Anti-Thump Power-On
- Soft Turn On / Off
- S/N Ratio: >95 dB
- RCA Line Input

Hydra Series Waterproof iPod/MP3 Marine Power Amplifiers & Speaker Kits

Model	Total Watt Output	Channels	Compact Micro Amplifier	Speakers Included	Color
PLMRKT2A	200	2	Yes	2	White
PLMRKT2B	200	2	Yes	2	Black
PLMRKT4A	400	4	No	4	White
PLMRKT4B	400	4	No	4	Black

All Models Include:

- iPod/MP3 Waterproof 3.5mm Stereo to RCA Connector
- iPod/MP3 Waterproof Poly Bag
- Adjustable High / Low Level Inputs
- Electronic Crossover Network
- Power Protection Circuitry
- 2 Ohm Stereo Stable

6.5" 2-Way Marine Speakers :

- 6.5" High Quality Polypropylene Cone
- Suspension Cloth Surround
- 2" Polymer Cone Tweeter

- Frequency Response: 10Hz - 40 kHz
- Volume Gain Remote Control
- Channel Separation: > 65 dB
- Anti-Thump Power-On
- Soft Turn On / Off
- S/N Ratio: >95 dB
- RCA Line Input

- 200 Watt RMS / 400 Watt Peak
- Frequency Response: 80-20kHz
- Impedance: 8 Ohm

2013 Complete Product Catalog

PLMRA420 4 Channel 1000 Watt Waterproof Marine Bridgeable Mosfet Amplifier

- 250 Watts x 4 Output
- 500 Watts x 2 Bridged Output (250W x 2 + 500W x 1)
- Dual Variable Hi/Lo Electronic Crossover Network
- Dual Variable Bass Boost
- Power On LED Indicator
- LED Protection Indicator
- Blue LED Level Display
- Tri-Mode Configurable
- Variable Input Level (Gain) Control
- Thermal, Overload, Short Circuit Protection
- Dimensions: 10.9" W x 2.7" H x 12" L



PLMRA620 6 Channel 2000 Watt Waterproof Marine Bridgeable Mosfet Amplifier

- 4 x 100W + 2 x 250W RMS @ 4 Ohms
- 4 x 250W + 2 x 500W MAX @ 4 Ohms
- 2 x 400W + 1 x 900W MAX @ 4 Ohms Bridged
- 4 x 175W + 1 x 400W RMS at 2 Ohms
- Variable Hi/Lo Electronic Crossover Network (CH1 / CH2 and CH3 / CH4)
- Variable Bass Boost (CH5 / CH6)
- 2 Ohm Stereo Stable
- Power ON LED Indicator
- Protection LED Indicator
- Gold RCA Inputs
- Remote Bass Boost
- Blue LED Level Display
- Soft Turn On/Off
- Tri-Mode Configurable
- Low and High Pass Filter Controls (CH3 / CH4)
- Variable Input Level (Gain) Control
- Thermal / Overload / Short Circuit Protection
- Dimensions: 10.9" W x 2.7" H x 19.6" L



PLMRA1000D 2000 Watt Mono Block Waterproof Marine Mosfet Digital Amplifier

- RMS Power @ 4 Ohms: 200 W
- RMS Power @ 2 Ohms: 400 W
- RMS Power @ 1.3 Ohms: 1000 W
- Maximum Power Output 2000W Mono
- Mono Block Subwoofer Amplifier
- 1 Ohm Stable
- MOSFET Power Supply
- PWM (Pulse-Width-Modulation) System
- Glass Epoxy PCB
- Gold RCA Inputs
- Remote Bass Boost
- Blue LED Level Display
- Soft Turn On/Off
- Custom Terminal Block for Speaker Connection
- Thermal / Overload / Short Circuit Protection
- Variable Subsonic Filter (15Hz~40Hz, 24dB/Octave)
- Phase Control 0-180 degree
- Input Impedance : 10K Ohms
- Advanced Protection Circuitry
- S/N Ratio: 90dB
- Dimensions: 10.9" W x 2.7" H x 12" L



PLMRAKT8 Marine Grade 8 Gauge Amplifier Installation Kit

- Marine Grade Cables and Wires
- Perfect for Installations in Boats and Outdoor
- High Resistance to Moisture
- 20ft. 8 Gauge Red Power Wire
- 4ft. 8 Gauge Black ground Wire
- 20ft. 18 Gauge Blue Remote Turn-On
- 20ft. 12 Gauge StereoSpeaker Wire
- 20ft. Right Angle/Standard Stereo RCA Audio Cable
- 6ft. Black Split Loom Cable Conduit
- AGU Type 60A Gold Plated Fuse
- Water Resistant In-line Fuse Holder
- 2 Ring Terminals: 8G
- 2 Spade Terminals: 8G
- 5 Spade Terminals: 14-16G
- 3 Butt Connectors 20 Cable Ties
- 1 Black Grommet



PLMRCAP18 1.8 F 20V Round Marine Capacitor


- Aluminum Brushed Case
- Blue Digital Display
- PVC sleeve and blister package
- Dimensions: 8.66" H x 2.99" W



***For a complete list of detailed product information and specifics, remember to visit PyleAudio.com and search the item model number.**

PLMRSW50 18 Gauge 50 FT Stereo Marine Grade Speaker Wire

- 18 AWG Stereo Wire
- Blue White Marine Grade Insulation
- Ideal for new Marine Installation
- 50ft Length Spool



PLMR64W 5" 3 Way Indoor/Outdoor Water Proof Wall Mount Speaker System

- Wall Mount Speaker System Impact ABS Plastic Cabinet.
- 5" Woofer With Rubber Edge.
- 1" Aluminum Voice Coil.
- 3" Mid & High Quality Cone & Cloth Edge.
- 0.75" Aluminum Voice Coil.
- 500 Watts Max Power.
- Frequency Response: 60--16K HZ (+-3dB).
- Sensiivity:90dB@1W/M.
- 8 Ohms Impedance.



PLMR64B 5" 3 Way Indoor/Outdoor Water Proof Wall Mount Speaker System

- Wall Mount Speaker System Impact ABS Plastic Cabinet.
- 5" Woofer With Rubber Edge.
- 1" Aluminum Voice Coil.
- 3" Mid & High Quality Cone & Cloth Edge.
- 0.75" Aluminum Voice Coil.
- 500 Watts Max Power.
- Frequency Response: 60--16K HZ (+-3dB).
- Sensiivity:90dB@1W/M.
- 8 Ohms Impedance.



PLMR65 6.5" 200 Watt Two-Way Black Wake Board Speakers

- Excellent For Monitor or Surround Sound Applications
- Water Resistant Construction Design
- 6-1/2" Poly Mica Woofer Cone
- Butyl Rubber Surround
- 25Oz. Magnet Structure
- 1" Polymer Dome Tweeter
- 200 Watts Rated Peak Power
- Frequency Response: 70Hz-20KHz
- 4 Ohm Impedance
- Heavy Duty Plastic Cabinet
- Gold Plated Plug Terminals
- 1.75" Mounting Bracket Included
- Dimensions: 8.5" D x 10" L



PLMR85 8" 300 Watt Two-Way Black Wake Board Speakers

- Excellent For Monitor or Surround Sound Applications
- Water Resistant Construction Design
- 8" Poly Mica Woofer Cone
- Butyl Rubber Surround
- 30Oz. Magnet Structure
- 1" Polymer Dome Tweeter
- 300 Watts Rated Peak Power
- Frequency Response: 60Hz-20KHz
- 4 Ohm Impedance
- Heavy Duty Plastic Cabinet
- Gold Plated Plug Terminals
- 1.75" Mounting Bracket Included
- Dimensions: 10" D x 10" L



2013 Complete Product Catalog

PLMRW65 6.5" 200 Watt Two-Way White Wake Board Speakers

- 4 Ohm Impedance
- Butyl Rubber Surround
- 25Oz. Magnet Structure
- Gold Plated Plug Terminals
- White Bullet-Style Cabinets
- 6-1/2" Poly Mica Woofer Cone
- 1-Inch' Polymer Dome Tweeter
- Frequency Response: 70Hz-20KHz
- 200 Watts Maximum Power Output
- 1.75" Mounting Bracket Included
- USB Charger & Satellite 5V Plug
- Water Resistant Construction Design
- Full Range Water Resistant Construction
- Excellent For Monitor or Surround Sound Applications
- Dimensions: 8.5" D x 10" L



PLMRW85 8" 300 Watt Two-Way White Wake Board Marine Speakers

- Excellent For Monitor or Surround Sound Applications
- Water Resistant Construction Design
- 8" Poly Mica Woofer Cone • Butyl Rubber Surround
- 30Oz. Magnet Structure
- 1" Polymer Dome Tweeter
- 300 Watts Rated Peak Power
- Frequency Response: 60Hz-20KHz
- 4 Ohm Impedance
- Heavy Duty Plastic Cabinet
- Gold Plated Plug Terminals
- 1.75" Mounting Bracket Included
- Dimensions: 10" D x 10" L



PLMR4W 4" Dual Cone Waterproof Stereo Speaker System

- 4" Dual Cone Full range Speakers
- Completely Water Proof
- For Marine or Car Door Use
- Polypropylene Cone with Cloth Surround
- Built-In Molded Grill
- Molded ABS Plastic Basket
- 15 Oz. Circuit magnet
- Frequency Response: 100 Hz-18 Khz
- Impedance: 4 Ohms
- Mounting Depth: Only 3"
- White Color Marine Speaker
- Complete Pair with wire & Mounting Hardware
- Cut-out Size: 97 mm



PLMR61W 120 Watts 6.5" Dual Cone White Marine Speakers

- 6.5" Dual Cone Full-Range Speakers
- Completely Waterproof
- For Marine or Car Use
- Polypropylene Cone With Cloth Surround
- Built-in Molded Grill
- Molded ABS Plastic Basket
- 1" Aluminum Voice Coil
- 20oz Circuit Magnet
- Power Handling: 120 Watts Peak
- Frequency Response: 45Hz - 16k Hz
- 4 Ohms Impedance
- Slim Mounting Depth: 2.5"
- Complete with Wires Mounting Hardware
- Cut-out Size: Φ135 mm



PLMR41B 4" Dual Cone Waterproof Stereo Speaker System

- 4" Dual Cone Full range Speakers
- Completely Water Proof
- For Marine or Car Door Use
- Polypropylene Cone with Cloth Surround
- Built-In Molded Grill
- Molded ABS Plastic Basket
- 15 Oz. Circuit magnet
- Frequency Response: 100 Hz-18 Khz
- Impedance: 4 Ohms
- Mounting Depth: Only 3"
- Black Color Marine Speaker
- Complete Pair with wire & Mounting Hardware
- Cut-out Size: 97 mm



PLMR61B 120 Watts 6.5" Dual Cone Black Marine Speakers

- 6.5" Dual Cone Full-Range Speakers
- Completely Waterproof
- For Marine or Car Use
- Polypropylene Cone With Cloth Surround
- Built-in Molded Grill
- Molded ABS Plastic Basket
- 1" Aluminum Voice Coil
- 20oz Circuit Magnet
- Power Handling: 120 Watts Peak
- Frequency Response: 45Hz - 16k Hz
- 4 Ohms Impedance
- Slim Mounting Depth: 2.5"
- Complete with Wires Mounting Hardware
- Cut-out Size: Φ135 mm



PLMR66W 5" High Quality PP Cone & PU Edge 500 Watts Marine Speakers

- Flush-mounted design for boat pre-cut opening
- 5" Woofer PP Cone
- High Impact ABS Ported Enclosure
- 1" Aluminum Voice Coil.
- 500 Watts Max Power.
- Frequency Response: 70--15K HZ (+-3dB).
- Sensitivity: 88dB@1W/M.
- 4 Ohms Impedance.
- Unit Dimensions: 7.75"W x 12"H x 4.5"D



PLMR66B 5" High Quality PP Cone & PU Edge 500 Watts Marine Speakers (Black)

- Flush-mounted design for boat pre-cut opening
- 5" Woofer PP Cone
- High Impact ABS Ported Enclosure
- 1" Aluminum Voice Coil.
- 500 Watts Max Power.
- Frequency Response: 70--15K HZ (+-3dB).
- Sensitivity: 88dB@1W/M.
- 4 Ohms Impedance.
- Unit Dimensions: 7.75"W x 12"H x 4.5"D



PLMR67W 6-1/2" Dual Cone Waterproof Stereo Speaker System

- 6-1/2" Dual Cone Full Range Speakers
- Completely Waterproof
- For Marine or Car Door Use
- Polypropylene Cone w/ Cloth Surround
- Built-In Molded Grill
- Molded ABS Plastic Basket
- 1" Aluminum Voice Coil
- 20 Oz. Circuit Magnet
- Frequency Response: 45-16KHz
- Impedance: 4 Ohms
- Mounting Depth: Only 2"
- Cut-out: Φ 135 mm
- Complete Pair with Wire & Mounting Hardware



PLMR67B 6 1/2" Dual Cone Waterproof Stereo Speaker System

- 6.5" Dual Cone Full Range Speakers
- Completely Waterproof
- For Marine or Car Door Use
- Polypropylene Cone with Cloth Surround
- Built-In Molded Grill
- Molded ABS Basket
- 1" Aluminum Voice Coil
- 20 Oz. Circuit Magnet
- Cut-out Size: Φ 135 mm
- Power Handling: 120 Watts Peak
- Frequency Response: 45-16 KHz
- Impedance: 4 Ohms
- Mounting Depth: Only 1 1/2"
- Complete Pair with Wire & Mounting Hardware



PLMR62 200 Watts 6.5" 2 Way White Marine Speakers

- 6.5" High Quality Poly Carbon Cone
- 2-Way Water Resistant Construction Design
- 1" High Temperature Voice Coil
- 1/2" Neodymium Dome Tweeter
- 200 Watts Rated Peak Power
- Frequency Response: 85Hz-20K Hz
- 4 Ohm Impedance
- Sensitivity: 90dB
- Mounting Depth: 2.5"
- Cut-out Size: Φ 135 mm



PLMR692 260 Watts 6" x 9" 2 Way White Marine Speakers

- 6" x 9" High Quality Poly Carbon Cone
- 2-Way Water Resistant Construction Design
- 40 oz Magnet Structure
- 1.5" High Temperature Voice Coil
- 1/2" Neodymium Dome Tweeter
- 260 Watts Peak Power
- Frequency Response: 55-20 KHz
- 4 Ohm Impedance
- Sensitivity: 92 dB
- Mounting Depth: 3.45"
- Cut-out Size: Ellipse, 225mmx152mm



2013 Complete Product Catalog

PLMR82 300 Watts 8" 2 Way White Marine Speakers

- 8" High Quality Poly Carbon Cone
- 2-Way Water Resistant Construction Design
- 1.5" High Temperature Voice Coil
- 0.5" Neodymium Dome Tweeter
- 300 Watts Rated Peak Power
- Frequency Response: 60Hz-20K Hz
- 4 Ohm Impedance
- Sensitivity: 91 dB
- Mounting Depth: 3.25"
- Cut-out Size: Φ 182 mm



PLMR67 250 Watts 6.5" 2 Way Marine Speakers

- 6.5" High Quality White Polypropylene Cone
- Santoprene Surround
- Water-Resistant Construction
- 2 Way Attachable Grille Design
- 1" High Temperature Kapton Voice Coil
- .75" Neodymium Dome Tweeter
- 35 Oz Magnet Structure
- 250 Watts Rated Peak Power
- Frequency Response: 65Hz-20K Hz
- 4 Ohm Impedance
- Sensitivity: 90dB
- Includes Custom Grills, Mounting Gasket, Installation Hardware
- Mounting Depth: 2.55"
- Cut-out Size: Φ 142 mm



PLMR69 300 Watts 6" x 9" 2 Way Marine Speakers

- 6" x 9" High Quality White Polypropylene Cone
- Santoprene Surround
- Water-Resistant Construction
- 2 Way Attachable Grille Design
- 1.25" High Temperature Kapton Voice Coil
- 1" Neodymium Dome Tweeter
- 70 Oz Magnet Structure
- 300 Watts Rated Peak Power
- Frequency Response: 50Hz-20K Hz
- 4 Ohm Impedance
- Sensitivity: 93dB
- Includes Custom Grills, Mounting Gasket, Installation Hardware
- Mounting Depth: 3.35"



PLMR77 280 Watts 7.7" 2 Way Marine Speakers

- 7.7" High Quality White Polypropylene Cone
- Santoprene Surround
- Water-Resistant Construction
- 2 Way Attachable Grille Design
- 1" High Temperature Kapton Voice Coil
- 0.75" Neodymium Dome Tweeter
- 50 Oz Magnet Structure
- 280 Watts Rated Peak Power
- Frequency Response: 60Hz-20K Hz
- 4 Ohm Impedance
- Sensitivity: 92dB
- Includes Custom Grills, Mounting Gasket, Installation Hardware
- Mounting Depth: 2.95"



PLMR5K 180 Watts 5.25" 2-Way Marine Component System

- This Custom Kit Contains:
- One Pair 5.25" Mid Bass Speaker
- One Pair 5.25" Mid Bass Speaker:
- 5.25" High Quality Poly Carbon Cone
- Water Resistant Construction Design
- 1" High Temperature Voice Coil
- 90 Watts RMS/180 Watts Peak Power
- Frequency Response: 100Hz-7K Hz
- 4 Ohm Impedance
- Mounting Depth: 2.15"
- One Pair 1" Tweeter:
- 1" PEI Dome Tweeter
- Neodymium Magnet
- 2 Mounting Options: Flush / Surface Mount
- 50 Watts RMS / 100 Watts Peak
- Frequency Response: 1.4-24KHz
- Impedance: 4 Ohms
- One Pair Passive Crossover Network:
- Two - Way Passive Crossover
- Water Proof ABS Protective Hosing
- Direct Connect Woofer and Tweeter Wiring
- 12dB Octave Slope
- Impedance: 4 Ohm
- Accessories**
- Includes Grills Wires Installation Hardware
- Wiring Kit
- Wiring Diagram Template
- Cut-out Size: Φ 111 mm



PLMR6K 200 Watts 6.5" 2-Way Marine Component System

- This Custom Kit Contains
- One Pair 6.5" Mid Bass Speaker
- 6.5" High Quality Poly Carbon Cone
- Water Resistant Construction Design
- 1" High Temperature Voice Coil
- 100 Watts RMS/ 200 Watts Peak Power
- Frequency Response: 85Hz-6K Hz
- 4 Ohm Impedance
- Mounting Depth: 2.45"
- One Pair 1" Tweeter:
- 1" PEI Dome Tweeter
- Neodymium Magnet
- 2 Mounting Options: Flush / Surface Mount

- 50 Watts RMS / 100 Watts Peak
 - Frequency Response: 1.4-24KHz
 - Impedance: 4 Ohms
 - Two - Way Passive Crossover
 - Water Proof ABS Protective Hosing
 - Direct Connect Woofer and Tweeter Wiring
 - 12dB Octave Slope
 - Impedance: 4 Ohm
- Accessories**
- Includes Grills Wires Installation Hardware
 - Wiring Kit
 - Wiring Diagram Template
 - Cut-out Size: $\Phi 135$ mm



PLMR65C 250 Watts 6.5" 2-Way Custom Marine Component System

- This Custom Kit Contains:
- One Pair 6.5" Mid Bass Speaker
- 6.5" High Quality White Polypropylene Cone
- Santoprene Surround
- Water-Resistant Construction
- 2 Way Attachable Grille Design
- 1" High Temperature Kapton Voice Coil
- 40 Oz Magnet Structure
- 250 Watts Rated Peak Power
- Frequency Response: 60Hz-20K Hz
- 4 Ohm Impedance
- Sensitivity: 91dB

- Mounting Depth: 2.60"
 - One Pair 1" Tweeter:
 - 1" Neodymium Dome Tweeter
 - Flush and Angled Surface Mount Capabilities
 - Impedance: 4 Ohm
 - One Pair Passive Crossover Network:
 - Two - Way Passive Crossover
 - Impedance: 4 Ohm
- Accessories**
- Includes Grills Wires Installation Hardware
 - Wiring Kit
 - Wiring Diagram Template



PLMR51W 100 Watts 5.25" 2 Way White Marine Speakers

- 5.25" Dual Cone Full-Range Speakers
- 100 Watts Rated Power
- Completely Waterproof
- For Marine or Car Use
- Polypropylene Cone w/Cloth Surround
- Built-in Molded Grill
- Molded ABS Plastic Basket

- 20oz Circuit Magnet
- Frequency Response: 100Hz - 18k Hz
- 4 Ohms Impedance
- Slim Mounting Depth: 1.5"
- Complete with Wires Mounting Hardware
- Cut-out Size: $\Phi 122$ mm



PLMR51B 100 Watts 5.25" 2 Way Black Marine Speakers

- 5.25" Dual Cone Full-Range Speakers
- 100 Watts Rated Power
- Completely Waterproof
- For Marine or Car Use
- Polypropylene Cone w/Cloth Surround
- Built-in Molded Grill
- Molded ABS Plastic Basket

- 20oz Circuit Magnet
- Frequency Response: 100Hz - 18k Hz
- 4 Ohms Impedance
- Slim Mounting Depth: 1.5"
- Complete with Wires Mounting Hardware
- Cut-out Size: $\Phi 122$ mm



PLMR52 150 Watts 5.25" 2 Way White Marine Speakers

- 5-1/4" High Quality Poly Carbon Cone
- 2-Way Water Resistant Construction Design
- 1" High Temperature Voice Coil
- 1/2" Neodymium Dome Tweeter
- 150 Watts Rated Peak Power

- Frequency Response: 100Hz-20K Hz
- 4 Ohm Impedance
- Mounting Depth: 2.25"
- Cut-out Size: $\Phi 111$ mm



2013 Complete Product Catalog

PLMR57W 5 1/4" Dual Cone Waterproof Stereo Speaker System

- 5.25" Dual Cone Full Range Speakers
- 100 Watt Rated Peak Power
- Completely Waterproof
- For Marine or Car Door Use
- Polypropylene Cone w/ Cloth Surround
- Built-In Molded Grill
- Molded ABS Plastic Basket
- 20 Oz. Circuit Magnet
- Frequency Response: 100Hz-18Khz
- Cut-Out: Φ 122 mm
- Impedance: 4 Ohms
- Mounting Depth: Only 2"
- Complete Pair with Wire & Mounting Hardware



PLMR60W 150 Watts 6.5" 2 Way White Marine Speakers

- 6.5" Dual Cone Full-Range Speakers
- Completely Waterproof
- For Marine or Car Use
- Polypropylene Cone With Cloth Surround
- Built-in Molded Grill
- Cut-out Size: Φ 135 mm
- Molded ABS Plastic Basket
- 1" Aluminum Voice Coil
- 20oz Circuit Magnet
- Power Handling: 150 Watts Peak
- Frequency Response: 45Hz - 16k Hz
- 4 Ohms Impedance
- Complete with Wires Mounting Hardware
- Mounting Depth: 2.5"



PLMR60B 6 1/2" Dual Cone Waterproof Stereo Speaker System

- 6.5" Dual Cone Full Range speakers
- Completely Waterproof
- For Marine or Car Door Use
- Cut-out Size: Φ 135 mm
- Polypropylene Cone with Cloth Surround
- Built-In Molded Grill
- Molded ABS Basket
- 1" Aluminum Voice Coil
- 20 Oz. Circuit Magnet
- Power handling: 150 Watts Peak
- Frequency Response: 45-16KHz
- Impedance: 4 Ohms
- Mounting Depth: Only 1 1/2"



PLMR605W 6 1/2" Dual Cone Marine Speakers (White)

- 4 Ohm Impedance
- Sensitivity: 90dB
- 1" Aluminum Voice Coil
- 1/2" Neodymium Dome Tweeter
- Frequency Response: 85Hz-20Khz
- 400 Watts Peak Power/ 200 Watt RMS
- Marine Coated Completely Waterproof
- 6.5" Dual Cone 2-way Full Range Speakers
- Polypropylene Cone with Butyl Rubber Surround
- Complete Pair with Grill and Mounting Hardware
- For Marine, RV, ATV, Automotive, & Motorcycle Use

NEW!
for 2013



PLMR605B 6 1/2" Dual Cone Marine Speakers (Black)

- 6.5" Dual Cone 2-way Full Range Speakers
- 400 Watts Peak Power/ 200 Watts RMS
- Marine Coated Completely Waterproof
- For Marine, RV, Automotive, & Motorcycle Use
- Polypropylene Cone with Butyl Rubber Surround
- 1" Aluminum Voice Coil
- 1/2" Neodymium Dome Tweeter
- Frequency Response: 85Hz-20Khz
- Sensitivity: 90dB
- 4 Ohm Impedance
- Complete Pair with Grill and Mounting Hardware

NEW!
for 2013



PLMR60S 150 Watts 6.5" 2 Way Marine Speakers (Silver)

- 6.5" Dual Cone Full-Range Speakers
- Completely Waterproof
- For Marine or Car Use
- Polypropylene Cone With Cloth Surround
- Built-in Molded Grill
- Cut-out Size: Φ 135 mm
- Molded ABS Plastic Basket
- 1" Aluminum Voice Coil
- 20oz Circuit Magnet
- Power Handling: 150 Watts Peak
- Frequency Response: 45Hz - 16k Hz
- 4 Ohms Impedance
- Complete with Wires Mounting Hardware
- Mounting Depth: 2.5"
- Sold as Pair



PLMR24S 3.5" 200 Watt 3-Way Weather Proof Mini Box Speaker System (Silver)

- Excellent for Use On Boats/Marine/Decks/Poolside/ Outdoors
- Completely Water Proof
- 3.5" Aluminum Injection Cone Woofer
- 24 Oz. Magnet Structure
- 1.75" Wide Dispersion Cone Midrange
- 1" Super Dome Tweeter
- Capacitor Crossover Network
- Bass Reflex Vent for Added Bass Response

- Heavy Duty ASB Construction
- Quick Connect / Disconnect Speaker Terminals
- Removable Rustproof of Mesh Grills
- Power: 100 Watts RMS / 200 Watts Peak
- Frequency Response: 70-21 Khz
- Impedance: 4 Ohms
- Complete Mounting Kit Wires
- Dimensions: 5.25"W x 3.75"H x 3.75"D



PLMR24 3.5" 200 Watt 3-Way Weather Proof Mini Box Speaker System (White)

- Excellent for Use On Boats/Marine/Decks/Poolside/ Outdoors
- Completely Water Proof
- 3.5" Aluminum Injection Cone Woofer
- 24 Oz. Magnet Structure
- 1.75" Wide Dispersion Cone Midrange
- 1" Super Dome Tweeter
- Capacitor Crossover Network
- Bass Reflex Vent for Added Bass Response

- Heavy Duty ASB Construction
- Quick Connect / Disconnect Speaker Terminals
- Removable Rustproof of Mesh Grills
- Power: 100 Watts RMS / 200 Watts Peak
- Frequency Response: 70-21 Khz
- Impedance: 4 Ohms
- Complete Mounting Kit Wires
- Dimensions: 5.25"W x 3.75"H x 3.75"D



PLMR24B 3.5" 200 Watt 3-Way Weather Proof Mini Box Speaker System (Black)

- Excellent for Use On Boats/Marine/Decks/Poolside/ Outdoors
- Completely Water Proof
- 3.5" Aluminum Injection Cone Woofer
- 24 Oz. Magnet Structure
- 1.75" Wide Dispersion Cone Midrange
- 1" Super Dome Tweeter
- Capacitor Crossover Network
- Bass Reflex Vent for Added Bass Response

- Heavy Duty ASB Construction
- Quick Connect / Disconnect Speaker Terminals
- Removable Rustproof of Mesh Grills
- Power: 100 Watts RMS / 200 Watts Peak
- Frequency Response: 70-21 Khz
- Impedance: 4 Ohms
- Complete Mounting Kit Wires
- Dimensions: 5.25"W x 3.75"H x 3.75"D



PLMR25 4" 300 Watt 3-Way Weather Proof Mini Box Speaker System (White)

- Excellent for Use On Boats/Marines/Decks/Patios/ Poolside/Outdoors
- Completely Water Proof
- 4" P.P Injection Cone Woofer
- 30 Oz. Magnet Structure
- 1.75" Wide Dispersion Cone Midrange
- Super Dome Tweeter
- Capacitor Crossover Network
- Bass Reflex Vent for Added Bass Response

- Heavy Duty ASB Construction
- Quick Connect/Disconnect Speaker Terminals
- Removable Rustproof Mesh Grills
- Power: 150Watts RMS/300Watts Peak
- Frequency Response: 60-21K Hz
- Impedance: 4 Ohms
- Complete Mounting Kit & Wires
- Dimensions: 5.6"(W) x 8.4"(H) x 4.8"(D)



PLMR26 5" 500 Watt 3-Way Weather Proof Mini Box System (White)

- Excellent for Use On Boats/Marines/ Decks/Patios/Poolside/Outdoors
- Completely Water Proof
- 5" P.P Injection Cone Woofer
- 40 Oz. Magnet Structure
- 1.75" Wide Dispersion Cone Midrange
- 1" Super Dome Tweeter
- Capacitor Crossover Network
- Bass Reflex Vent for Added Bass Response

- Heavy Duty ASB Construction
- Quick Connect/Disconnect Speaker Terminals
- Removable Rustproof Mesh Grills
- Power: 250 Watts RMS/500Watts Peak
- Frequency Response: 50-21K Hz
- Impedance: 4 Ohms
- Complete Mounting Kit & Wires
- Dimensions: 6"(W) x 9"(H) x 4.8"(D)



PLMR34 3.5" 200 Watt Two Way Sealed Speaker System

- Excellent for Monitor or Surround Sound Applications
- 3.5" Long Throw Woofer
- 1" Polymer Dome Tweeter
- 200 Watts Rated Peak Power
- Frequency Response: 100Hz-20k Hz
- 8 Ohm Impedance
- Vented Design For High Power and Deep Bass Response
- Heavy Duty Plastic Cabinet
- Gold Plated Plug Terminals
- Spring Loaded Mounting Bracket Included
- Dimensions: 5.35"W x 7.95"H x 5"D



PLMR44 4" 250 Watt Two Way Sealed Speaker System

- Excellent for Monitor or Surround Sound Applications
- 4" Long Throw Woofer
- 1" Polymer Dome Tweeter
- 250 Watts Rated Peak Power
- Frequency Response: 90Hz-20k Hz
- 8 Ohm Impedance
- Vented Design For High Power and Deep Bass Response
- Heavy Duty Plastic Cabinet
- Gold Plated Plug Terminals
- Spring Loaded Mounting Bracket Included
- Dimensions: 6.95"W x 10.15"H x 6.15"D



PLMR54 5.25" 300 Watt Two Way Sealed Speaker System

- Excellent for Monitor or Surround Sound Applications
- 5.25" Long Throw Woofer
- 1" Polymer Dome Tweeter
- 300 Watts Rated Peak Power
- Frequency Response: 75Hz-20k Hz
- 8 Ohm Impedance
- Vented Design For High Power and Deep Bass Response
- Heavy Duty Plastic Cabinet
- Gold Plated Plug Terminals
- Spring Loaded Mounting Bracket Included
- Dimensions: 7.35"W x 10.65"H x 6.5"D



PLMR53 5.25" 150 Watt Two-Way Shielded Marine Water Proof Speakers

- 5.25" Shielded Two-Way Speakers
- Excellent For Monitor or Surround Sound Applications
- Water Resistant Construction Design
- 5.25" Poly Mica Woofer Cone With Butyl Rubber Surround
- 25oz Shielded Magnet Structure
- 1.0" Polymer Dome Tweeter
- 150 Watts Rated Peak Power
- Frequency Response: 80Hz - 20k Hz
- 4 Ohms Impedance
- For Marine or Car Use
- Built-in Molded Grill
- Gold Plated Plug Terminals
- Threaded Rear Mounting Pos
- Molded White ABS Plastic Basket
- Complete with Wires
- Dimensions: 6.25"W x 6.25"H x 4.15"L



PLMR63 6.5" 200 Watt Two-Way Shielded Marine Water Proof Speakers

- 6.5" Shielded Two-Way Speakers
- Excellent For Monitor or Surround Sound Applications
- Water Resistant Construction Design
- 6.5" Poly Mica Woofer Cone With Butyl Rubber Surround
- 30oz Shielded Magnet Structure
- 1.0" Polymer Dome Tweeter
- 200 Watts Rated Peak Power
- Frequency Response: 70Hz - 20k Hz
- 4 Ohms Impedance
- For Marine or Car Use
- Built-in Molded Grill
- Gold Plated Plug Terminals
- Built-In Spring Loaded Rear Mounting Hook
- Molded White ABS Plastic Basket
- Complete with Wires
- Dimensions: 7.35"W x 7.35"H x 5.35"L



PLMRBS8 8-Inch Low-Profile Super Slim Active Amplified Marine/Waterproof Subwoofer System

- 8" Slim marine woofer
- RCA low level input
- High level input
- Green & red LED power status indicator
- Remote level control
- Phase shift switch: 0 or 180°
- Adjustable input sensitivity: 0.2V-3V
- 0 to +12dB variable Bass Boost (@45Hz)
- Low pass filter (50-150 Hz)
- Soft delay remote turn-on
- Thermal, short and overload protection circuits
- Fuse: 2x15A
- Max power: 600 Watts
- Dimension: 14.5" X9.5" X 3"
- Weight: 10.5 LBS.



PLMRBS10 10" 1000 Watts Low-Profile Super Slim Active Amplified Marine/Waterproof Subwoofer System

- 10" Slim Marine Woofer
- RCA Low Level Input
- High Level Input
- Green and Red LED Power Status Indicator
- Remote Level Control
- Phase Shift Switch : 0 or 180°
- Adjustable Input Sensitivity : 0.2V-3V
- 0 to +12Db Variable Bass Boost (@ 45Hz)
- Low Pass Filter (50-150 Hz)
- Soft Delay Remote Turn-On
- Thermal , Short and Overload Protection Circuits
- Fuse : 2 x 20A
- Max Power : 1000 Watts
- RMS Power of Amplifier : 100 Watts
- Dimension : 15" (L) x 11.8"(W) x 3"(H)
- Weight : 15.5 LBS



PLMRW8 8" 400 Watt White 4 Ohm Marine Subwoofer

- 8" High Quality Polypropylene Cone
- Water Resistant Construction Design
- 40 oz Magnet Structure
- 1.5" High Temperature Voice Coil
- 400 Watts Peak Power
- Frequency Response: 35-3.5K Hz
- 4 Ohm Impedance
- Sensitivity: 91 dB
- Overall Diameter: 8.5"
- Mounting Depth: 3.60"



PLMRW10 10" 500 Watt White 4 Ohm Marine Subwoofer

- 10" High Quality Polypropylene Cone
- Water Resistant Construction Design
- 50 oz Magnet Structure
- 1.5" High Temperature Voice Coil
- 500 Watts Peak Power
- Frequency Response: 25-2.5K Hz
- 4 Ohm Impedance
- Sensitivity: 93 Db
- Overall Diameter: 10.6"
- Mounting Depth: 4.60"



PLMRW12 12" 600 Watt White 4 Ohm Marine Subwoofer

- 12" High Quality Polypropylene Cone
- Water Resistant Construction Design
- 60 Oz Magnet Structure
- 2" High Temperature Voice Coil
- 600 Watts Peak Power
- Frequency Response: 20-2.2K Hz
- 4 Ohm Impedance
- Sensitivity: 95 Db
- Overall Diameter: 12.7"
- Mounting Depth: 5.25"



PLMRW124 12" 1000 Watt White 4 Ohm Marine Subwoofer

- 12" High Quality White Polypropylene Cone
- Santoprene Surround
- Water-resistant Construction
- 2 Way Attachable Grille Design
- 2" High Temperature TIL Voice Coil
- 80 Oz Magnet Structure
- 1000 Watts Rated Peak Power
- Frequency Response: 28Hz-2.5K Hz
- 4 Ohm Impedance
- Fs:30, Qms:7.406, Qes:0.699, Qts:0.639, X-Max(mm):8.9 Vas (Cu ft)2.53
- Sensitivity: 92dB
- Overall Diameter: 12 7/8"
- Mounting Depth: 5 5/8"





1600 63rd Street . Brooklyn . NY 11204 . 718 535-1800 . Fax: 718 236-2400



Like Us On:



PYLE®

Visit Us @ pyleaudio.com